



ALPINA					
ALPINA D3 (G20)					
B 1	S	05/20 – /	261 kW	14-292408	with electronic suspension control
B 4 DTC	S	05/20 – /	261 kW	23-305069 23-305076	20-303334 with electronic suspension control FA: 23-305076; 23-305069
B 6 DTC	S	05/20 – /	261 kW	23-305106 23-305113	20-303426 with electronic suspension control FA: 23-305113; 23-305106
ES	S	05/20 – /	261 kW	47-304932	with standard chassis; only in connection with 14-292408; Conditions see certificates FA: Lowering ca. [mm]: 25-50 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 20-55 mm; Axle load [kg] to 1345 kg
ESE DTC	S	05/20 – /	261 kW	49-305135	Conditions see certificates; with electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 15-35 mm; Axle load [kg] to 1170 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1365 kg
ET1	S	05/20 – /	261 kW	48-304979	only in connection with 14-292408; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1170 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1365 kg; Lowering ca. [mm]: 25-45 mm
ET2	S	05/20 – /	261 kW	48-313070	only in connection with 14-292408; Conditions see certificates; without electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1170 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1365 kg
ER	S	05/20 – /	261 kW	89-312780	with standard chassis; without roadworthy certificate; not permitted on public roads; with suspension strut support bearing FA: Lowering ca. [mm]: 30-70 mm RA: Lowering ca. [mm]: 20-60 mm

ALPINA D3 Touring (G21)

B 1	S	05/20 – /	261 kW	14-292408	with electronic suspension control
B 4 DTC	S	05/20 – /	261 kW	23-305069 23-305076	20-303334 with electronic suspension control FA: 23-305076; 23-305069
B 6 DTC	S	05/20 – /	261 kW	23-305106 23-305113	20-303426 with electronic suspension control FA: 23-305113; 23-305106
ES	S	05/20 – /	261 kW	47-304932	with standard chassis; only in connection with 14-292408; Conditions see certificates FA: Lowering ca. [mm]: 25-50 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 20-55 mm; Axle load [kg] to 1345 kg
ESE DTC	S	05/20 – /	261 kW	49-305135	Conditions see certificates; with electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 15-35 mm; Axle load [kg] to 1170 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1365 kg
ET1	S	05/20 – /	261 kW	48-304979	only in connection with 14-292408; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1170 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1365 kg; Lowering ca. [mm]: 25-45 mm
ET2	S	05/20 – /	261 kW	48-313070	only in connection with 14-292408; Conditions see certificates; without electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1170 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1365 kg
ER	S	05/20 – /	261 kW	89-312780	with standard chassis; without roadworthy certificate; not permitted on public roads; with suspension strut support bearing FA: Lowering ca. [mm]: 30-70 mm RA: Lowering ca. [mm]: 20-60 mm

AUDI
AUDI A3 Sportback (8VA, 8VF)

B 1	1.4 TFSI e-tron 05/14 – 10/20	150 kW	11-305934		from CH-No.: 8V-D-000 001→; Rigid Axle; without lowered chassis
B 1	1.4 TFSI e-tron 05/14 – 10/20	150 kW	11-305965		Multilink Axle; for PR number: UA3; for PR number: UA7
B 1	1.4 TFSI e-tron 05/14 – 10/20	150 kW	11-305965		01/17→; Multilink Axle; for PR number: UA6
B 1	1.4 TFSI e-tron 05/14 – 10/20	150 kW	12-281442		for PR number: OK0; for PR number: 1JA; for PR number: 1JC
B 1	1.4 TFSI e-tron 05/14 – 10/20	150 kW	12-281459		→08/16; Independent wheel suspension; without electronic suspension control






A

AUDI				
AUDI A3 Sportback (8YA)				
B 1	30 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSIle, 45 TFSIle 04/20 - / 81 - 110 kW	14-292330		with electronic suspension control
B 6	30 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSIle, 45 TFSIle 04/20 - / 81 - 110 kW	35-229872 $\frac{1}{2}$ \times	24-267137 $\frac{1}{2}$ \circ	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
B12 PK	45 TFSIle 07/21 - / 110 kW	46-340122		without electronic suspension control; Conditions see certificates; Strut outside diameter [mm] 55mm; Multilink Axle FA: Axle load [kg] to 1080 kg; Lowering ca. [mm]: 35-40 mm RA: Axle load [kg] to 1075 kg; Lowering ca. [mm]: 40 mm
AUDI A3 Limousine (8YS)				
B 6	30 TFSI Mild Hybrid, 35 TFSI Mild Hybrid 04/20 - / 81 - 110 kW	35-229872 $\frac{1}{2}$ \times	24-267137 $\frac{1}{2}$ \circ	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
AUDI A4 B5 Avant (8D5)				
B 1	1.9 Hybrid 03/98 - 06/00 66 kW	11-267959	PK	with standard chassis
B 1	1.9 Hybrid 03/98 - 06/00 66 kW	12-117642		FA: Steel Elastomer; without ball bearing
B 4	1.9 Hybrid 03/98 - 06/00 66 kW	22-031167 $\frac{1}{2}$ $\frac{1}{2}$	19-105376 $\frac{1}{2}$ \circ	08/97-01/99; with standard chassis RA: Length [mm]: 602 mm
B 4	1.9 Hybrid 03/98 - 06/00 66 kW	22-031167 $\frac{1}{2}$ $\frac{1}{2}$	19-103471 $\frac{1}{2}$ \circ	02/99-06/00; CH-No.: 8D-X-200001-8D-1-030000; with standard chassis RA: Length [mm]: 638 mm
AUDI A4 B9 (8W2, 8WC)				
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 - 11/19 100 - 255 kW	24-262330 $\frac{1}{2}$ \times	24-262347 $\frac{1}{2}$ \circ	with standard chassis; For vehicles with comfort suspension; Monotube; for PR number: 1BA; for PR number: 1BM; without electronic suspension control FA: serie production spring seat must be used
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 - 11/19 100 - 195 kW	24-303828 $\frac{1}{2}$ \times	24-262347 $\frac{1}{2}$ \circ	with standard chassis; For vehicles with comfort suspension; Monotube; for PR number: 1BA; for PR number: 1BM; without electronic suspension control
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 - 11/19 100 - 255 kW	24-275019 $\frac{1}{2}$ \times	24-279697 $\frac{1}{2}$ \circ	with sports suspension; for PR number: 1BE; for PR number: 1BD; without electronic suspension control FA: serie production spring seat must be used
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 - 11/19 100 - 255 kW	24-279451 $\frac{1}{2}$ \times	24-279697 $\frac{1}{2}$ \circ	with sports suspension; without electronic suspension control; for PR number: 1BD; for PR number: 1BE FA: serie production spring seat must be used
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 - 11/19 100 - 255 kW	19-262352 $\frac{1}{2}$ \times	19-262369 $\frac{1}{2}$ \circ	with off-road suspension; Twin-Tube; For vehicles with comfort suspension; for PR number: 1BP; for PR number: 1BR; without electronic suspension control FA: serie production spring seat must be used


















AUDI				
AUDI A4 B9 (8W2, 8WC)				
B 4 DTC	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	26-296012	26-296029	with electronic suspension control
B 6	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	24-274869	24-262293	with standard chassis; without electronic suspension control; for PR number: 1BA; for PR number: 1BM; without off-road suspension FA: serie production spring seat must be used
B 6	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	24-262286	24-262293	with standard chassis; without electronic suspension control; for PR number: 1BA; for PR number: 1BM; without off-road suspension FA: serie production spring seat must be used
B 6	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	24-300612	24-300629	with off-road suspension
B 6 DTC	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	26-296036	26-296043	with electronic suspension control
B 8	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	24-274876	24-262323	with sports suspension; without electronic suspension control; for PR number: 1BE; for PR number: 1BD FA: serie production spring seat must be used
B 8	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	24-262309	24-262323	without electronic suspension control; with sports suspension; for PR number: 1BE; for PR number: 1BD FA: serie production spring seat must be used
B12 PK	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 195 kW	46-275349		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1180 kg
B12 PK	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 11/19 100 – 185 kW	46-334459		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1180 kg
B12 PK	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 11/19 100 – 185 kW	46-334480		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1060 kg RA: Axle load [kg] to 1180 kg
B12 PK	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 195 kW	46-278647		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1180 kg

			
AUDI			
AUDI A4 B9 (8W2, 8WC)			
B12 PK	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 11/19 120 – 185 kW	46-332844	Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1220 kg
B12 PK	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 07/18 – 11/19 150 – 180 kW	46-332851	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1220 kg
B12 PK	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/17 – 11/19 150 – 195 kW	46-334503	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1220 kg
B12 PK	40 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/20 – / 150 kW	46-334510	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1220 kg
B12 PK	50 TDI Mild Hybrid quattro 08/20 – / 210 kW	46-332998	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1265 kg RA: Axle load [kg] to 1220 kg
B12 PK	50 TDI Mild Hybrid quattro 08/20 – / 210 kW	46-334558	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1265 kg RA: Axle load [kg] to 1220 kg
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 195 kW	46-334565	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1180 kg
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 11/19 100 – 185 kW	46-333001	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1180 kg
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 11/19 100 – 185 kW	46-334572	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1195 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1180 kg
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 11/19 110 – 185 kW	46-333018	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1195 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 07/18 – 11/19 150 – 180 kW	46-333179	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1195 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/17 – 11/19 150 – 195 kW	46-333025	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/17 – 11/19 150 – 195 kW	46-334633	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro 05/17 – 11/19 150 – 210 kW	46-334640	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1195 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B16 PSS10	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	48-275071	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 35-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg
B16 PSS10	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 255 kW	48-262316	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 35-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg



AUDI			
AUDI A4 B9 (8W2, 8WC)			
B16 DTC	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 11/19 100 – 195 kW	49-290868	with electronic suspension control; without leveling control; Conditions see certificates FA: Axle load [kg] to 1260 kg; Lowering ca. [mm]: 10-35 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 15-35 mm
B16 DTC	50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/19 – / 210 – 255 kW	49-290868	with electronic suspension control; without leveling control; Conditions see certificates FA: Axle load [kg] to 1260 kg; Lowering ca. [mm]: 5-20 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 10-20 mm

AUDI A4 B9 Avant (8W5, 8WD)				
B 4	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-262330	24-262347	with standard chassis; For vehicles with comfort suspension; Monotube; for PR number: 1BA; for PR number: 1BM; without electronic suspension control FA: serie production spring seat must be used
B 4	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-303828	24-262347	with standard chassis; For vehicles with comfort suspension; Monotube; for PR number: 1BA; for PR number: 1BM; without electronic suspension control
B 4	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-275019	24-279697	with sports suspension; for PR number: 1BE; for PR number: 1BD; without electronic suspension control FA: serie production spring seat must be used
B 4	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-275019		with sports suspension; without electronic suspension control; for PR number: 1BE; for PR number: 1BD; Monotube FA: serie production spring seat must be used
B 4	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-279451	24-279697	with sports suspension; without electronic suspension control; for PR number: 1BD; for PR number: 1BE FA: serie production spring seat must be used
B 4	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	19-262352	19-262369	with off-road suspension; Twin-Tube; For vehicles with comfort suspension; for PR number: 1BP; for PR number: 1BR; without electronic suspension control FA: serie production spring seat must be used
B 4	40 TFSI Mild Hybrid 05/17 – 10/19 140 kW	24-275019		with sports suspension; without electronic suspension control; for PR number: 1BE; for PR number: 1BD; Monotube FA: serie production spring seat must be used
B 4 DTC	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	26-296012	26-296029	with electronic suspension control

				
AUDI				
AUDI A4 B9 Avant (8W5, 8WD)				
B 6	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-274869 	24-262293 	with standard chassis; without electronic suspension control; for PR number: 1BA; for PR number: 1BM; without off-road suspension FA: serie production spring seat must be used
B 6	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-262286 	24-262293 	with standard chassis; without electronic suspension control; for PR number: 1BA; for PR number: 1BM; without off-road suspension FA: serie production spring seat must be used
B 6	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-300612 	24-300629 	
B 6 DTC	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	26-296036 	26-296043 	with electronic suspension control
B 8	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-274876 	24-262323 	with sports suspension; without electronic suspension control; for PR number: 1BE; for PR number: 1BD FA: serie production spring seat must be used
B 8	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 – 10/19 100 – 255 kW	24-262309 	24-262323 	without electronic suspension control; with sports suspension; for PR number: 1BE; for PR number: 1BD FA: serie production spring seat must be used
B12 PK	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 10/19 110 – 185 kW	46-332844		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1220 kg
B12 PK	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 10/19 100 – 185 kW	46-334503		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1220 kg
B12 PK	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 10/19 100 – 185 kW	46-332851		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1220 kg
B12 PK	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 10/19 110 – 185 kW	46-334510		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1220 kg
B12 PK	2.0 TFSI Mild Hybrid quattro, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 07/18 – 10/19 150 – 195 kW	46-333186		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1250 kg
B12 PK	2.0 TFSI Mild Hybrid quattro, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 07/18 – 10/19 150 – 195 kW	46-333193		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1250 kg
B12 PK	50 TDI Mild Hybrid quattro 08/20 – / 210 kW	46-333520		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1265 kg RA: Axle load [kg] to 1250 kg

AUDI			
AUDI A4 B9 Avant (8W5, 8WD)			
B12 PK	50 TDI Mild Hybrid quattro 08/20 - / 210 kW	46-333537	Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1265 kg RA: Axle load [kg] to 1250 kg
B12 SL	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 - 10/19 100 - 185 kW	46-333179	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1195 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid 05/17 - 10/19 110 - 185 kW	46-333025	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 - 10/19 100 - 185 kW	46-334633	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	2.0 TFSI Mild Hybrid, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 - 10/19 100 - 185 kW	46-334640	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1195 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg
B12 SL	2.0 TFSI Mild Hybrid quattro, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 07/18 - 10/19 150 - 195 kW	46-333544	Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1095 kg; Lowering ca. [mm]: 45 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 40 mm
B12 SL	2.0 TFSI Mild Hybrid quattro, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 07/18 - 10/19 150 - 195 kW	46-333551	Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1095 kg; Lowering ca. [mm]: 45 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 40 mm
B12 SL	40 TDI Mild Hybrid quattro 05/20 - / 150 kW	46-333568	Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1195 kg; Lowering ca. [mm]: 45 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 40 mm
B12 SL	40 TDI Mild Hybrid quattro 05/20 - / 150 kW	46-333575	Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1195 kg; Lowering ca. [mm]: 45 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 40 mm
B16 PSS10	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 - 10/19 100 - 255 kW	48-275071	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 35-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg
B16 PSS10	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 - 10/19 100 - 255 kW	48-262316	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 35-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg
B16 DTC	2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S4 TDI Mild Hybrid quattro 05/17 - 10/19 100 - 255 kW	49-290868	with electronic suspension control; without leveling control; Conditions see certificates FA: Axle load [kg] to 1260 kg; Lowering ca. [mm]: 10-35 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 15-35 mm
AUDI A4 Allroad B9 (8WH, 8WJ)			
B 6	45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro 07/18 - 10/19 150 - 210 kW	24-300612	24-300629
AUDI A5 (F53, F5P)			
B 4	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 - 02/20 100 - 255 kW	24-262330	24-262347
B 4	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 - 02/20 100 - 255 kW	24-303828	24-262347



AUDI			
AUDI A5 (F53, F5P)			
B 4	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-275019 ⚡	24-262347 ⚡ with sports suspension; Monotube FA: serie production spring seat must be used
B 4	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	19-262352 ⚡	19-262369 ⚡ with off-road suspension; Twin-Tube FA: serie production spring seat must be used
B 4 DTC	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	26-296012 ⚡	26-296029 ⚡ with electronic suspension control
B 6	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-274869 ⚡	24-262293 ⚡ without electronic suspension control FA: serie production spring seat must be used
B 6	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-262286 ⚡	24-262293 ⚡ without electronic suspension control FA: serie production spring seat must be used
B 6 DTC	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	26-296036 ⚡	26-296043 ⚡ with electronic suspension control
B 8	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-274876 ⚡	24-262323 ⚡ without electronic suspension control FA: serie production spring seat must be used
B 8	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-262309 ⚡	24-262323 ⚡ without electronic suspension control FA: serie production spring seat must be used
B12 PK	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	46-334459 Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 20 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1180 kg	
B12 PK	40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 09/20 – / 150 kW	46-334480 Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1060 kg RA: Axle load [kg] to 1180 kg	
B12 PK	50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 12/18 – 02/20 210 – 255 kW	46-334497 Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1265 kg RA: Axle load [kg] to 1180 kg	
B12 SL	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	46-333001 Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1180 kg	



AUDI				
AUDI A5 (F53, F5P)				
B12 SL	45 TFSI Mild Hybrid quattro, 40 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/17 – 02/20 150 – 195 kW	46-333179		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1195 kg RA: Axle load [kg] to 1220 kg
B12 SL	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	46-334565		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1180 kg
B12 SL	40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro 08/20 – / 150 – 210 kW	46-333018		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1195 kg RA: Axle load [kg] to 1180 kg
B12 SL	40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro 08/20 – / 150 – 210 kW	46-334572		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1195 kg RA: Axle load [kg] to 1180 kg
B16 PSS10	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	48-275071		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg
B16 PSS10	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	48-262316		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg
B16 DTC	45 TFSI Mild Hybrid quattro, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	49-290868		with electronic suspension control; without leveling control; Conditions see certificates FA: Axle load [kg] to 1260 kg; Lowering ca. [mm]: 10-35 mm RA: Axle load [kg] to 1330 kg; Lowering ca. [mm]: 15-35 mm
AUDI A5 Sportback (F5A, F5F)				
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-262330 ⚡	24-262347 ⚡	with standard chassis; For vehicles with comfort suspension; Monotube FA: serie production spring seat must be used
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-303828 ⚡	24-262347 ⚡	with standard chassis; For vehicles with comfort suspension; Monotube
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-275019 ⚡	24-262347 ⚡	with sports suspension; Monotube FA: serie production spring seat must be used
B 4	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	19-262352 ⚡	19-262369 ⚡	with off-road suspension; Twin-Tube FA: serie production spring seat must be used
B 4 DTC	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	26-296012 ⚡	26-296029 ⚡	FA: with sports suspension



A

AUDI				
AUDI A5 Sportback (F5A, F5F)				
B 6	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-274869	24-262293	without electronic suspension control; with standard chassis FA: serie production spring seat must be used
B 6	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-262286	24-262293	without electronic suspension control; with standard chassis FA: serie production spring seat must be used
B 6 DTC	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	26-296036	26-296043	FA: with sports suspension
B 8	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-274876	24-262323	without electronic suspension control; with sports suspension FA: serie production spring seat must be used
B 8	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	24-262309	24-262323	without electronic suspension control; with sports suspension FA: serie production spring seat must be used
B12 PK	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	46-332844		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 20 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1250 kg
B12 PK	40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	46-334503		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 20 mm FA: Axle load [kg] to 1080 kg RA: Axle load [kg] to 1250 kg
B12 PK	40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	46-332851		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 20 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1250 kg
B12 PK	40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 140 – 195 kW	46-334510		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 20 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1250 kg
B12 PK	50 TDI Mild Hybrid quattro 08/20 – / 210 kW	46-332998		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 20 mm FA: Axle load [kg] to 1265 kg RA: Axle load [kg] to 1220 kg
B12 PK	50 TDI Mild Hybrid quattro 08/20 – / 210 kW	46-334558		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1265 kg RA: Axle load [kg] to 1250 kg
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 02/20 110 – 185 kW	46-333001		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1180 kg
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	46-334565		Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1180 kg



AUDI				
AUDI A5 Sportback (F5A, F5F)				
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 02/20 100 – 185 kW	46-333018	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 53mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1195 kg RA: Axle load [kg] to 1180 kg	
B12 SL	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid 05/17 – 02/20 100 – 185 kW	46-334572	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 49mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1195 kg RA: Axle load [kg] to 1180 kg	
B12 SL	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/17 – 02/20 150 – 195 kW	46-333025	Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1220 kg	
B12 SL	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/17 – 02/20 150 – 195 kW	46-334633	Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1220 kg	
B12 SL	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid quattro 05/17 – 02/20 150 – 195 kW	46-334640	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 45 mm; Axle load [kg] to 1195 kg RA: Lowering ca. [mm]: 40 mm; Axle load [kg] to 1220 kg	
B16 PSS10	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	48-275071	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg	
B16 PSS10	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 255 kW	48-262316	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1260 kg RA: Axle load [kg] to 1250 kg	
B16 DTC	35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 02/20 100 – 195 kW	49-290868	with electronic suspension control; without leveling control; Conditions see certificates FA: Axle load [kg] to 1260 kg; Lowering ca. [mm]: 10-35 mm RA: Axle load [kg] to 1330 kg; Lowering ca. [mm]: 15-35 mm	
B16 DTC	50 TDI Mild Hybrid quattro, S5 TDI Mild Hybrid quattro 12/18 – 02/20 210 – 255 kW	49-290868	with electronic suspension control; without leveling control; Conditions see certificates FA: Axle load [kg] to 1260 kg; Lowering ca. [mm]: 5-20 mm RA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 10-20 mm	
AUDI A5 Convertible (F57, F5E)				
B 4	30 TDI MILD HYBRID, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 12/19 100 – 195 kW	24-303828 ⚡	24-302463 ⚡	with standard chassis; For vehicles with comfort suspension; Monotube
B 4 DTC	30 TDI MILD HYBRID, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 12/19 100 – 195 kW	26-296012 ⚡	26-310220 ⚡	FA: with electronic suspension control
B 6	30 TDI MILD HYBRID, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 12/19 100 – 195 kW	24-274869 ⚡	24-302487 ⚡	without electronic suspension control; with standard chassis FA: serie production spring seat must be used
B 6	30 TDI MILD HYBRID, 35 TFSI Mild Hybrid, 40 TFSI Mild Hybrid, 40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 2.0 TFSI Mild Hybrid, 2.0 TFSI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 05/17 – 12/19 100 – 195 kW	24-262286 ⚡	24-302487 ⚡	without electronic suspension control; with standard chassis FA: serie production spring seat must be used
AUDI A6 C7 (4G2, 4GC)				
B 1	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	12-224463	12-276455	FA: without ball bearing RA: Inner diameter [mm]: 10 mm; for PR number: 1BA; for PR number: 1BE; for PR number: 1BR; for PR number: 1BV
B 3	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	36-250158	36-248933	with standard chassis


A

AUDI				
AUDI A6 C7 (4G2, 4GC)				
B 3	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	36-250080	36-248919	with sports suspension
B 4	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	19-226880	11-299899 19-226897	with standard chassis; without leveling control; for vehicles without pneumatic suspension
B 4	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	19-226903	19-226910	with sports suspension; without leveling control; for vehicles without pneumatic suspension
B 4 AMC	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	45-248573	20-264765	for pneumatic suspension vehicles; with electronic suspension control
B 6	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	24-145961	24-145978	with standard chassis; without leveling control; for vehicles without pneumatic suspension
B 8	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	24-145985	24-145992	with sports suspension; without leveling control; for vehicles without pneumatic suspension
B16 PSS10	2.0 TFSI Hybrid 11/11 – 04/15 155 kW	48-221832		disconnect AMM; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1375 kg RA: Axle load [kg] to 1410 kg
AUDI A6 C8 (4A2)				
B 4	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S6 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid quattro 02/18 – / 100 – 331 kW	19-302591	19-303802	with standard chassis; without leveling control
B 4	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S6 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid quattro 02/18 – / 100 – 331 kW	19-302614	19-304397	with sports suspension; without leveling control FA: Outer diameter [mm] 53 mm
B 4	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S6 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid quattro 02/18 – / 100 – 331 kW	19-302607	19-304397	with sports suspension; without leveling control
B 4	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S6 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid quattro 02/18 – / 100 – 331 kW	19-302614	19-303789	with off-road suspension; without leveling control FA: Outer diameter [mm] 53 mm
B 6	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S6 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid quattro 02/18 – / 100 – 331 kW	24-324540	24-324557	
B 6	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S6 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid quattro 02/18 – / 100 – 331 kW		24-324557	



AUDI				
AUDI A6 C8 Avant (4A5)				
B 4	45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 50 TFSI e quattro, 55 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid, S6 TDI Mild Hybrid quattro 05/18 - / 100 - 270 kW	19-302591	19-303796 $\frac{1}{\circ}$	with standard chassis; without leveling control
B 4	45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 50 TFSI e quattro, 55 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid, S6 TDI Mild Hybrid quattro 05/18 - / 100 - 270 kW	19-302607	19-304397 $\frac{1}{\circ}$	with sports suspension; without leveling control
B 4	45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 50 TFSI e quattro, 55 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid, S6 TDI Mild Hybrid quattro 05/18 - / 100 - 270 kW	19-302614	19-303789 $\frac{1}{\circ}$	with off-road suspension; without leveling control FA: Outer diameter [mm] 53 mm
B 4 DTC	45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 50 TFSI e quattro, 55 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid, S6 TDI Mild Hybrid quattro 05/18 - / 100 - 270 kW	26-324609 $\frac{1}{\times}$	26-324616 $\frac{1}{\circ}$	with standard chassis; for coil-spring suspension vehicles
B 6	45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 50 TFSI e quattro, 55 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid, S6 TDI Mild Hybrid quattro 05/18 - / 100 - 270 kW	24-324540 $\frac{1}{\times}$	24-324557 $\frac{1}{\circ}$	with standard chassis; with sports suspension
B 6	45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 50 TFSI e quattro, 55 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid, S6 TDI Mild Hybrid quattro 05/18 - / 100 - 270 kW		24-324557 $\frac{1}{\circ}$	
B 6 DTC	45 TFSI Mild Hybrid, 45 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 50 TFSI e quattro, 55 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 35 TDI Mild Hybrid quattro, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S6 TDI Mild Hybrid, S6 TDI Mild Hybrid quattro 05/18 - / 100 - 270 kW	26-324562 $\frac{1}{\times}$	26-324579 $\frac{1}{\times}$	with sports suspension; for coil-spring suspension vehicles
AUDI A7 Sportback (4KA)				
B 4	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild hybrid quattro, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S7 TFSI Mild Hybrid quattro, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S7 TDI Mild Hybrid quattro 10/17 - / 120 - 331 kW	19-306261		with standard chassis
B 4	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild hybrid quattro, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S7 TFSI Mild Hybrid quattro, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S7 TDI Mild Hybrid quattro 10/17 - / 120 - 331 kW	19-306261	19-303802 $\frac{1}{\circ}$	with standard chassis


A

AUDI				
AUDI A7 Sportback (4KA)				
B 4	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild hybrid quattro, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S7 TFSI Mild Hybrid quattro, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S7 TDI Mild Hybrid quattro 10/17 - / 120 - 331 kW		19-304397	with sports suspension; without leveling control
B 6	40 TFSI Mild Hybrid, 45 TFSI Mild Hybrid, 45 TFSI Mild hybrid quattro, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSI Mild Hybrid quattro, S7 TFSI Mild Hybrid quattro, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 45 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, S7 TDI Mild Hybrid quattro 10/17 - / 120 - 331 kW	24-324540	24-324557	
AUDI A8 D4 (4H2, 4H8, 4HC, 4HL)				
B 4 AMC	2.0 TFSI hybrid 02/12 - 11/15 155 kW	45-248573	45-248580	for pneumatic suspension vehicles; with electronic suspension control
AUDI Q3 (F3B)				
B 1	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	12-243945		with standard chassis FA: without ball bearing
B 1	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW		12-281459	09/18 →; with electronic suspension control
B 4	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	22-267108	19-317939	without electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Length 1 [mm]: 402 mm; Length 2 [mm]: 632 mm
B 4 DTC	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	23-238978	20-267520	with electronic suspension control FA: Strut outside diameter [mm] 55mm; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Multilink Axle
B 6	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	35-229872	24-328029	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
B 6 DTC	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	23-254343	20-267537	with electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Multilink Axle
B12 PK	35 TFSI Mild Hybrid 11/19 - / 110 kW		46-340016	without electronic suspension control; Conditions see certificates; Strut outside diameter [mm] 55mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1100 kg RA: Axle load [kg] to 1095 kg
B16 DTC	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW		49-255874	Strut outside diameter [mm] 55mm; Multilink Axle; Threaded Suspension (height adjustable); with electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: for PR number: G02; for PR number: G04; Axle load [kg] to 1120 kg RA: Axle load [kg] to 1230 kg
ES	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW		47-309067	with standard chassis; Conditions see certificates; Strut outside diameter [mm] 55mm; Multilink Axle FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1200 kg RA: Lowering ca. [mm]: 10-40 mm; Axle load [kg] to 1255 kg
AUDI Q3 Sportback (F3N)				
B 4	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	22-267108	19-317939	without electronic suspension control; with standard chassis FA: Strut outside diameter [mm] 55mm RA: Length 1 [mm]: 402 mm; Length 2 [mm]: 632 mm
B 4 DTC	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	23-238978	20-267520	with electronic suspension control FA: Strut outside diameter [mm] 55mm; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Multilink Axle
B 6	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	35-229872	24-328029	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
B 6 DTC	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - / 110 kW	23-254343	20-267537	with electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Multilink Axle
B12 PK	35 TFSI Mild Hybrid 11/19 - / 110 kW		46-340016	without electronic suspension control; Conditions see certificates; Strut outside diameter [mm] 55mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1100 kg RA: Axle load [kg] to 1095 kg

AUDI					
AUDI Q3 Sportback (F3N)					
B16 DTC	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - /	110 kW		49-255874	Strut outside diameter [mm] 55mm; MultiLink Axle; Threaded Suspension (height adjustable); with electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: for PR number: G02; for PR number: G04; Axle load [kg] to 1120 kg RA: Axle load [kg] to 1230 kg
ES	35 TFSI Mild Hybrid, 45 TFSI e 11/19 - /	110 kW		47-309067	with standard chassis; Conditions see certificates; Strut outside diameter [mm] 55mm; MultiLink Axle FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1200 kg RA: Lowering ca. [mm]: 10-40 mm; Axle load [kg] to 1255 kg
AUDI Q4 SUV (F4B)					
B 4	35 e-tron, 40 e-tron 03/21 - /	125 - 150 kW	22-327123	19-324586	with standard chassis FA: for PR number: 1X2
B 4	45 e-tron quattro, 50 e-tron quattro 03/21 - /	195 - 220 kW	22-330079	19-324586	without electronic suspension control FA: for PR number: 1X1
B 6	35 e-tron, 40 e-tron 03/21 - /	125 - 150 kW	22-330055	24-324595	without electronic suspension control; with sports suspension
B 6	45 e-tron quattro, 50 e-tron quattro 03/21 - /	195 - 220 kW	22-327130	24-324595	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	35 e-tron, 40 e-tron 03/21 - /	125 - 150 kW		47-330108	Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Axle load [kg] to 1210 kg; Lowering ca. [mm]: 25-45 mm RA: Axle load [kg] to 1560 kg; Lowering ca. [mm]: 20-40 mm
ES	45 e-tron quattro, 50 e-tron quattro 03/21 - /	195 - 220 kW		47-327085	with standard chassis; for PR number: 1X1; Conditions see certificates FA: Lowering ca. [mm]: 20-40 mm RA: Lowering ca. [mm]: 25-45 mm
AUDI Q4 Sportback (F4N)					
B 4	35 e-tron, 40 e-tron 06/21 - /	125 - 150 kW	22-327123	19-324586	with standard chassis FA: for PR number: 1X2
B 4	50 e-tron quattro 06/21 - /	220 kW	22-330079	19-324586	with standard chassis FA: for PR number: 1X1
B 6	35 e-tron, 40 e-tron 06/21 - /	125 - 150 kW	22-330055	24-324595	without electronic suspension control; with sports suspension
B 6	50 e-tron quattro 06/21 - /	220 kW	22-327130	24-324595	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	35 e-tron, 40 e-tron 06/21 - /	125 - 150 kW		47-330108	Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Axle load [kg] to 1210 kg; Lowering ca. [mm]: 25-45 mm RA: Axle load [kg] to 1560 kg; Lowering ca. [mm]: 20-40 mm
ES	50 e-tron quattro 06/21 - /	220 kW		47-327085	for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates
AUDI Q5 (8RB)					
B 1	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW		12-228805	without electronic suspension control RA: Steel Elastomer; without ball bearing
B 1	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW	12-228812	12-228805	without ball bearing FA: with electronic suspension control RA: Steel Elastomer
B 1	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW	12-305926		→06/16
B 3	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW		36-240388	with standard chassis
B 4	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW	19-171593	19-171609	with standard chassis; without electronic suspension control
B 6	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW	24-145961	24-145978	without electronic suspension control
B 8	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW	24-145985	24-145992	without electronic suspension control
B16 PSS10	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW		48-246125	with standard chassis; Conditions see certificates; Lowering ca. [mm]: 10-35 mm
B16 PSS10	2.0 TFSI Hybrid quattro 06/11 - 06/16	155 kW		48-246125	Conditions see certificates; Lowering ca. [mm]: 0-10 mm FA: with sports suspension



AUDI			
AUDI Q5 (FYB, FYG)			
B 4	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSi e quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, SQ5 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro 12/18 - / 100 - 270 kW	19-281353	19-281360
B 4	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSi e quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, SQ5 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro, SQ5 TDI Mild Hybrid quattro 12/18 - / 100 - 270 kW	19-283579	19-282237
B 6	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 50 TFSI e quattro, 55 TFSI e quattro, 55 TFSi e quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, SQ5 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro, 50 TDI Mild Hybrid quattro 12/18 - / 100 - 270 kW	19-306650	24-306669
B12 PK	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro 12/18 - / 150 - 195 kW	46-339973	Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1205 kg; Lowering ca. [mm]: 35 mm RA: Axle load [kg] to 1390 kg; Lowering ca. [mm]: 25 mm
B12 PK	40 TFSI Mild Hybrid quattro, 30 TDI Mild Hybrid, 35 TDI Mild Hybrid, 40 TDI Mild Hybrid quattro 09/19 - / 100 - 150 kW	46-339980	Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1275 kg; Lowering ca. [mm]: 35 mm RA: Axle load [kg] to 1390 kg; Lowering ca. [mm]: 25 mm
B12 PK	50 TFSI e quattro, 55 TFSI e quattro, 55 TFSi e quattro 04/19 - / 195 - 270 kW	46-340009	Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1480 kg
AUDI Q5 Van (FYB, FYG)			
B 4	3.0 SQ5 TDI Mild Hybrid quattro 02/19 - 11/20 255 kW	19-281353	19-281360
B 4	3.0 SQ5 TDI Mild Hybrid quattro 02/19 - 11/20 255 kW	19-283579	19-282237
B 6	3.0 SQ5 TDI Mild Hybrid quattro 02/19 - 11/20 255 kW	19-306650	24-306669
AUDI Q5 Sportback (FYT)			
B 4	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 45 TFSI quattro, 50 TFSI e quattro, 55 TFSI e quattro, 35 TDI, 40 TDI quattro, 50 TDI quattro 11/20 - / 120 - 210 kW	19-281353	19-281360
B 4	40 TFSI Mild Hybrid quattro, 45 TFSI Mild Hybrid quattro, 45 TFSI quattro, 50 TFSI e quattro, 55 TFSI e quattro, 35 TDI, 40 TDI quattro, 50 TDI quattro 11/20 - / 120 - 210 kW	19-283579	19-282237
AUDI Q7 (4MB, 4MG)			
B 4	2.0 TFSI e-tron quattro, 55 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 60 TFSI e quattro, 45 TDI Mild Hybrid quattro, 3.0 TDI e-tron quattro, 50 TDI Mild Hybrid quattro 08/15 - 12/19 170 - 335 kW	22-261526	19-261539
B 6	2.0 TFSI e-tron quattro, 55 TFSI Mild Hybrid quattro, 55 TFSI e quattro, 60 TFSI e quattro, 45 TDI Mild Hybrid quattro, 3.0 TDI e-tron quattro, 50 TDI Mild Hybrid quattro 08/15 - 12/19 170 - 335 kW	24-263528	24-263535
AUDI Q7 Van (4MB, 4MG)			
B 4	3.0 45 TDI Mild Hybrid quattro, 3.0 50 TDI Mild Hybrid quattro 07/18 - 12/19 170 - 210 kW	22-261526	19-261539
B 4	3.0 45 TDI Mild Hybrid quattro, 3.0 50 TDI Mild Hybrid quattro 07/18 - 12/19 170 - 210 kW	22-261526	19-261539
B 6	3.0 45 TDI Mild Hybrid quattro, 3.0 50 TDI Mild Hybrid quattro 07/18 - 12/19 170 - 210 kW	24-263528	24-263535

AUDI			
AUDI Q7 Van (4MB, 4MG)			
B 6	3.0 45 TDI Mild Hybrid quattro, 3.0 50 TDI Mild Hybrid quattro 07/18 – 12/19 170 – 210 kW	24-263528 $\frac{1}{\times}$	24-263535 $\frac{1}{\circ}$ without electronic suspension control; for coil-spring suspension vehicles FA: serie production spring seat must be used

AUDI (FAW)			
AUDI (FAW) A6L C7 (4X8, 4XL)			
B 1	40 e-tron 08/17 – 12/18 155 kW	12-224463	12-276455 FA: without ball bearing RA: Inner diameter [mm]: 10 mm; for PR number: 1BA; for PR number: 1BE; for PR number: 1BR; for PR number: 1BV
B 4	40 e-tron 08/17 – 12/18 155 kW	19-226880	19-226897 $\frac{1}{\circ}$ 11-299899 $\frac{1}{\text{PK}}$ with standard chassis; without leveling control; for vehicles without pneumatic suspension
B 4	40 e-tron 08/17 – 12/18 155 kW	19-226903	19-226910 $\frac{1}{\circ}$ with sports suspension; without leveling control; for vehicles without pneumatic suspension
B 4 AMC	40 e-tron 08/17 – 12/18 155 kW	45-248573 $\frac{\infty}{\times}$	20-264765 $\frac{1}{\text{T}}$ for pneumatic suspension vehicles; with electronic suspension control
B 6	40 e-tron 08/17 – 12/18 155 kW	24-145961 $\frac{1}{\times}$	24-145978 $\frac{1}{\circ}$ with standard chassis; without leveling control; for vehicles without pneumatic suspension
B 8	40 e-tron 08/17 – 12/18 155 kW	24-145985 $\frac{1}{\times}$	24-145992 $\frac{1}{\circ}$ with sports suspension; without leveling control; for vehicles without pneumatic suspension
B12 PK	40 e-tron 08/17 – 12/18 155 kW	46-257642 Conditions see certificates; for vehicles without pneumatic suspension; without leveling control; disconnect AMM FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1190 kg	
B16 PSS10	40 e-tron 08/17 – 12/18 155 kW	48-221832 disconnect AMM; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1375 kg RA: Axle load [kg] to 1410 kg	

AUDI (FAW) A6L C8 (488)			
B 4	55 TFSI e quattro, 55 TFSI Mild Hybrid quattro 01/19 – / 250 – 270 kW	19-302591	19-303802 $\frac{1}{\circ}$ with standard chassis; without leveling control
B 4	55 TFSI e quattro, 55 TFSI Mild Hybrid quattro 01/19 – / 250 – 270 kW	19-302614	19-304397 $\frac{1}{\circ}$ with sports suspension; without leveling control FA: Outer diameter [mm] 53 mm
B 4	55 TFSI e quattro, 55 TFSI Mild Hybrid quattro 01/19 – / 250 – 270 kW	19-302607	19-304397 $\frac{1}{\circ}$ with sports suspension; without leveling control
B 4	55 TFSI e quattro, 55 TFSI Mild Hybrid quattro 01/19 – / 250 – 270 kW	19-302614	19-303789 $\frac{1}{\circ}$ with off-road suspension; without leveling control FA: Outer diameter [mm] 53 mm
B 6	55 TFSI e quattro, 55 TFSI Mild Hybrid quattro 01/19 – / 250 – 270 kW	24-324540 $\frac{1}{\times}$	24-324557 $\frac{1}{\circ}$
B 6	55 TFSI e quattro, 55 TFSI Mild Hybrid quattro 01/19 – / 250 – 270 kW		24-324557 $\frac{1}{\circ}$

AUDI (FAW) Q2L (G1I)			
B 1	e-tron 11/19 – / 100 kW	12-243945	FA: without ball bearing
B 1	e-tron 11/19 – / 100 kW		12-281459 09/18→
B 4	e-tron 11/19 – / 100 kW	22-273994 $\frac{1}{\text{T}}$	19-274003 $\frac{1}{\circ}$ without electronic suspension control FA: Strut outside diameter [mm] 55mm RA: for PR number: ON1; Rigid Axle
B 4	e-tron 11/19 – / 100 kW	22-273994 $\frac{1}{\text{T}}$	19-275277 $\frac{1}{\circ}$ without electronic suspension control FA: Strut outside diameter [mm] 55mm RA: for PR number: ON4; Multilink Axle
B 4 DTC	e-tron 11/19 – / 100 kW	23-238978 $\frac{1}{\times}$	20-279875 $\frac{1}{\circ}$ FA: for PR number: UC8; Strut outside diameter [mm] 55mm; with electronic suspension control; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Rigid Axle; Length 2 [mm]: 681 mm; Length 1 [mm]: 428,5 mm
B 4 DTC	e-tron 11/19 – / 100 kW	23-238978 $\frac{1}{\times}$	20-279547 $\frac{1}{\circ}$ for PR number: UC8; with electronic suspension control FA: Strut outside diameter [mm] 55mm; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Multilink Axle; for OE number: 5Q0 512 009 CF
B 6	e-tron 11/19 – / 100 kW	35-274018 $\frac{1}{\times}$	24-273121 $\frac{1}{\circ}$ without electronic suspension control FA: Strut outside diameter [mm] 55mm RA: for PR number: ON1; Rigid Axle
B 6	e-tron 11/19 – / 100 kW	35-274018 $\frac{1}{\times}$	24-267137 $\frac{1}{\circ}$ without electronic suspension control; with standard chassis FA: Strut outside diameter [mm] 55mm RA: for PR number: ON4; Multilink Axle



AUDI (FAW)					
AUDI (FAW) Q2L (G11)					
B 6 DTC	e-tron 11/19 - /	100 kW	23-254343	20-279882	for PR number: UC8; with electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Rigid Axle
B 6 DTC	e-tron 11/19 - /	100 kW	23-254343	20-279530	for PR number: UC8; with electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Multilink Axle
B 8	e-tron 11/19 - /	100 kW	35-267126	24-273121	without electronic suspension control; with lowered chassis FA: Strut outside diameter [mm] 55mm RA: for PR number: 0N1; Rigid Axle
B 8	e-tron 11/19 - /	100 kW	35-267126	24-267137	without electronic suspension control; with lowered chassis FA: Strut outside diameter [mm] 55mm RA: for PR number: 0N4; Multilink Axle
B12 PK	e-tron 11/19 - /	100 kW	46-276018		Conditions see certificates; Rigid Axle FA: Axle load [kg] to 995 kg; Lowering ca. [mm]: 35 mm RA: Axle load [kg] to 990 kg; Lowering ca. [mm]: 30 mm

AUDI (FAW) Q4 (G3B)					
B 6	40 e-tron 05/22 - /	150 kW	22-330055	24-324595	without electronic suspension control; with sports suspension
ES	40 e-tron 05/22 - /	150 kW	47-330108		Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Axle load [kg] to 1210 kg; Lowering ca. [mm]: 25-45 mm RA: Axle load [kg] to 1560 kg; Lowering ca. [mm]: 20-40 mm

BMW					
BMW 2 Coupe (G42)					
B 1	220 d Mild-Hybrid 08/21 - /	140 kW	14-292408		with electronic suspension control
B 4 DTC	220 d Mild-Hybrid 08/21 - /	140 kW	23-303324	20-303334	with M-technology; with standard chassis FA: 23-305014; 23-303324
ET1	220 d Mild-Hybrid 08/21 - /	140 kW	48-300162		with standard chassis; Conditions see certificates FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg

BMW 2 Active Tourer (F45)					
B 4	225 xe Plug-in-Hybrid 11/14 - /	162 - 165 kW	22-247070	19-247090	with standard chassis; without EDC FA: 22-247087; 22-247070
B 4	225 xe Plug-in-Hybrid 11/14 - /	162 - 165 kW	22-252944	19-252988	with M-technology; without EDC FA: 22-252951; 22-252944
B 6	225 xe Plug-in-Hybrid 11/14 - /	162 - 165 kW	22-247049	24-247061	without EDC; with standard chassis FA: 22-247056; 22-247049
B 8	225 xe Plug-in-Hybrid 11/14 - /	162 - 165 kW	22-251985	24-251990	without EDC; with M-technology FA: 22-252005; 22-251985

BMW 2 Active Tourer (U06)					
B 4	220i Mild Hybrid, 223i Mild Hybrid xDrive, 223i Mild Hybrid, 225e xDrive, 230e xDrive 11/21 - /	125 - 240 kW	22-346414	19-298825	with standard chassis FA: 22-346421; 22-346414

BMW 3 (F30, F80)					
B 1	ActiveHybrid 07/12 - 06/15	250 kW	12-251377		→12/14; without EDC; without electronic suspension control FA: Mounting points diameter [mm] 10 mm; Number of mounting bores 3
B 1	ActiveHybrid 07/12 - 06/15	250 kW	12-283286		without M-technology; 01/14→ FA: Mounting points diameter [mm] 8 mm; Number of mounting bores 6
B 1	330 e 11/15 - 10/18	185 kW	12-283286		without M-technology FA: Mounting points diameter [mm] 8 mm; Number of mounting bores 6
B 1	ActiveHybrid, 330 e 07/12 - 10/18	185 - 250 kW	14-292408		with electronic suspension control
B 3	330 e 11/15 - 10/18	185 kW	37-247102	36-251285	with standard chassis
B 3	330 e 11/15 - 10/18	185 kW	37-251338	36-251292	with M-technology; Manual Transmission
B 3	330 e 11/15 - 10/18	185 kW	37-251352	36-251292	with M-technology; Fully Automatic
B 4	ActiveHybrid 07/12 - 06/15	250 kW	22-220066	19-247038	

BMW					
BMW 3 (F30, F80)					
B 4	330 e 11/15 – 10/18 185 kW	22-220066		19-220079	with standard chassis; without electronic suspension control
B 4	330 e 11/15 – 10/18 185 kW	22-220080		19-220093	with M-technology; with sports suspension; without electronic suspension control
B 4 DTC	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	23-238916 23-238923	 	20-238933	with EDC; with electronic suspension control FA: 23-238923; 23-238916
B 6 DTC	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	23-250727 23-250734	 	20-250744	with EDC; with electronic suspension control FA: 23-250734; 23-250727
B 8	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	35-264552		24-264563	with M-technology; without electronic suspension control
B12 PK	ActiveHybrid 07/12 – 06/15 250 kW	46-237576			Conditions see certificates; without electronic suspension control; with General Certification (ABE) FA: Lowering ca. [mm]: 35 mm; Axle load [kg] to 1065 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1310 kg
B12 PK	330 e 11/15 – 10/18 185 kW	46-229809			Conditions see certificates; without electronic suspension control; with General Certification (ABE) FA: Lowering ca. [mm]: 25-30 mm; Axle load [kg] to 990 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1265 kg
B12 DTC	ActiveHybrid 07/12 – 06/15 250 kW	46-331038			Conditions see certificates; with electronic suspension control; with General Certification (ABE) FA: Lowering ca. [mm]: 35 mm; Axle load [kg] to 1065 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1310 kg
B12 DTC	330 e 11/15 – 10/18 185 kW	46-331540			Conditions see certificates; with General Certification (ABE); with electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1020 kg RA: Axle load [kg] to 1310 kg
B14	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	47-264632			without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1285 kg
B14	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	47-264632			with electronic suspension control; only in connection with 1x 31306792211; without roadworthy certificate; disconnect EDC; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1285 kg
B16 PSS10	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	48-217170			without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1285 kg
B16 PSS10	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	48-217170			with electronic suspension control; only in connection with 1x 31306792211; without roadworthy certificate; disconnect EDC; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1285 kg
B16 PSS10	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	48-229012			Vehicle Type: Comfort; without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 10-30 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1285 kg
B16 PSS10	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	48-229012			with electronic suspension control; only in connection with 1x 31306792211; Vehicle Type: Comfort; without roadworthy certificate; disconnect EDC; Lowering ca. [mm]: 10-30 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1285 kg
B16 DTC	ActiveHybrid, 330 e 07/12 – 10/18 185 – 250 kW	49-255935			with EDC; Threaded Suspension (height adjustable); with electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm
B16 BCS	ActiveHybrid 07/12 – 06/15 250 kW	48-256322 48-230834			→12/14; without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; with uniball joint bearing; Number of mounting bores 3; Mounting points diameter [mm] 10 mm; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1235 kg
BMW 3 (G20, G80, G28)					
B 1	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 07/19 – / 85 – 275 kW	14-292408			with electronic suspension control
B 4	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 – / 90 – 215 kW	22-303301 22-305008	 	19-323312	FA: without electronic suspension control; with standard chassis; 22-305008; 22-303301 RA: Damper lengthened [mm]: 550,5 mm



BMW			
BMW 3 (G20, G80, G28)			
B 4	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 90 - 215 kW	22-306609 22-306616	19-323312 FA: without electronic suspension control; with M-technology; 22-306616; 22-306609 RA: Damper lengthened [mm]: 550,5 mm
B 4	330 e Plug-in-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 250 kW	22-305046 22-305053	19-323312 FA: without electronic suspension control; with standard chassis; 22-305053; 22-305046 RA: Damper lengthened [mm]: 550,5 mm
B 4	330 e Plug-in-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 250 kW	22-306623 22-306630	19-323312 FA: without electronic suspension control; with M-technology; 22-306630; 22-306623 RA: Damper lengthened [mm]: 550,5 mm
B 4	316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid 03/20 - / 90 - 140 kW	22-303301 22-305008	19-303314 without electronic suspension control FA: with standard chassis; 22-305008; 22-303301
B 4 DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid xDrive 07/19 - / 90 - 215 kW	23-303324 23-305014	20-303334 with M-technology; with standard chassis FA: 23-305014; 23-303324
B 4 DTC	330 e Plug-in-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 250 kW	23-305069 23-305076	20-303334 with electronic suspension control FA: 23-305076; 23-305069
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	22-303295 22-305022	24-313728 with standard chassis FA: 22-305022; 22-303295
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	22-303295 22-305022	24-303347 with M-technology FA: 22-305022; 22-303295
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	22-303295 22-305022	24-313728 with M-technology FA: 22-305022; 22-303295
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	22-303295 22-305022	24-313728 with standard chassis FA: 22-305022; 22-303295
B 6	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	22-305084 22-305091	24-313728 with standard chassis FA: 22-305091; 22-305084
B 6	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	22-305084 22-305091	24-303347 with M-technology FA: 22-305091; 22-305084
B 6	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	22-305084 22-305091	24-313728 with standard chassis FA: 22-305091; 22-305084
B 6	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	22-305084 22-305091	24-313728 with M-technology FA: 22-305091; 22-305084
B 6 DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	23-300187 23-305038	20-303426 with M-technology FA: 23-305038; 23-300187
B 6 DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	23-300187 23-305038	20-303426 with M-technology FA: 23-305038; 23-300187
B 6 DTC	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	23-305106 23-305113	20-303426 with electronic suspension control FA: 23-305113; 23-305106
B12 PK	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid 07/19 - / 150 - 215 kW	46-340139 Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1120 kg RA: Axle load [kg] to 1410 kg	
B12 PK	320 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid 03/20 - / 90 - 150 kW	46-313324 Conditions see certificates; with General Certification (ABE); without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 985 kg RA: Axle load [kg] to 1210 kg	



BMW			
BMW 3 (G20, G80, G28)			
B12 PK	330 e Plug-in-Hybrid xDrive 07/20 - / 215 kW	46-340160	Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1120 kg RA: Axle load [kg] to 1410 kg
B12 SL	320 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid 03/20 - / 85 - 150 kW	46-313331	Conditions see certificates; with General Certification (ABE); without electronic suspension control; Lowering ca. [mm]: 40 mm FA: Axle load [kg] to 985 kg RA: Axle load [kg] to 1210 kg
ES	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	47-326170	with standard chassis; without M-technology FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg
ES	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	47-326163	without electronic suspension control; Conditions see certificates FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 15-40 mm; Axle load [kg] to 1410 kg
ES	320 d Mild-Hybrid xDrive 03/20 - / 120 - 140 kW	47-304932	with standard chassis; Conditions see certificates FA: Lowering ca. [mm]: 25-50 mm; Axle load [kg] to 1170 kg RA: Lowering ca. [mm]: 20-55 mm; Axle load [kg] to 1345 kg
ES	320 d Mild-Hybrid xDrive 03/20 - / 120 - 140 kW	47-304932	with M-technology; Conditions see certificates FA: Lowering ca. [mm]: 25-40 mm; Axle load [kg] to 1170 kg RA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1365 kg
ESE DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	49-326185	FA: Lowering ca. [mm]: 25-40 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1325 kg
ESE DTC	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	49-326192	Conditions see certificates; with electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 15-35 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1345 kg
ESE DTC	320 d Mild-Hybrid xDrive 03/20 - / 120 - 140 kW	49-305135	Conditions see certificates; with electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 15-35 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1345 kg
ET1	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	48-326209	with standard chassis FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg
ET1	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	48-326216	with sports suspension; without roadworthy certificate FA: Axle load [kg] to 1115 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1345 kg; Lowering ca. [mm]: 25-45 mm
ET1	320 d Mild-Hybrid xDrive 03/20 - / 120 - 140 kW	48-304979	with sports suspension; Conditions see certificates FA: Axle load [kg] to 1170 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1365 kg; Lowering ca. [mm]: 25-45 mm
ET2	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 07/19 - / 85 - 215 kW	48-326230	with standard chassis FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1410 kg
ET2	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	48-326223	with sports suspension; without roadworthy certificate FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1410 kg
ET2	320 d Mild-Hybrid xDrive 03/20 - / 120 - 140 kW	48-313070	with sports suspension; Conditions see certificates FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1170 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1365 kg
ER	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid, 330 d Mild-Hybrid xDrive, M340 d Mild-Hybrid xDrive 07/19 - / 85 - 275 kW	89-312780	with standard chassis; without roadworthy certificate; not permitted on public roads; with suspension strut support bearing FA: Lowering ca. [mm]: 30-70 mm RA: Lowering ca. [mm]: 20-60 mm
BMW 3 Touring (G21, G81)			
B 1	320 e Plug-in-Hybrid, 320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 85 - 275 kW	14-292408	with electronic suspension control
B 4	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 90 - 215 kW	22-303301 $\frac{1}{2}$ 22-305008 $\frac{1}{2}$	19-323312 $\frac{1}{2}$ FA: without electronic suspension control; with standard chassis; 22-305008; 22-303301 RA: Damper lengthened [mm]: 550,5 mm



BMW			
BMW 3 Touring (G21, G81)			
B 4	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 90 - 215 kW	22-306609 22-306616	19-323305 FA: without electronic suspension control; with M-technology; 22-306616; 22-306609
B 4	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 140 - 275 kW	22-305046 22-305053	19-323312 FA: without electronic suspension control; with standard chassis; 22-305046 RA: Damper lengthened [mm]: 550,5 mm
B 4	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 140 - 275 kW	22-306623 22-306630	19-323305 FA: without electronic suspension control; with M-technology; 22-306630; 22-306623
B 4 DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 90 - 215 kW	23-303324 23-305014	20-303334 with electronic suspension control FA: 23-305014; 23-303324
B 4 DTC	330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 140 - 275 kW	23-305069 23-305076	20-303334 with electronic suspension control FA: 23-305076; 23-305069
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	22-303295 22-305022	24-313728 with standard chassis FA: 22-305022; 22-303295
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	22-303295 22-305022	24-303347 with M-technology FA: 22-305022; 22-303295
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	22-303295 22-305022	24-313728 with M-technology FA: 22-305022; 22-303295
B 6	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	22-303295 22-305022	24-313728 with standard chassis FA: 22-305022; 22-303295
B 6	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	22-305084 22-305091	24-313728 with standard chassis FA: 22-305091; 22-305084
B 6	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	22-305084 22-305091	24-303347 with M-technology FA: 22-305091; 22-305084
B 6 DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	23-300187 23-305038	20-303426 with electronic suspension control FA: 23-305038; 23-300187
B 6 DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	23-300187 23-305038	20-303426 with M-technology FA: 23-305038; 23-300187
B 6 DTC	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	23-305106 23-305113	20-303426 with electronic suspension control FA: 23-305113; 23-305106
B12 PK	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid 07/20 - / 150 - 215 kW	46-340139 Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1120 kg RA: Axle load [kg] to 1410 kg	
B12 PK	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive 07/20 - / 150 - 215 kW	46-340160 Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1120 kg RA: Axle load [kg] to 1410 kg	
B12 PK	330 e Plug-in-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 04/20 - / 210 - 250 kW	46-262585 Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 20 mm; Axle load [kg] to 1120 kg RA: Lowering ca. [mm]: 15 mm; Axle load [kg] to 1360 kg	
B12 PK	M 340 i Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 04/20 - / 250 - 275 kW	46-262585 Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1025 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1360 kg	
B12 PK	316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid 03/20 - / 85 - 140 kW	46-322319 Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1025 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1360 kg	
















































BMW

BMW 3 Touring (G21, G81)

B12 PK	320 d Mild-Hybrid xDrive 03/20 - / 120 - 140 kW	46-262585	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 20 mm; Axle load [kg] to 1120 kg RA: Lowering ca. [mm]: 15 mm; Axle load [kg] to 1360 kg
B12 PK	330 d Mild-Hybrid 11/20 - / 210 kW	46-322326	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1120 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1360 kg
B12 SL	316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid 03/20 - / 85 - 140 kW	46-334688	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 40-45 mm; Axle load [kg] to 1000 kg RA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1345 kg
B12 SL	320 d Mild-Hybrid xDrive 03/20 - / 120 - 140 kW	46-335593	Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1345 kg
ES	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	47-326170	with standard chassis; without M-technology FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg
ES	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	47-326163	with sports suspension FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 15-40 mm; Axle load [kg] to 1410 kg
ES	330 e Plug-in-Hybrid xDrive 07/20 - / 215 kW	47-304932	with sports suspension; Conditions see certificates FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1410 kg
ESE DTC	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	49-326185	FA: Lowering ca. [mm]: 25-40 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1325 kg
ESE DTC	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	49-326192	with electronic suspension control; Threaded Suspension (height adjustable); Conditions see certificates FA: Lowering ca. [mm]: 15-35 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1345 kg
ESE DTC	330 e Plug-in-Hybrid xDrive 07/20 - / 215 kW	49-305135	with sports suspension; Conditions see certificates FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1345 kg
ET1	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	48-326209	with standard chassis FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg
ET1	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	48-326216	with sports suspension FA: Axle load [kg] to 1115 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1345 kg; Lowering ca. [mm]: 25-45 mm
ET2	320 e Plug-in-Hybrid, 330 e Plug-in-Hybrid, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 330 d Mild-Hybrid 03/20 - / 85 - 215 kW	48-326230	with standard chassis FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1410 kg
ET2	320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 120 - 275 kW	48-326223	with sports suspension FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1410 kg
ER	320 e Plug-in-Hybrid, 320 e Plug-in-Hybrid xDrive, 330 e Plug-in-Hybrid, 330 e Plug-in-Hybrid xDrive, M 340 i Mild-Hybrid xDrive, 316 d Mild-Hybrid, 318 d Mild-Hybrid, 320 d Mild-Hybrid, 320 d Mild-Hybrid xDrive, 330 d Mild-Hybrid, 330 d Mild-Hybrid xDrive, M 340 d Mild-Hybrid xDrive 03/20 - / 85 - 275 kW	89-312780	with standard chassis; without roadworthy certificate; not permitted on public roads; with suspension strut support bearing FA: Lowering ca. [mm]: 30-70 mm RA: Lowering ca. [mm]: 20-70 mm

BMW 3 Touring Van (G21)

B 1	320 d Mild-Hybrid, 320 d Mild-Hybrid xDrive 03/20 - / 140 kW	14-292408	with electronic suspension control
B 4	320 d Mild-Hybrid 03/20 - / 140 kW	22-303301 ⚡ 22-305008 ⚡	19-323312 ⚡ FA: without electronic suspension control; with standard chassis; 22-305008; 22-303301 RA: Damper lengthened [mm]: 550,5 mm
B 4	320 d Mild-Hybrid 03/20 - / 140 kW	22-306609 ⚡ 22-306616 ⚡	19-323305 ⚡ FA: without electronic suspension control; with M-technology; 22-306616; 22-306609
B 4	320 d Mild-Hybrid xDrive 03/20 - / 140 kW	22-305046 ⚡ 22-305053 ⚡	19-323312 ⚡ FA: without electronic suspension control; with standard chassis; 22-305053; 22-305046 RA: Damper lengthened [mm]: 550,5 mm
B 4	320 d Mild-Hybrid xDrive 03/20 - / 140 kW	22-306623 ⚡ 22-306630 ⚡	19-323305 ⚡ FA: without electronic suspension control; with M-technology; 22-306630; 22-306623
B 4 DTC	320 d Mild-Hybrid 03/20 - / 140 kW	23-303324 ⚡ 23-305014 ⚡	20-303334 ⚡ with electronic suspension control FA: 23-305014; 23-303324











































				
BMW				
BMW 3 Touring Van (G21)				
B 4 DTC	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	23-305069  23-305076 	20-303334  with electronic suspension control FA: 23-305076; 23-305069
B 6	320 d Mild-Hybrid 03/20 - /	140 kW	22-303295  22-305022 	24-313728  with standard chassis FA: 22-305022; 22-303295
B 6	320 d Mild-Hybrid 03/20 - /	140 kW	22-303295  22-305022 	24-303347  with M-technology FA: 22-305022; 22-303295
B 6	320 d Mild-Hybrid 03/20 - /	140 kW	22-303295  22-305022 	24-313728  with M-technology FA: 22-305022; 22-303295
B 6	320 d Mild-Hybrid 03/20 - /	140 kW	22-303295  22-305022 	24-313728  with standard chassis FA: 22-305022; 22-303295
B 6	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	22-305084  22-305091 	24-313728  with standard chassis FA: 22-305091; 22-305084
B 6	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	22-305084  22-305091 	24-313728  with standard chassis FA: 22-305091; 22-305084
B 6	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	22-305084  22-305091 	24-303347  with M-technology FA: 22-305091; 22-305084
B 6	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	22-305084  22-305091 	24-313728  with standard chassis FA: 22-305091; 22-305084
B 6	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	22-305084  22-305091 	24-313728  with M-technology FA: 22-305091; 22-305084
B 6 DTC	320 d Mild-Hybrid 03/20 - /	140 kW	23-300187  23-305038 	20-303426  with electronic suspension control FA: 23-305038; 23-300187
B 6 DTC	320 d Mild-Hybrid 03/20 - /	140 kW	23-300187  23-305038 	20-303426  with M-technology FA: 23-305038; 23-300187
B 6 DTC	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	23-305106  23-305113 	20-303426  with electronic suspension control FA: 23-305113; 23-305106
B 6 DTC	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	23-305106  23-305113 	20-303426  with electronic suspension control FA: 23-305113; 23-305106
B12 PK	320 d Mild-Hybrid 03/20 - /	140 kW	46-322319 Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1025 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1360 kg	
B12 PK	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	46-262585 Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 20 mm; Axle load [kg] to 1120 kg RA: Lowering ca. [mm]: 15 mm; Axle load [kg] to 1360 kg	
B12 SL	320 d Mild-Hybrid 03/20 - /	140 kW	46-334688 Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 40-45 mm; Axle load [kg] to 1000 kg RA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1345 kg	
B12 SL	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	46-335593 Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1095 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1345 kg	
ESE DTC	320 d Mild-Hybrid 03/20 - /	140 kW	49-326185 FA: Lowering ca. [mm]: 25-40 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1325 kg	
ESE DTC	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	49-326192 without roadworthy certificate; with electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 15-35 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1345 kg	
ET1	320 d Mild-Hybrid 03/20 - /	140 kW	48-326209 with standard chassis FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg	
ET1	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	48-326216 with sports suspension; without roadworthy certificate FA: Axle load [kg] to 1115 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1345 kg; Lowering ca. [mm]: 25-45 mm	
ET2	320 d Mild-Hybrid 03/20 - /	140 kW	48-326230 with standard chassis FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1410 kg	
ET2	320 d Mild-Hybrid xDrive 03/20 - /	140 kW	48-326223 with sports suspension; without roadworthy certificate FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1410 kg	
ER	320 d Mild-Hybrid, 320 d Mild-Hybrid xDrive 03/20 - /	140 kW	89-312780 with standard chassis; without roadworthy certificate; not permitted on public roads; with suspension strut support bearing FA: Lowering ca. [mm]: 30-70 mm RA: Lowering ca. [mm]: 20-70 mm	
BMW 4 Coupe (G22, G82)				
B 1	420 d Mild-Hybrid 07/20 - /	120 - 140 kW	14-292408 with electronic suspension control	

BMW			
BMW 4 Coupe (G22, G82)			
B 4	M 440 i Mild-Hybrid, M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW	22-305046 22-305053	19-325798 with standard chassis FA: 22-305053; 22-305046
B 4	M 440 i Mild-Hybrid, M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW	22-306623 22-306630	19-323305 with M-technology FA: 22-306630; 22-306623
B 4	420 d Mild-Hybrid 07/20 - / 120 - 140 kW	22-303301 22-305008	19-325798 with standard chassis FA: 22-305008; 22-303301
B 4	420 d Mild-Hybrid 07/20 - / 120 - 140 kW	22-306609 22-306616	19-323305 with M-technology FA: 22-306616; 22-306609
B 4 DTC	M 440 i Mild-Hybrid, M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW	23-305069 23-305076	20-303334 with standard chassis FA: 23-305076; 23-305069
B 4 DTC	420 d Mild-Hybrid 07/20 - / 120 - 140 kW	23-303324 23-305014	20-303334 with M-technology; with standard chassis FA: 23-305014; 23-303324
B 6	M 440 i Mild-Hybrid, 420 d Mild-Hybrid 07/20 - / 120 - 285 kW	22-303295 22-305022	24-303347 with M-technology; with standard chassis FA: 22-305022; 22-303295
B 6	M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW	22-305084 22-305091	24-303347 without electronic suspension control FA: 22-305091; 22-305084 RA: with M-technology
B 6	420 d Mild-Hybrid 07/20 - / 120 - 140 kW	22-303295 22-305022	24-313728 with standard chassis FA: 22-305022; 22-303295
B 6	420 d Mild-Hybrid 07/20 - / 120 - 140 kW	22-303295 22-305022	24-313728 with M-technology FA: 22-305022; 22-303295
B 6 DTC	M 440 i Mild-Hybrid, 420 d Mild-Hybrid 07/20 - / 120 - 285 kW	23-300187 23-305038	20-303426 with M-technology; with standard chassis FA: 23-305038; 23-300187
B 6 DTC	M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW	23-305106 23-305113	20-303426 with M-technology FA: 23-305113; 23-305106
B 6 DTC	420 d Mild-Hybrid 07/20 - / 120 - 140 kW	23-300187 23-305038	20-303426 with M-technology FA: 23-305038; 23-300187
ES	M 440 i Mild-Hybrid, 420 d Mild-Hybrid 07/20 - / 120 - 285 kW		47-326170 with standard chassis FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg
ES	M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW		47-326163 with sports suspension FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 15-40 mm; Axle load [kg] to 1410 kg
ESE DTC	M 440 i Mild-Hybrid, 420 d Mild-Hybrid 07/20 - / 120 - 285 kW		49-326185 FA: Lowering ca. [mm]: 25-40 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1325 kg
ET1	M 440 i Mild-Hybrid, 420 d Mild-Hybrid 07/20 - / 120 - 285 kW		48-326209 with standard chassis FA: Lowering ca. [mm]: 35-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1325 kg
ET1	M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW		48-326216 with sports suspension FA: Axle load [kg] to 1115 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1345 kg; Lowering ca. [mm]: 25-45 mm
ET2	M 440 i Mild-Hybrid, 420 d Mild-Hybrid 07/20 - / 120 - 285 kW		48-326230 with standard chassis FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1410 kg
ET2	M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 140 - 285 kW		48-326223 with sports suspension FA: Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1115 kg RA: Lowering ca. [mm]: 25-45 mm; Axle load [kg] to 1410 kg
ER	M 440 i Mild-Hybrid, M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 07/20 - / 120 - 285 kW		89-312780 with standard chassis; without roadworthy certificate; not permitted on public roads; with suspension strut support bearing FA: Lowering ca. [mm]: 30-70 mm RA: Lowering ca. [mm]: 20-70 mm
BMW 4 Convertible (G23, G83)			
B 1	M 440 i Mild-Hybrid xDrive 11/20 - / 285 kW		14-292408 with electronic suspension control
B 4	M 440 i Mild-Hybrid, 420 d Mild-Hybrid, 430 d Mild-Hybrid 11/20 - / 120 - 285 kW	22-303301 22-305008	19-325798 with standard chassis FA: 22-305008; 22-303301
B 4	M440 d Mild-Hybrid xDrive 11/21 - / 250 kW	22-306623 22-306630	19-323305 with sports suspension; with M-technology FA: 22-306630; 22-306623





























BMW				
BMW 4 Convertible (G23, G83)				
B 4 DTC	M 440 i Mild-Hybrid xDrive 11/20 - / 285 kW	23-305069 23-305076	 	20-303334 with electronic suspension control FA: 23-305076; 23-305069
B 6 DTC	M 440 i Mild-Hybrid, 420 d Mild-Hybrid, 430 d Mild-Hybrid 11/20 - / 120 - 285 kW	23-300187 23-305038	 	20-303426 with M-technology FA: 23-305038; 23-300187
ET1	M 440 i Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 11/20 - / 250 - 275 kW	48-304979		with sports suspension; Conditions see certificates FA: Axle load [kg] to 1170 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1365 kg; Lowering ca. [mm]: 25-45 mm
ET1	M 440 i Mild-Hybrid xDrive, M440 d Mild-Hybrid xDrive 11/20 - / 250 - 285 kW	48-326216		with sports suspension FA: Axle load [kg] to 1170 kg; Lowering ca. [mm]: 20-40 mm RA: Axle load [kg] to 1365 kg; Lowering ca. [mm]: 25-45 mm
ER	M 440 i Mild-Hybrid, M 440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid, 430 d Mild-Hybrid, M440 d Mild-Hybrid xDrive 11/20 - / 120 - 285 kW	89-312780		with standard chassis; without roadworthy certificate; not permitted on public roads; with suspension strut support bearing FA: Lowering ca. [mm]: 30-70 mm RA: Lowering ca. [mm]: 20-70 mm
BMW 4 Gran Coupe (G26)				
B 4 DTC	420 d Mild-Hybrid 07/21 - / 140 kW			20-303334 with M-technology
B 6 DTC	M440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive 07/21 - / 140 - 285 kW			20-303426 RA: with electronic suspension control
B 6 DTC	420 d Mild-Hybrid 07/21 - / 140 kW			20-303426 with M-technology
ES	M440 i Mild-Hybrid xDrive, 420 d Mild-Hybrid xDrive, 430 d Mild-Hybrid xDrive 07/21 - / 140 - 285 kW	47-342231		
BMW 5 (F10)				
B 1	ActiveHybrid 12/11 - 10/16 250 kW	11-305798		with electronic suspension control
B 1	ActiveHybrid 12/11 - 10/16 250 kW	12-244966		without electronic suspension control
B 4	ActiveHybrid 12/11 - 10/16 250 kW	19-193298 19-193304	 	19-193311 11-299479 with standard chassis; without electronic suspension control FA: 19-193304; 19-193298
B 6	ActiveHybrid 12/11 - 10/16 250 kW	24-178488 24-178495	 	24-176255 with standard chassis; without electronic suspension control FA: 24-178495; 24-178488
B 8	ActiveHybrid 12/11 - 10/16 250 kW	24-178501 24-178518	 	24-178525 with M-technology; without electronic suspension control FA: 24-178518; 24-178501
B16 PSS10	ActiveHybrid 12/11 - 10/16 250 kW	48-177580		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1250 kg RA: Axle load [kg] to 1320 kg
BMW 5 (G30, F90)				
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid xDrive, 545 e Plug-in-Hybrid xDrive, 530 i Mild-Hybrid xDrive, 540 i Mild-Hybrid xDrive, 520 d Mild-Hybrid xDrive, 523 D XDRIVE MILD-HYBRID, 530 d Mild-Hybrid xDrive, 540 d Mild-Hybrid xDrive 03/17 - 06/20 140 - 290 kW	19-276946 19-276953	 	19-274379 with M-technology FA: 19-276953; 19-276946
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 540 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 03/17 - 06/20 100 - 245 kW	19-276885 19-276892	 	19-280981 with standard chassis FA: 19-276892; 19-276885
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid xDrive, 545 e Plug-in-Hybrid xDrive, 530 i Mild-Hybrid xDrive, 540 i Mild-Hybrid xDrive, 520 d Mild-Hybrid xDrive, 523 D XDRIVE MILD-HYBRID, 530 d Mild-Hybrid xDrive, 540 d Mild-Hybrid xDrive 03/17 - 06/20 140 - 290 kW	19-276946 19-276953	 	19-280998 with off-road suspension FA: 19-276953; 19-276946
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 540 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 03/17 - 06/20 100 - 245 kW	19-276908 19-276915	 	19-280998 with off-road suspension FA: 19-276915; 19-276908






















BMW					
BMW 5 (G30, F90)					
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid xDrive, 545 e Plug-in-Hybrid xDrive, 530 i Mild-Hybrid xDrive, 540 i Mild-Hybrid xDrive, 520 d Mild-Hybrid xDrive, 523 D XDRIVE MILD-HYBRID, 530 d Mild-Hybrid xDrive, 540 d Mild-Hybrid xDrive 03/17 – 06/20 140 – 290 kW	19-276922 19-276939	 	19-280981	with standard chassis; without electronic suspension control FA: 19-276939; 19-276922
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 540 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 03/17 – 06/20 100 – 245 kW	19-274355 19-274362	 	19-274379	with M-technology FA: 19-274362; 19-274355
B 6	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 540 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 03/17 – 06/20 100 – 245 kW	24-279772 24-281072	 	24-279789	without electronic suspension control; with standard chassis FA: 24-281072; 24-279772
B 6	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid xDrive, 545 e Plug-in-Hybrid xDrive, 530 i Mild-Hybrid xDrive, 540 i Mild-Hybrid xDrive, 520 d Mild-Hybrid xDrive, 523 D XDRIVE MILD-HYBRID, 530 d Mild-Hybrid xDrive, 540 d Mild-Hybrid xDrive 03/17 – 06/20 140 – 290 kW	24-279819		24-279789	without electronic suspension control; with standard chassis
B 8	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 d Mild-Hybrid 07/19 – 06/20 120 – 170 kW	24-279772 24-281072	 	24-296472	without electronic suspension control FA: 24-281072; 24-279772
B 8	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid xDrive, 545 e Plug-in-Hybrid xDrive, 530 i Mild-Hybrid xDrive, 540 i Mild-Hybrid xDrive, 520 d Mild-Hybrid xDrive, 523 D XDRIVE MILD-HYBRID, 530 d Mild-Hybrid xDrive, 540 d Mild-Hybrid xDrive 03/17 – 06/20 140 – 290 kW	24-296489		24-296472	without electronic suspension control
B12 PK	520 E PLUG-IN-HYBRID 03/21 – / 150 kW	46-280763		Conditions see certificates; without leveling control; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1140 kg RA: Axle load [kg] to 1325 kg	
B16 PSS10	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 540 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 03/17 – 06/20 100 – 245 kW	48-279765		without electronic suspension control; Threaded Suspension (height adjustable); Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1125 kg RA: Axle load [kg] to 1405 kg	
BMW 5 Touring (G31)					
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid xDrive, 530 i Mild-Hybrid xDrive, 540 i Mild-Hybrid xDrive, 520 d Mild-Hybrid xDrive, 530 d Mild-Hybrid xDrive, 540 d Mild-Hybrid xDrive 11/19 – / 140 – 250 kW	19-287409 19-287416	 	with M-technology; with off-road suspension FA: 19-287416; 19-287409	
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid xDrive, 530 i Mild-Hybrid xDrive, 540 i Mild-Hybrid xDrive, 520 d Mild-Hybrid xDrive, 530 d Mild-Hybrid xDrive, 540 d Mild-Hybrid xDrive 11/19 – / 140 – 250 kW	19-276922 19-276939	 	with standard chassis FA: 19-276939; 19-276922	
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 11/19 – / 100 – 215 kW	19-287379 19-287386	 	with standard chassis FA: 19-287386; 19-287379	
B 4	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 11/19 – / 100 – 215 kW	19-306230 19-306247	 	with sports suspension FA: 19-306247; 19-306230	
B 6	520 E PLUG-IN-HYBRID, 530 e Plug-in-Hybrid, 520 i Mild-Hybrid, 530 i Mild-Hybrid, 518 d Mild-Hybrid, 520 d Mild-Hybrid, 530 d Mild-Hybrid 11/19 – / 100 – 215 kW	24-279772 24-281072	 	without electronic suspension control FA: 24-281072; 24-279772	
BMW 6 Gran Turismo (G32)					
B 4	630 i Mild-Hybrid, 640 i Mild-Hybrid, 620 d Mild-Hybrid, 630 d Mild-Hybrid 07/20 – / 120 – 245 kW	19-282619 19-282626	 	for vehicles without pneumatic suspension; with standard chassis; without electronic suspension control FA: 19-282626; 19-282619	
B 4 AMC	640 i Mild-Hybrid xDrive, 620 d Mild-Hybrid xDrive, 630 d Mild-Hybrid xDrive, 640 d Mild-Hybrid xDrive 07/20 – / 140 – 250 kW	22-295972 22-295989	 	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 22-295989; 22-295972	











				
BMW				
BMW 7 (F01, F02, F03, F04)				
B 1	ActiveHybrid 7 04/10 – 06/15	260 – 342 kW	12-234622	with electronic suspension control FA: without ball bearing
BMW i3 (I01)				
B 1	Electric, s Electric 08/13 – /	75 – 135 kW	12-303106	12-303120 12-303113 
B 4	Electric, s Electric 08/13 – /	75 – 135 kW	22-240057  22-240064 	19-240084  with standard chassis FA: 22-240064; 22-240057
BMW i4 (G26)				
B 6	eDrive40 11/21 – /	250 kW	22-342287  22-342294 	with M-technology FA: 22-342294; 22-342287
BMW X1 (F48)				
B 4	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-247070  22-247087 	19-247090  without electronic suspension control FA: 22-247087; 22-247070
B 4	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-252944  22-252951 	19-252988  without electronic suspension control; with M-technology FA: 22-252951; 22-252944
B 6	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-247049  22-247056 	24-247061  without EDC; with standard chassis FA: 22-247056; 22-247049
B 8	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-251985  22-252005 	24-251990  without EDC; with M-technology FA: 22-252005; 22-251985
B12 PK	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	46-275158 Conditions see certificates; without leveling control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1150 kg RA: Axle load [kg] to 1075 kg	
BMW X2 (F39)				
B 4	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-300942  22-300959 	19-247090  without electronic suspension control; with standard chassis FA: 22-300959; 22-300942
B 4	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-300966  22-300973 	19-298825  without electronic suspension control; with sports suspension FA: 22-300973; 22-300966
B 6	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-247049  22-247056 	24-247061  without EDC; with standard chassis FA: 22-247056; 22-247049
B 8	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	22-251985  22-252005 	24-251990  without EDC; with M-technology FA: 22-252005; 22-251985
B12 PK	xDrive 25 e Plug-in-Hybrid 03/20 – /	162 kW	46-334855 Conditions see certificates; without leveling control; without electronic suspension control; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1080 kg	
BMW X3 (G01, F97)				
B 4	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid, xDrive M40 i Mild Hybrid, sDrive 18 d Mild-Hybrid, xDrive 20 d Mild-Hybrid, xDrive 30d Mild-Hybrid, xDrive M40 d Mild-Hybrid 08/18 – /	100 – 265 kW	22-298539  22-298560 	19-295442  with standard chassis; without electronic suspension control FA: 22-298560; 22-298539
B 4	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid, xDrive M40 i Mild Hybrid, sDrive 18 d Mild-Hybrid, xDrive 20 d Mild-Hybrid, xDrive 30d Mild-Hybrid, xDrive M40 d Mild-Hybrid 08/18 – /	100 – 265 kW	22-298539  22-298560 	19-295695  with sports suspension; without electronic suspension control FA: 22-298560; 22-298539
B 6	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid, xDrive M40 i Mild Hybrid, sDrive 18 d Mild-Hybrid, xDrive 20 d Mild-Hybrid, xDrive 30d Mild-Hybrid, xDrive M40 d Mild-Hybrid 08/18 – /	100 – 265 kW	22-305169  22-305183 	24-305174  with standard chassis; without electronic suspension control FA: 22-305183; 22-305169
B12 PK	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid, xDrive 20 d Mild-Hybrid 04/20 – /	120 – 180 kW	46-332790 Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 1180 kg RA: Axle load [kg] to 1505 kg	
B12 PK	xDrive 30d Mild-Hybrid 07/20 – /	183 – 210 kW	46-339898 without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 1255 kg RA: Axle load [kg] to 1505 kg	

BMW				
BMW X4 (G02, F98)				
B 4	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid, xDrive M40 i Mild Hybrid, xDrive 20 d Mild-Hybrid, xDrive 30 d Mild-Hybrid, M40 d Mild-Hybrid xDrive 04/20 – / 120 – 265 kW	22-298539 22-298560	 19-295442 19-295695	with standard chassis; without electronic suspension control FA: 22-298560; 22-298539
B 4	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid, xDrive M40 i Mild Hybrid, xDrive 20 d Mild-Hybrid, xDrive 30 d Mild-Hybrid, M40 d Mild-Hybrid xDrive 04/20 – / 120 – 265 kW	22-298539 22-298560	 19-295442 19-295695	with sports suspension; without electronic suspension control FA: 22-298560; 22-298539
B 6	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid, xDrive M40 i Mild Hybrid, xDrive 20 d Mild-Hybrid, xDrive 30 d Mild-Hybrid, M40 d Mild-Hybrid xDrive 04/20 – / 120 – 265 kW	22-305169 22-305183	 24-305174	with standard chassis; without electronic suspension control; with sports suspension FA: 22-305183; 22-305169
B12 PK	xDrive 20 i Mild Hybrid, xDrive 30 i Mild Hybrid 07/21 – / 135 – 180 kW	46-332790		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 1180 kg RA: Axle load [kg] to 1505 kg
B12 PK	xDrive M40 i Mild Hybrid, xDrive 30 d Mild-Hybrid, M40 d Mild-Hybrid xDrive 07/20 – / 183 – 265 kW	46-339898		without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1255 kg; Lowering ca. [mm]: 30 mm RA: Axle load [kg] to 1505 kg; Lowering ca. [mm]: 25 mm
B12 PK	xDrive 20 d Mild-Hybrid 04/20 – / 120 – 140 kW	46-339898		without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 1255 kg RA: Axle load [kg] to 1505 kg
BMW X5 (F15, F85)				
B 1	xDrive 40e 08/15 – 07/18 205 – 230 kW	14-346293		with electronic suspension control
B 3 AMC	xDrive 40e 08/15 – 07/18 205 – 230 kW	40-221595		with electronic suspension control; for pneumatic suspension vehicles
B 4	xDrive 40e 08/15 – 07/18 205 – 230 kW	22-240316	 19-240329 19-240336	with standard chassis RA: 19-240336; 19-240329
B 4 DTC	xDrive 40e 08/15 – 07/18 205 – 230 kW	23-339651 23-339668	 23-339675 23-339682	with standard chassis; with M-technology; with electronic suspension control
B 6	xDrive 40e 08/15 – 07/18 205 – 230 kW	29-241668	 24-241670 24-241687	with standard chassis RA: 24-241687; 24-241670
BMW X5 (G05, F95)				
B 4 DTC	xDrive 45 e Plug-in-Hybrid, xDrive 40 i Mild-Hybrid, xDrive 30 d Mild-Hybrid, xDrive 40 d Mild-Hybrid 06/19 – / 183 – 290 kW	23-328983 23-328976	 20-328955 20-328962	with electronic suspension control; with standard chassis; with M-technology
BMW X6 (E71, E72)				
B 3 AMC	ActiveHybrid 01/09 – 10/11 357 kW	40-221595		with leveling control; for pneumatic suspension vehicles; with standard chassis
B 4	ActiveHybrid 01/09 – 10/11 357 kW	19-261515	 19-184074 19-184081	with standard chassis; without leveling control; without 3rd seating row RA: 19-184081; 19-184074
B 4	ActiveHybrid 01/09 – 10/11 357 kW	19-261515	 19-249070 19-249087	with standard chassis; with leveling control; without 3rd seating row RA: 19-249087; 19-249070
B 6	ActiveHybrid 01/09 – 10/11 357 kW	24-272674	 24-143943 24-143950	without 3rd seating row; without leveling control; with standard chassis RA: 24-143950; 24-143943
B 8	ActiveHybrid 01/09 – 10/11 357 kW	24-272681	 24-143974 24-143981	without 3rd seating row; without leveling control; with sports suspension RA: 24-143981; 24-143974
B12 PK	ActiveHybrid 01/09 – 10/11 357 kW	46-187987		Conditions see certificates; without leveling control; without 3rd seating row; Lowering ca. [mm]: 20 mm FA: Axle load [kg] to 1365 kg RA: Axle load [kg] to 1520 kg
BMW X6 (G06, F96)				
B 4 DTC	xDrive 40 i Mild-Hybrid, xDrive 30 d Mild-Hybrid, xDrive 40 d Mild-Hybrid 05/20 – / 155 – 250 kW	23-328983 23-328976	 20-328955 20-328962	with electronic suspension control; with standard chassis; with M-technology

					
BMW (BRILLIANCE)					
BMW (BRILLIANCE) 5 SERIES (F10, F18)					
B 4	530 Le Hybrid 01/15 – 05/17	160 kW	19-193298  19-193304 	19-193311 	with standard chassis; without electronic suspension control FA: 19-193304; 19-193298
B 6	530 Le Hybrid 01/15 – 05/17	160 kW	24-178488  24-178495 	24-176255 	with standard chassis FA: 24-178495; 24-178488
B 8	530 Le Hybrid 01/15 – 05/17	160 kW	24-178501  24-178518 		with M-technology FA: 24-178518; 24-178501
B16 PSS10	530 Le Hybrid 01/15 – 05/17	160 kW	48-177580		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm

BMW (BRILLIANCE) 5 SERIES (G38)					
B 4	530 Le Hybrid, 535 Le Hybrid 08/18 – /	135 – 185 kW	19-276885  19-276892 	19-280981 	with standard chassis FA: 19-276892; 19-276885
B 4	530 Le Hybrid, 535 Le Hybrid 08/18 – /	135 – 185 kW	19-276908  19-276915 	19-280998 	with off-road suspension FA: 19-276915; 19-276908
B 4	530 Le Hybrid, 535 Le Hybrid 08/18 – /	135 – 185 kW	19-274355  19-274362 	19-274379 	with M-technology FA: 19-274362; 19-274355
B 6	530 Le Hybrid, 535 Le Hybrid 08/18 – /	135 – 185 kW	24-279772  24-281072 	24-279789 	without electronic suspension control; with standard chassis FA: 24-281072; 24-279772
B 8	530 Le Hybrid, 535 Le Hybrid 08/18 – /	135 – 185 kW	24-279772  24-281072 	24-296472 	without electronic suspension control FA: 24-281072; 24-279772
B16 PSS10	530 Le Hybrid, 535 Le Hybrid 08/18 – /	135 – 185 kW	48-279765		without electronic suspension control; Threaded Suspension (height adjustable); Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1125 kg RA: Axle load [kg] to 1405 kg

BMW (BRILLIANCE) X1 (F49)					
B 4	xDrive25 Le 09/16 – /	100 kW	22-247070  22-247087 	19-247090 	without electronic suspension control; with standard chassis FA: 22-247087; 22-247070
B 4	xDrive25 Le 09/16 – /	100 kW	22-252944  22-252951 	19-247090 	without electronic suspension control; with M-technology FA: 22-252951; 22-252944
B 4	xDrive30 Le xDrive 10/19 – /	100 kW	22-247070  22-247087 	19-247090 	without electronic suspension control FA: 22-247087; 22-247070
B 4	xDrive30 Le xDrive 10/19 – /	100 kW	22-252944  22-252951 	19-252988 	without electronic suspension control; with M-technology FA: 22-252951; 22-252944
B 6	xDrive30 Le xDrive 10/19 – /	100 kW	22-247049  22-247056 	24-247061 	without EDC; with standard chassis FA: 22-247056; 22-247049
B 8	xDrive25 Le 09/16 – /	100 kW	22-251985  22-252005 	24-251990 	without EDC; with M-technology FA: 22-252005; 22-251985
B 8	xDrive30 Le xDrive 10/19 – /	100 kW	22-251985  22-252005 	24-251990 	without EDC; with M-technology FA: 22-252005; 22-251985
B12 PK	xDrive30 Le xDrive 10/19 – /	100 kW	46-275110		Conditions see certificates; without leveling control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1110 kg RA: Axle load [kg] to 1080 kg

BUICK (SGM)					
BUICK (SGM) EXCELLE GT (SK1)					
B 4	MHEV 04/20 – /	120 kW	22-257574  22-261571 	19-257587 	without electronic suspension control FA: 22-261571; 22-257574
B 4	MHEV 04/20 – /	120 kW		19-263755 	with off-road suspension
B 6	MHEV 04/20 – /	120 kW	35-257554  35-261612 	24-257565 	without electronic suspension control FA: 35-261612; 35-257554
B 8	MHEV 04/20 – /	120 kW	35-261582  35-261599 	24-267076 	without electronic suspension control FA: 35-261599; 35-261582
B14	MHEV 04/20 – /	120 kW	47-257597		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm; Axle load [kg] to 1020 kg



--	--	--	--

BUICK (SGM)

BUICK (SGM) LACROSSE (CW2, CW3)

B 4	2.4 Hybrid 07/08 – 07/09	125 kW	22-183675 22-183682		19-183664	without FlexRide; with standard chassis FA: 22-183682; 22-183675
B 6	2.4 Hybrid 07/08 – 07/09	125 kW	35-167990 35-168003		24-168014	without FlexRide; with standard chassis FA: 35-168003; 35-167990
B 8	2.4 Hybrid 07/08 – 07/09	125 kW	35-168027 35-168034		24-168045	without FlexRide; with sports suspension FA: 35-168034; 35-168027

BUICK (SGM) LACROSSE (EG2)

B 4	2.4 Hybrid 08/11 – 12/15	137 kW	22-183675 22-183682		19-183664	without FlexRide; with standard chassis FA: 22-183682; 22-183675
B 6	2.4 Hybrid 08/11 – 12/15	137 kW	35-167990 35-168003		24-168014	without FlexRide; with standard chassis FA: 35-168003; 35-167990
B 8	2.4 Hybrid 08/11 – 12/15	137 kW	35-168027 35-168034		24-168045	without FlexRide; with sports suspension FA: 35-168034; 35-168027

CHEVROLET

CHEVROLET SILVERADO 1500 Crew Cab Pickup

B 6 4600	6.0 Flex/Hybrid, 6.0 Flex/Hybrid 4WD 09/09 – 12/13	248 kW	24-188227			without electronic suspension control
B 8	6.0 Flex/Hybrid, 6.0 Flex/Hybrid 4WD 09/09 – 12/13	248 kW	24-186940		24-293082	without roadworthy certificate; without electronic suspension control FA: Lifting ca. [mm] 0-45 mm; Length 2 [mm]: 469,3 mm RA: Lifting ca. [mm] 0-25 mm

CHEVROLET SILVERADO 1500 Extended Cab Pickup

B 6 4600	5.3 Hybrid 09/03 – 12/07	220 kW	24-029025			Vehicle Type: GMT800 Chassis; for coil-spring suspension vehicles; Vehicle Type: Heavy Duty
B 6 4600	5.3 Hybrid AWD 09/03 – 12/07	220 kW			24-029056	with standard chassis; Vehicle Type: GMT800 Chassis; Vehicle Type: Incl. Classic
B 8	5.3 Hybrid AWD 09/03 – 12/07	220 kW	24-186643		24-186742	Vehicle Type: GMT800 Chassis; Vehicle Type: Incl. Classic; without roadworthy certificate FA: Lifting ca. [mm] 0-65 mm; Length 2 [mm]: 414 mm RA: Lifting ca. [mm] 0-25 mm; Length 2 [mm]: 664,2 mm
B 8	5.3 Hybrid AWD 09/03 – 12/07	220 kW	24-185950		24-191203	Vehicle Type: GMT800 Chassis; Vehicle Type: Incl. Classic; without roadworthy certificate FA: Lifting ca. [mm] 100 mm; Length 2 [mm]: 543 mm RA: Lifting ca. [mm] 50 mm; Length 2 [mm]: 695 mm
B 8	5.3 Hybrid AWD 09/03 – 12/07	220 kW	24-185950		24-186636	Vehicle Type: GMT800 Chassis; Vehicle Type: Incl. Classic; without roadworthy certificate FA: Lifting ca. [mm] 150 mm; Length 2 [mm]: 543 mm RA: Lifting ca. [mm] 100 mm; Length 2 [mm]: 760 mm

CHEVROLET SILVERADO 2500

B 6 4600	5.3 Hybrid 09/07 – 09/09	220 kW	24-060813		24-060820	with standard chassis
B 8	5.3 Hybrid 09/07 – 09/09	220 kW	33-174525 24-186735		24-186742	without roadworthy certificate FA: Lifting ca. [mm] 0-65 mm; Length 2 [mm]: 400 mm RA: Lifting ca. [mm] 0-25 mm; Length 2 [mm]: 664,2 mm
B 8	5.3 Hybrid 09/07 – 09/09	220 kW	33-174525 24-187183		24-191203	without roadworthy certificate FA: Lifting ca. [mm] 100 mm; Length 2 [mm]: 545 mm RA: Lifting ca. [mm] 50 mm; Length 2 [mm]: 695 mm
B 8	5.3 Hybrid 09/07 – 09/09	220 kW	33-174525 24-187183		24-186636	without roadworthy certificate FA: Lifting ca. [mm] 150 mm; Length 2 [mm]: 545 mm RA: Lifting ca. [mm] 100 mm; Length 2 [mm]: 760 mm

CHEVROLET TAHOE (GMT900)

B 6 4600	6.0 Flex/Hybrid, 6.0 Flex/Hybrid 4WD 09/09 – 12/13	248 kW	24-186926		24-186933	without electronic suspension control
B 8	6.0 Flex/Hybrid, 6.0 Flex/Hybrid 4WD 09/09 – 12/13	248 kW	24-186940		24-187237	without electronic suspension control; without roadworthy certificate FA: Lifting ca. [mm] 0-45 mm; Length 2 [mm]: 469,3 mm RA: Lifting ca. [mm] 0-25 mm; Length 2 [mm]: 618 mm

CHEVROLET VOIT

B 3	EV 150 05/15 – /	111 kW	36-241910			with standard chassis FA: Coil spring with constant wire diameter
B 4	EV 150 05/15 – /	111 kW	22-232496 22-232502		19-232515	with standard chassis FA: 22-232502; 22-232496


CHRYSLER
CHRYSLER ASPEN (HG)

B 6 4600	5.7 Hybrid AWD 12/08 - /	246 kW	24-139106	24-139113	with standard chassis
-------------	-----------------------------	--------	-----------	-----------	-----------------------

CITROËN
CITROËN BERLINGO Box Body/MPV (B9)

B 1	Electric 01/13 - /	35 - 49 kW	12-117932		
B 4	Electric 01/13 - /	35 kW	22-226716 22-226723 11-270676	19-226750	with standard chassis FA: 22-226723; 22-226716 RA: Payload to: 600 kg
B 4	Electric 01/13 - /	35 kW	22-226716 22-226723 11-270676	19-226736	with standard chassis FA: 22-226723; 22-226716 RA: Payload to: 800 kg; Payload to: 1000 kg

CITROËN C5 AIRCROSS (A_)

B 4	1.6 Hybrid 225 04/20 - /	165 kW	22-313904	19-322940	with standard chassis
-----	-----------------------------	--------	-----------	-----------	-----------------------

CUPRA
CUPRA BORN (K11)

B 4	45, 58, 58 e-boost, 77 e-boost 08/21 - /	110 - 170 kW	22-323521		without electronic suspension control
B 6	45, 58, 58 e-boost, 77 e-boost 08/21 - /	110 - 170 kW	22-323606	24-323604	without electronic suspension control; with sports suspension
ES	45, 58, 58 e-boost, 77 e-boost 08/21 - /	110 - 170 kW		47-324466	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates

CUPRA FORmentor (KM7)

B 1	1.4 e-Hybrid, VZ 1.4 e-Hybrid 01/21 - /	150 - 180 kW		14-292330	with electronic suspension control
B 4	1.4 e-Hybrid, VZ 1.4 e-Hybrid 01/21 - /	150 - 180 kW	22-297075	19-342016	with standard chassis; without electronic suspension control FA: Strut outside diameter [mm] 55mm
B 6	1.4 e-Hybrid, VZ 1.4 e-Hybrid 01/21 - /	150 - 180 kW	35-273806	24-267137	with standard chassis FA: Strut outside diameter [mm] 55mm RA: Multilink Axle
ES	1.4 e-Hybrid, VZ 1.4 e-Hybrid 01/21 - /	150 - 180 kW		47-334373	Multilink Axle; Strut outside diameter [mm] 55mm; Threaded Suspension (height adjustable); Conditions see certificates; without electronic suspension control

CUPRA LEON (KL1)

B 1	1.4 e-HYBRID, VZ 1.4 e-HYBRID 09/20 - /	150 - 180 kW		14-292330	with electronic suspension control
B 4	1.4 e-HYBRID 09/20 - /	150 kW	22-297075 22-297082	19-334042	with standard chassis FA: Strut outside diameter [mm] 55mm RA: Rigid Axle
B 6	1.4 e-HYBRID, VZ 1.4 e-HYBRID 09/20 - /	150 - 180 kW	35-229872	24-267137	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
ES	1.4 e-HYBRID, VZ 1.4 e-HYBRID 09/20 - /	150 - 180 kW		47-327030	with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg

CUPRA LEON Sportstourer (KL8)

B 1	1.4 e-HYBRID, VZ 1.4 e-HYBRID 09/20 - /	150 - 180 kW		14-292330	with electronic suspension control
B 4	1.4 e-HYBRID 09/20 - /	150 kW	22-297082 22-297075	19-334042	with standard chassis FA: Strut outside diameter [mm] 55mm RA: Rigid Axle
B 4	1.4 e-HYBRID 09/20 - /	150 kW		19-230542	Rigid Axle; with sports suspension RA: for PR number: 1JA; for PR number: 1JC; for PR number: OK0; Piston conrod diameter [mm] 11mm

CUPRA					
CUPRA LEON Sportstourer (KL8)					
B 6	1.4 e-HYBRID, VZ 1.4 e-HYBRID 09/20 - /	150 - 180 kW	35-229872 ↑	24-267137 ↓	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
ES	1.4 e-HYBRID, VZ 1.4 e-HYBRID 09/20 - /	150 - 180 kW	47-327030		with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg

**C
F**

DODGE					
DODGE DURANGO (HB)					
B 6 4600	5.7 Hybrid 4WD 09/08 - 12/09	287 kW	24-139106 ○	24-139113 ○	with standard chassis

DS					
DS DS 3 CROSSBACK (UR_, UC_, UJ_)					
B 4	E-TENSE 05/19 - /	100 - 120 kW	22-328298 ↓ 22-328304 ↓	19-343488 ○	FA: 22-328304; 22-328298

FIAT					
FIAT PANDA (312_, 319_)					
B 4	1.0 Mild Hybrid 01/20 - /	51 kW	22-260390 ↓ 22-260406 ↓	19-260419 ○	with standard chassis; not: Trekking FA: 22-260406; 22-260390

FIAT ULYSSE Bus					
B 6	E-ULYSSE 01/22 - /	100 kW		24-290418 ○	with standard chassis

FIAT 500 C (312_)					
B14	E 09/12 - /	83 kW	47-270169		with Xenon light; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 830 kg RA: Axle load [kg] to 630 kg

FIAT 500e (332_)					
B 4	Elektro 10/20 - /	70 kW	22-338396 ↓ 22-338402 ↓	19-333885 ○	with standard chassis; Vehicle Type: ZFA FA: 22-338402; 22-338396 RA: Vehicle Type: Battery with 24kWh
B 4	Elektro 3+1 10/20 - /	87 kW	22-338396 ↓ 22-338402 ↓	19-333830 ○	with standard chassis; Vehicle Type: ZFA FA: 22-338402; 22-338396 RA: Vehicle Type: Battery with 42kWh

FIAT 500e Convertible (332_)					
B 4	Elektro 10/20 - /	70 - 87 kW	22-338396 ↓ 22-338402 ↓	19-333830 ○	Vehicle Type: ZFA; with standard chassis FA: 22-338402; 22-338396 RA: Vehicle Type: Battery with 42kWh

FORD					
FORD FIESTA VII (HJ, HF)					
B 4	1.0 EcoBoost mHEV 11/19 - /	92 - 114 kW	22-275653 ↓ 22-283580 ↓	19-275666 ○	with standard chassis FA: 22-283580; with sports suspension; 22-275653
B 4	1.0 EcoBoost mHEV 11/19 - /	92 - 114 kW	22-275653 ↓ 22-283580 ↓	19-289021 ○	Vehicle Type: ST-Line; with sports suspension FA: 22-283580; with standard chassis; 22-275653
B 4	1.0 EcoBoost mHEV Active 01/21 - /	92 - 114 kW	22-290236 ↓ 22-290243 ↓	19-289038 ○	Vehicle Type: Active; for vehicles with increased ground clearance FA: 22-290243; 22-290236
B 6	1.0 EcoBoost mHEV 11/19 - /	92 - 114 kW	22-275677 ↓ 22-287069 ↓	24-275682 ○	with standard chassis; with sports suspension FA: 22-287069; 22-275677
B 6	1.0 EcoBoost mHEV 11/19 - /	92 - 114 kW	22-275691 ↓ 22-298973 ↓	24-298995 ○	with sports suspension; Vehicle Type: ST FA: 22-298973; 22-275691



FORD

FORD FIESTA VII (HJ, HF)

B12 PK	1.0 EcoBoost mHEV 11/19 - /	92 - 114 kW	46-336378		with standard chassis; without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 860 kg RA: Axle load [kg] to 850 kg
B14	1.0 EcoBoost mHEV 11/19 - /	92 - 114 kW	47-275713		with standard chassis; Conditions see certificates FA: Lowering ca. [mm]: 20-55 mm; Axle load [kg] to 915 kg RA: Lowering ca. [mm]: 30-45 mm; Axle load [kg] to 860 kg
B14	1.0 EcoBoost mHEV 11/19 - /	92 - 114 kW	47-275713		with sports suspension; Vehicle Type: ST-Line; Conditions see certificates FA: Lowering ca. [mm]: 10-45 mm; Axle load [kg] to 915 kg RA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 860 kg

FORD FIESTA VII Van

B 4	1.0 EcoBoost mHEV 06/20 - /	92 kW	22-275653 22-283580		19-275666	with standard chassis FA: 22-283580; with sports suspension; 22-275653
B 4	1.0 EcoBoost mHEV 06/20 - /	92 kW	22-290236 22-290243		19-289038	Number of Doors 5 FA: 22-290243; 22-290236 RA: with sports suspension
B 6	1.0 EcoBoost mHEV 06/20 - /	92 kW	22-275677 22-287069		24-275682	with standard chassis FA: 22-287069; 22-275677
B14	1.0 EcoBoost mHEV 06/20 - /	92 kW	47-275713			with standard chassis; Conditions see certificates FA: Lowering ca. [mm]: 20-55 mm; Axle load [kg] to 890 kg RA: Lowering ca. [mm]: 30-45 mm; Axle load [kg] to 840 kg

FORD FOCUS IV (HN)

B 1	1.0 EcoBoost mHEV Active, 1.0 EcoBoost mHEV 06/20 - /	92 - 114 kW	14-320699			with electronic suspension control
-----	--	-------------	-----------	--	--	------------------------------------

FORD FOCUS IV Turnier (HP)

B 1	1.0 EcoBoost mHEV 07/20 - /	92 - 114 kW	14-320699			with electronic suspension control
B 4	1.0 EcoBoost mHEV 07/20 - /	92 - 114 kW	22-295804 22-295903			with standard chassis; with off-road suspension FA: 22-295903; 22-295804

FORD GALAXY III (CK)

B 4	2.5 FHEV 07/21 - /	140 kW	22-263155 22-264688		19-263168	with standard chassis FA: 22-264688; 22-263155
B 4	2.5 FHEV 07/21 - /	140 kW	22-290885 22-290892		19-289588	with sports suspension FA: 22-290892; 22-290885
B 6	2.5 FHEV 07/21 - /	140 kW	35-264651 35-264668		24-264679	FA: 35-264668; 35-264651

FORD KUGA III (DFK)

B 4	2.0 EcoBlue mHEV, 2.5 FHEV, 2.5 FHEV 4x4, 2.5 Duratec Plug-in-Hybrid 07/19 - /	110 - 165 kW	22-317339 22-317346		19-317380	with standard chassis FA: 22-317346; 22-317339
-----	--	--------------	------------------------	--	-----------	---

FORD MONDEO V Saloon (CD)

B 4	2.0 Hybrid 08/14 - /	105 - 140 kW	22-250315 22-250322		19-250335	with standard chassis; without leveling control FA: 22-250322; 22-250315
B 4	2.0 Hybrid 08/14 - /	105 - 140 kW	22-263773 22-263780		19-263793	with sports suspension; without leveling control FA: 22-263780; 22-263773
B 4	2.0 Hybrid 09/14 - /	138 - 140 kW	22-250315 22-250322		19-250335	with standard chassis; without leveling control FA: 22-250322; 22-250315
B 6	2.0 Hybrid 08/14 - /	105 - 140 kW	35-252108 35-252115		24-252126	FA: 35-252115; 35-252108
B 6	2.0 Hybrid 09/14 - /	138 - 140 kW	35-252108 35-252115		24-252126	FA: 35-252115; 35-252108
B 8	2.0 Hybrid 08/14 - /	105 - 140 kW	35-252139 35-252146		24-252157	with sports suspension; without leveling control FA: 35-252146; 35-252139

FORD MONDEO V Turnier (CF)

B 4	2.0 Hybrid iVCT 01/19 - /	138 kW	22-250315 22-250322		19-250335	with standard chassis; without leveling control FA: 22-250322; 22-250315
B 4	2.0 Hybrid iVCT 01/19 - /	138 kW	22-263773 22-263780		19-263793	with sports suspension; without leveling control FA: 22-263780; 22-263773

FORD					
FORD MONDEO V Turnier (CF)					
B 6	2.0 Hybrid iVCT 01/19 - /	138 kW	35-252108 35-252115	 	24-252126 with standard chassis; without leveling control FA: 35-252115; 35-252108
B 8	2.0 Hybrid iVCT 01/19 - /	138 kW	35-252139 35-252146	 	24-252157 with sports suspension; without leveling control FA: 35-252146; 35-252139
FORD PUMA (J2K, CF7)					
B 4	1.0 EcoBoost mHEV 09/19 - /	92 – 114 kW	22-317353 22-317360	 	19-317373 with standard chassis FA: 22-317360; 22-317353
B 4	1.0 EcoBoost mHEV 09/19 - /	92 – 114 kW	22-319753 22-319760	 	19-317373 with sports suspension FA: 22-319760; 22-319753
FORD S-MAX (CJ, WA6)					
B 4	2.5 FHEV 07/21 - /	140 kW	22-263155 22-264688	 	19-263168 with standard chassis FA: 22-264688; 22-263155
B 4	2.5 FHEV 07/21 - /	140 kW	22-290885 22-290892	 	19-289588 with sports suspension FA: 22-290892; 22-290885
B 6	2.5 FHEV 07/21 - /	140 kW	35-264651 35-264668	 	24-264679 FA: 35-264668; 35-264651
FORD TOURNEO CUSTOM V362 Bus (F3)					
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 136 kW	22-328540		19-246444 Trim Level 250/260/270/280/290; Trim Level 300/310; with standard chassis FA: 06/19 →
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 136 kW	22-328564		19-258997 Trim Level 330/290S Sport; with standard chassis FA: 06/19 →
B 6	2.0 EcoBlue mHEV 05/19 - /	96 – 136 kW	22-328557		24-272544 with standard chassis FA: 05/19 →
B14	2.0 EcoBlue mHEV 05/19 - /	96 – 136 kW	47-292055		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1750 kg RA: Lowering ca. [mm]: 0 mm
FORD TRANSIT V363 Bus (FAD, FBD)					
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-249346 RA: Length 2 [mm]: 509 mm; Length 1 [mm]: 330 mm; Length [mm]: 549 mm; for OE number: 1 911 848; for OE number: 1 828 695; for OE number: 1 828 696; for OE number: BK31-18080-BD; for OE number: BK31-18080-JD; for OE number: FK31-18080-LA; for OE number: 1 828 698; for OE number: BK31-18080-AD; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-255569 RA: Length 2 [mm]: 594 mm; Length 1 [mm]: 375 mm; for OE number: 1 828 697; for OE number: BK31-18080-CD; Length [mm]: 634 mm
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-255576 RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 408 mm; for OE number: 1 843 164; for OE number: 1 842 637; for OE number: CK41-18080-DC; for OE number: BK31-18080-UC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm; Reinforced Version
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-255583 RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 410 mm; for OE number: 1 843 163; for OE number: 5 272 913; for OE number: CK41-18080-AC; for OE number: CK41-18080-CC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
FORD TRANSIT V363 Van (FCD, FDD)					
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-249346 RA: Length 2 [mm]: 509 mm; Length 1 [mm]: 330 mm; Length [mm]: 549 mm; for OE number: 1 911 848; for OE number: 1 828 695; for OE number: 1 828 696; for OE number: BK31-18080-BD; for OE number: BK31-18080-JD; for OE number: FK31-18080-LA; for OE number: 1 828 698; for OE number: BK31-18080-AD; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-255569 RA: Length 2 [mm]: 594 mm; Length 1 [mm]: 375 mm; for OE number: 1 828 697; for OE number: BK31-18080-CD; Length [mm]: 634 mm
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-255576 RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 408 mm; for OE number: 1 843 164; for OE number: 1 842 637; for OE number: CK41-18080-DC; for OE number: BK31-18080-UC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm; Reinforced Version
B 4	2.0 EcoBlue mHEV 05/19 - /	96 – 125 kW	22-257277		19-255583 RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 410 mm; for OE number: 1 843 163; for OE number: 5 272 913; for OE number: CK41-18080-AC; for OE number: CK41-18080-CC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm



F

FORD					
FORD TRANSIT V363 Van (FCD, FDD)					
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-249346	RA: Length 2 [mm]: 509 mm; Length 1 [mm]: 330 mm; Length [mm]: 549 mm; for OE number: 1 911 848; for OE number: 1 828 695; for OE number: 1 828 696; for OE number: BK31-18080-BD; for OE number: BK31-18080-JD; for OE number: FK31-18080-LA; for OE number: 1 828 698; for OE number: BK31-18080-AD; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-255569	RA: Length 2 [mm]: 594 mm; Length 1 [mm]: 375 mm; for OE number: 1 828 697; for OE number: BK31-18080-CD; Length [mm]: 634 mm
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-255576	RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 408 mm; for OE number: 1 843 164; for OE number: 1 842 637; for OE number: CK41-18080-DC; for OE number: BK31-18080-UC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm; Reinforced Version
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-255583	RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 410 mm; for OE number: 1 843 163; for OE number: 5 272 913; for OE number: CK41-18080-AC; for OE number: CK41-18080-CC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 6	2.0 EcoBlue mHEV 05/19 - / 96 - 125 kW	22-338075	↑	24-338097	Vehicle Type: Camper RA: Length 1 [mm]: 331 mm; Length 2 [mm]: 504 mm; Length [mm]: 552 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 6	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249357	↑	24-277846	RA: Length 2 [mm]: 510 mm; Length 1 [mm]: 330 mm; for OE number: 1 828 695; for OE number: 1 828 696; for OE number: 1 828 698
B 6 DMC	2.0 EcoBlue mHEV 05/19 - / 96 - 125 kW	22-338082	↑	24-338103	Vehicle Type: Camper Advance RA: Length 1 [mm]: 331 mm; Length 2 [mm]: 504 mm; Length [mm]: 552 mm
FORD TRANSIT V363 Platform/Chassis (FED, FFD)					
B 4	2.0 EcoBlue mHEV 05/19 - / 96 - 125 kW	22-257277	↑	19-249346	RA: Length 2 [mm]: 509 mm; Length 1 [mm]: 330 mm; Length [mm]: 549 mm; for OE number: 1 911 848; for OE number: 1 828 695; for OE number: 1 828 696; for OE number: BK31-18080-BD; for OE number: BK31-18080-JD; for OE number: FK31-18080-LA; for OE number: 1 828 698; for OE number: BK31-18080-AD; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 4	2.0 EcoBlue mHEV 05/19 - / 96 - 125 kW	22-257277	↑	19-255569	RA: Length 2 [mm]: 594 mm; Length 1 [mm]: 375 mm; for OE number: 1 828 697; for OE number: BK31-18080-CD; Length [mm]: 634 mm
B 4	2.0 EcoBlue mHEV 05/19 - / 96 - 125 kW	22-257277	↑	19-255576	RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 408 mm; for OE number: 1 843 164; for OE number: 1 842 637; for OE number: CK41-18080-DC; for OE number: BK31-18080-UC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm; Reinforced Version
B 4	2.0 EcoBlue mHEV 05/19 - / 96 - 125 kW	22-257277	↑	19-255583	RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 410 mm; for OE number: 1 843 163; for OE number: 5 272 913; for OE number: CK41-18080-AC; for OE number: CK41-18080-CC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-249346	RA: Length 2 [mm]: 509 mm; Length 1 [mm]: 330 mm; Length [mm]: 549 mm; for OE number: 1 911 848; for OE number: 1 828 695; for OE number: 1 828 696; for OE number: BK31-18080-BD; for OE number: BK31-18080-JD; for OE number: FK31-18080-LA; for OE number: 1 828 698; for OE number: BK31-18080-AD; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-255569	RA: Length 2 [mm]: 594 mm; Length 1 [mm]: 375 mm; for OE number: 1 828 697; for OE number: BK31-18080-CD; Length [mm]: 634 mm
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-255576	RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 408 mm; for OE number: 1 843 164; for OE number: 1 842 637; for OE number: CK41-18080-DC; for OE number: BK31-18080-UC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm; Reinforced Version
B 4	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249333	↑	19-255583	RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 410 mm; for OE number: 1 843 163; for OE number: 5 272 913; for OE number: CK41-18080-AC; for OE number: CK41-18080-CC; Length [mm]: 702 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 6	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249357	↑	24-277846	RA: Length 2 [mm]: 510 mm; Length 1 [mm]: 330 mm; for OE number: 1 828 695; for OE number: 1 828 696; for OE number: 1 828 698
B 6	2.0 EcoBlue mHEV RWD 05/19 - / 96 - 125 kW	22-249357	↑	24-265331	RA: Length 2 [mm]: 657 mm; Length 1 [mm]: 410 mm; Length [mm]: 698 mm

FORD USA			
FORD USA ESCAPE			
B 4	2.3 Hybrid 4x4, 2.3 Hybrid 09/05 – 07/07 115 kW		19-165998
B 4	2.5 Hybrid, 2.5 Hybrid 4WD 09/08 – 12/12 132 kW		19-165998
FORD USA MUSTANG MACH-E (CGW)			
B 4	EV, EV 4x4, First Edition, EV GT 4x4 07/20 – / 190 – 358 kW	22-343222 22-343239	19-343266 with standard chassis FA: 22-343239; 22-343222

GMC			
GMC YUKON (GMT900)			
B 6 4600	6.0 Hybrid, 6.0 Hybrid 4WD, 6.0 Flex/Hybrid, 6.0 Flex/Hybrid 4WD 09/07 – 12/13 248 kW	24-186926	24-186933 without electronic suspension control
B 8	6.0 Hybrid, 6.0 Hybrid 4WD, 6.0 Flex/Hybrid, 6.0 Flex/Hybrid 4WD 09/07 – 12/13 248 kW	24-186940	24-187237 without electronic suspension control; without roadworthy certificate FA: Lifting ca. [mm] 0-45 mm; Length 2 [mm]: 469,3 mm RA: Lifting ca. [mm] 0-25 mm; Length 2 [mm]: 618 mm

HONDA			
HONDA CIVIC VII Saloon (ES, ET)			
B 1	1.3 IMA 10/03 – 09/05 61 kW	12-263837 12-263844	FA: 12-263844; 12-263837
B 4	1.3 IMA 10/03 – 09/05 61 kW		19-144948 Thread Size: M14; with standard chassis
B 6	1.3 IMA 10/03 – 09/05 61 kW	35-115298 	Thread Size: M16; with standard chassis FA: 35-115304

HONDA CIVIC VIII Saloon (FD, FA)			
B 4	1.3 IMA 09/05 – 02/12 70 – 85 kW	22-213983 22-213990	with standard chassis FA: 22-213990; 22-213983

HONDA CR-V V (RW_, RT_)			
B 4	2.0 e-CVT Hybrid, 2.0 2.0 E-CVT HYBRID AWD AWD 12/18 – / 107 – 158 kW	22-290939 22-290946	19-290959 19-290966 FA: 22-290946; 22-290939 RA: 19-290966; 19-290959
B 6	2.0 e-CVT Hybrid, 2.0 2.0 E-CVT HYBRID AWD AWD 12/18 – / 107 – 158 kW	22-291219 22-291776	24-295864 24-295871 FA: 22-291776; 22-291219 RA: 24-295871; 24-295864

HONDA JAZZ III (GE_, GG_, GP_, ZA_)			
B 4	1.3 HYBRID 04/11 – / 65 kW	22-213808 22-213815	19-213828 FA: 22-213815; 22-213808
B14	1.3 HYBRID 04/11 – / 65 kW	47-172401	Threaded Suspension (height adjustable); without electronic suspension control; without roadworthy certificate FA: Lowering ca. [mm]: 20-45 mm RA: Lowering ca. [mm]: 15-45 mm

HONDA JAZZ IV (GK_)			
B 4	EV 01/14 – / 92 kW	22-213808 22-213815	19-213828 FA: 22-213815; 22-213808
B14	EV 01/14 – / 92 kW	47-172401	Threaded Suspension (height adjustable); without electronic suspension control; without roadworthy certificate FA: Lowering ca. [mm]: 20-45 mm RA: Lowering ca. [mm]: 15-45 mm

HONDA JAZZ V (GR_)			
B14	1.5 eHEV 02/20 – / 80 kW	47-327764	Threaded Suspension (height adjustable); Conditions see certificates FA: Lowering ca. [mm]: 35-55 mm RA: Lowering ca. [mm]: 15-45 mm
B14	1.5 eHEV 02/20 – / 80 kW	14-348884	only in connection with 14-348884; Threaded Suspension (height adjustable); without electronic suspension control; without roadworthy certificate FA: Lowering ca. [mm]: 20-45 mm RA: Lowering ca. [mm]: 15-45 mm
B14	1.5 eHEV 02/20 – / 80 kW	14-348884	Lowering ca. [mm]: 0-30 mm; only in connection with 14-348884





HYUNDAI

HYUNDAI BAYON (BC3)

B 4	1.0 T-GDI 48V-Hybrid 05/21 - /	74 – 88 kW	22-342614 22-342621		19-330198	with standard chassis
-----	-----------------------------------	------------	------------------------	--	-----------	-----------------------

HYUNDAI ELANTRA V Saloon (MD, UD)

B 4	1.6 Hybrid 09/10 – 08/15	84 kW	22-238405 22-238412		19-238425	FA: 22-238412; 22-238405
-----	-----------------------------	-------	------------------------	--	-----------	--------------------------

HYUNDAI IONIQ (AE)

B 4	1.6 GDI Hybrid, 1.6 GDI Plug-in Hybrid 03/16 - /	77 – 104 kW	22-332202 22-332219		19-338651	with standard chassis FA: 22-332219; 22-332202
B 4	Electric 03/16 - /	88 kW	22-340504 22-340511		19-332222	with standard chassis FA: 22-340511; 22-340504 RA: →11/19
B 4	Electric 03/16 - /	88 kW	22-340504 22-340511		19-338644	with standard chassis FA: 22-340511; 22-340504 RA: 12/19→
B 4	Electric 07/19 - /	100 kW	22-340528 22-340535		19-332222	with standard chassis FA: 22-340535; 22-340528 RA: →11/19
B 4	Electric 07/19 - /	100 kW	22-340528 22-340535		19-338644	with standard chassis FA: 22-340535; 22-340528 RA: 12/19→

HYUNDAI IONIQ 5 (NE)

B 4	EV 05/21 - /	125 – 239 kW	22-343512 22-343529		19-340357	FA: 22-343529; 22-343512
-----	-----------------	--------------	------------------------	--	-----------	--------------------------

HYUNDAI KONA (OS, OSE, OSI)

B 4	EV 04/18 - /	100 – 150 kW	22-320988 22-323439		19-323367	with standard chassis FA: 22-323439; 22-320988
B 4	1.0 T-GDi Hybrid 48V, 1.6 CRDi Hybrid 48V 11/20 - /	88 – 100 kW	22-320988 22-323439		19-320991	with standard chassis FA: 22-323439; 22-320988
B 4	1.6 CRDi Hybrid 48V 4WD 11/20 - /	100 kW	22-320988 22-323439		19-323367	with standard chassis FA: 22-323439; 22-320988

HYUNDAI i20 III (BC3, BI3)

B 4	1.0 T-GDI hybrid 48V 08/20 - /	74 – 88 kW	22-325976 22-325983		19-325996	with standard chassis FA: 22-325983; 22-325976
-----	-----------------------------------	------------	------------------------	--	-----------	---

HYUNDAI TUCSON (NX4E, NX4A)

B 4	1.6 T-GDi Hybrid 48V, 1.6 T-GDi Hybrid 48V HTRAC, 1.6 T-GDi Hybrid, 1.6 T-GDi Hybrid HTRAC, 1.6 T-GDi Plug-in-Hybrid HTRAC, 1.6 CRDi Hybrid 48V, 1.6 CRDi Hybrid 48V HTRAC 11/20 - /	100 – 195 kW	22-335913 22-335920		19-342658	with standard chassis FA: 22-335920; 22-335913
-----	--	--------------	------------------------	--	-----------	---

JAGUAR

JAGUAR I-PACE (X590)

B 4	EV400 AWD 02/18 - /	294 kW			19-322612	
-----	------------------------	--------	--	--	-----------	--

JEEP

JEEP COMPASS (MP, M6, MV, M7)

B 4	1.3 Hybrid 4x4, 1.5 T4 Hybrid 04/20 - /	96 – 177 kW	22-310491 22-310507		22-283788 22-283795	with standard chassis FA: 22-310507; 22-310491 RA: 22-283795; 22-283788
-----	--	-------------	------------------------	--	------------------------	---

JEEP RENEGADE SUV (BU, B1, BV)

B 4	1.3 PHEV 4Xe 08/20 - /	140 – 177 kW	22-267504 22-267511		22-260987 22-260994	All-wheel Drive; with standard chassis; Mounting bores distance [mm] 72 FA: 22-267511; 22-267504 RA: 22-260994; 22-260987
B 6	1.3 PHEV 4Xe 08/20 - /	140 – 177 kW	22-266842 22-266859		22-259738 22-259745	All-wheel Drive; with standard chassis; Mounting bores distance [mm] 72 FA: 22-266859; 22-266842 RA: 22-259745; 22-259738



JEEP			
JEEP RENEGADE SUV (BU, B1, BV)			
B14	1.3 PHEV 4xe 08/20 - /	140 - 177 kW	47-265417 All-wheel Drive; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Mounting bores distance [mm] 72; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1150 kg RA: Axle load [kg] to 1000 kg

JEEP WRANGLER IV (JL)			
B12 LK	2.0 4xe Plug-in Hybrid, 2.0 Mild Hybrid 11/17 - /	195 - 280 kW	46-340191 Vehicle Type: short wheel base; Vehicle Type: with OE bumper; without roadworthy certificate; Lifting ca. [mm] 50 mm FA: Axle load [kg] to 1224 kg RA: Axle load [kg] to 1360 kg
B12 LK	2.0 4xe Plug-in Hybrid, 2.0 Mild Hybrid 11/17 - /	195 - 280 kW	46-340207 Vehicle Type: short wheel base; Vehicle Type: with Asfir bumper; Vehicle Type: with Asfir winch; without roadworthy certificate; Lifting ca. [mm] 50 mm FA: Axle load [kg] to 1224 kg RA: Axle load [kg] to 1360 kg

KIA			
KIA RIO IV (YB, SC, FB)			
B 4	1.0 T-GDi 120 Eco-Dynamics+ 02/17 - /	88 kW	22-327154 22-327161 19-327181
B 4	1.0 T-GDi 120 Eco-Dynamics+ 02/17 - /	88 kW	22-331212 22-331229 19-327181

KIA SOUL III (SK3)			
B 4	E-SOUL 01/19 - /	100 - 150 kW	22-332165 22-332172 19-341972

KIA SPORTAGE IV (QL, QLE)			
B 4	1.6 CRDi Eco-Dynamics+, 1.6 CRDi Eco-Dynamics+ AWD, 2.0 CRDi Eco-Dynamics+ AWD 06/18 - /	85 - 136 kW	22-265289 22-267948 19-265292
B 6	1.6 CRDi Eco-Dynamics+, 1.6 CRDi Eco-Dynamics+ AWD, 2.0 CRDi Eco-Dynamics+ AWD 06/18 - /	85 - 136 kW	35-264699 35-264705 24-263566

KIA STONIC (YB)			
B 4	1.0 T-GDi Eco-Dynamics+ 07/20 - /	74 - 88 kW	22-323538 22-327147 19-323541
B 4	1.0 T-GDi Eco-Dynamics+ 07/20 - /	74 - 88 kW	22-331212 22-331229 19-323541

LAND ROVER			
LAND ROVER DISCOVERY SPORT (L550)			
B 4	1.5 P300e Hybrid 4x4, 2.0 P200 MHEV 4x4, 2.0 P200 FLEX MHEV 4x4, 2.0 P250 MHEV 4x4, 2.0 P290 MHEV 4x4, 2.0 D150 MHEV 4x4, 2.0 D165 MHEV, 2.0 D165 MHEV 4x4, 2.0 D180 MHEV 4x4, 2.0 D200 MHEV 4x4, 2.0 D240 MHEV 4x4 05/19 - /	110 - 227 kW	22-295651 22-295668 19-295671
B 6	1.5 P300e Hybrid 4x4, 2.0 P200 MHEV 4x4, 2.0 P200 FLEX MHEV 4x4, 2.0 P250 MHEV 4x4, 2.0 P290 MHEV 4x4, 2.0 D150 MHEV 4x4, 2.0 D165 MHEV, 2.0 D165 MHEV 4x4, 2.0 D180 MHEV 4x4, 2.0 D200 MHEV 4x4, 2.0 D240 MHEV 4x4 05/19 - /	110 - 227 kW	35-293057 35-293071 24-293068

LAND ROVER RANGE ROVER IV (L405)			
B 4 AMC	3.0 SDV6 Hybrid 4x4 10/13 - /	225 - 250 kW	40-268446 26-256474



LAND ROVER

LAND ROVER RANGE ROVER SPORT II (L494)

B 4	3.0 SDV6 Hybrid 4x4 10/13 – 12/17	225 – 250 kW		24-282185	without electronic suspension control; for coil-spring suspension vehicles
B 4 AMC	3.0 SDV6 Hybrid 4x4 06/15 – 12/17	225 kW		24-282185 40-268446	without electronic suspension control; for pneumatic suspension vehicles
B 4 AMC	3.0 SDV6 Hybrid 4x4 06/15 – 12/17	225 kW		26-280974 40-268446	with electronic suspension control; for pneumatic suspension vehicles
B 4 AMC	3.0 SDV6 Hybrid 4x4 10/13 – /	250 kW		40-268446 24-282185	without electronic suspension control; for pneumatic suspension vehicles
B 4 AMC	3.0 SDV6 Hybrid 4x4 10/13 – /	250 kW		40-268446 26-280974	with electronic suspension control; for pneumatic suspension vehicles

LAND ROVER DEFENDER Station Wagon (L663)

B 6	P400e Hybrid 4x4, P400 I6 MHEV 4x4, P300 MHEV 4x4, D200 MHEV 4x4, D250 MHEV 4x4, D300 MHEV 4x4 09/19 – /	147 – 297 kW	29-321131	24-321143	with standard chassis; for coil-spring suspension vehicles
-----	---	--------------	-----------	-----------	--

LAND ROVER DEFENDER Van (L663)

B 6	3.0 P400 I6 MHEV 4x4, 3.0 D250 MHEV 4x4, 3.0 D300 MHEV 4x4, 2.0 P400e Hybrid 4x4 02/20 – /	147 – 297 kW	29-321131	24-321143	with standard chassis; for coil-spring suspension vehicles
-----	---	--------------	-----------	-----------	--

MAN

MAN TGE Van

B 4	eTGE 07/18 – /	100 kW	22-282262		for OE number: 65.43701-0002; for OE number: 65.43701-0013; for OE number: 65.43701-0022; with standard chassis FA: Thread Size: M14; Piston conrod diameter [mm] 25mm
-----	-------------------	--------	-----------	--	---

MAZDA

MAZDA 2 (DL, DJ)

B 4	1.5 SKYACTIV-G M Hybrid 08/19 – /	55 – 66 kW	22-329035 22-329042	19-261393	with standard chassis FA: 22-329042; 22-329035
-----	--------------------------------------	------------	------------------------	-----------	---

MAZDA 2 Hatchback (KB)

B 4	1.5 Hybrid 03/22 – /	85 kW	22-329592 22-329608	19-329581	with standard chassis FA: 22-329608; 22-329592
-----	-------------------------	-------	------------------------	-----------	---

MAZDA 3 Saloon (BM_, BN_)

B 4	2.0 Hybrid 10/14 – 05/19	73 kW	22-240200 22-240217	19-240220	with standard chassis FA: 22-240217; 22-240200
B 4	2.0 Hybrid 10/14 – 05/19	73 kW	22-240200 22-240217	19-240220	with standard chassis; Vehicle Type: i-STOP; Vehicle Type: i-ELOOP FA: 22-240217; 22-240200
B 8	2.0 Hybrid 10/14 – 05/19	73 kW	35-240167 35-240174	24-240185	with sports suspension FA: 35-240174; 35-240167
B14	2.0 Hybrid 10/14 – 05/19	73 kW		47-242302	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1135 kg RA: Axle load [kg] to 945 kg

MAZDA 3 Hatchback (BP)

B 4	2.0 SKYACTIV-G M Hybrid, SKYACTIV-X M Hybrid 11/18 – /	90 – 137 kW	22-326942 22-326959	19-325958	FA: 22-326959; 22-326942
B 4	SKYACTIV-X M Hybrid AWD 06/19 – /	132 – 137 kW	22-326942 22-326959		FA: 22-326959; 22-326942

MAZDA 3 Saloon (BP_)

B 4	2.0 SKYACTIV-G M Hybrid, 2.0 SKYACTIV-X M Hybrid 11/18 – /	90 – 137 kW	22-326942 22-326959	19-325958	FA: 22-326959; 22-326942
-----	---	-------------	------------------------	-----------	--------------------------

MAZDA CX-30 (DM)

B 4	SKYACTIV-G M Hybrid, SKYACTIV-X M Hybrid, e-SKYACTIV-X M Hybrid 07/19 – /	90 – 137 kW	22-326966 22-326973	19-325965	with standard chassis FA: 22-326973; 22-326966 RA: Front Wheel Drive
-----	--	-------------	------------------------	-----------	--

MAZDA			
MAZDA CX-30 (DM)			
B 4	SKYACTIV-G M Hybrid AWD, SKYACTIV-X M Hybrid AWD, e-SKYACTIV-X M Hybrid AWD 07/19 - / 90 - 137 kW	22-326966 22-326973	with standard chassis FA: 22-326973; 22-326966

MAZDA MX-30 (DR)			
B 4	e-SKYACTIV 05/20 - / 105 - 107 kW	22-327062 22-327079	19-326924 with standard chassis FA: 22-327079; 22-327062

MAZDA TRIBUTE			
B 4	2.3 Hybrid, 2.3 Hybrid 4WD, 2.5 Hybrid, 2.5 Hybrid AWD 09/07 - 12/10 99 - 132 kW		19-165998 with standard chassis

MERCEDES-BENZ

MERCEDES-BENZ A-CLASS (W177)			
B 4	A 250 e 08/19 - / 160 kW	22-306692 22-306708	19-306308 with standard chassis; with off-road suspension; Vehicle Type: Avantgarde FA: 22-306708; 22-306692 RA: Rigid Axle; for PR number: U54
B 4	A 250 e 08/19 - / 160 kW	22-306692 22-306708	19-302775 with standard chassis; with off-road suspension; Vehicle Type: Avantgarde FA: 22-306708; 22-306692 RA: Multilink Axle; for PR number: U55
ES	A 250 e 08/19 - / 160 kW		47-313798 Rigid Axle; without electronic suspension control; Threaded Suspension (height adjustable); Conditions see certificates; Lowering ca. [mm]: 30-50 mm

MERCEDES-BENZ A-CLASS Saloon (V177)			
ES	A 250 e 08/19 - / 160 kW		47-313798 Rigid Axle; without electronic suspension control; Threaded Suspension (height adjustable); Conditions see certificates; Lowering ca. [mm]: 25-35 mm FA: Axle load [kg] to 1165 kg RA: Axle load [kg] to 1110 kg

MERCEDES-BENZ B-CLASS Sports Tourer (W247)			
B 4	B 250 e 06/20 - / 160 kW	22-306692 22-306708	19-302775 with standard chassis; Vehicle Type: Avantgarde FA: 22-306708; 22-306692 RA: Multilink Axle; for PR number: U55
B 4	B 250 e 06/20 - / 160 kW	22-306692 22-306708	19-306308 with standard chassis; with off-road suspension; Vehicle Type: Avantgarde FA: 22-306708; 22-306692 RA: Rigid Axle; for PR number: U54
B 4	B 250 e 06/20 - / 160 kW	22-306715 22-306722	19-306322 For vehicles with comfort suspension FA: 22-306722; 22-306715 RA: Rigid Axle; for PR number: U54
B 4	B 250 e 06/20 - / 160 kW	22-306715 22-306722	19-306315 For vehicles with comfort suspension FA: 22-306722; 22-306715 RA: Multilink Axle
B 4	B 250 e 06/20 - / 160 kW	22-306715 22-306722	19-306339 with off-road suspension; for vehicles with increased ground clearance FA: 22-306722; 22-306715 RA: Multilink Axle; for PR number: U55

MERCEDES-BENZ C-CLASS (W205)			
B 1	C 200 EQ Boost, C 200 EQ Boost 4-matic, C 300 e, C 300 e 4-matic, C 300 EQ Boost, C 300 EQ Boost 4-matic, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 - 08/18 135 - 235 kW	12-307197	with standard chassis; without Airmatic DC
B 3	C 200 EQ Boost 04/18 - / 135 kW	37-289652	36-291465 with standard chassis; Manual Transmission FA: for OE number: A 205 321 14 04; for OE number: A 205 321 15 04; for OE number: A 205 321 16 04 RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04
B 3	C 200 EQ Boost 04/18 - / 135 kW	37-289591	36-291557 For vehicles with comfort suspension FA: Fully Automatic; for OE number: A 205 321 03 04; for OE number: A 205 321 04 04; for OE number: A 205 321 05 04 RA: for OE number: A 205 324 02 04; for OE number: 205 324 01 04; for OE number: A 205 324 01 04; for OE number: 205 324 02 04
B 3	C 200 EQ Boost 04/18 - / 135 kW	37-289591	36-291564 For vehicles with comfort suspension; with sunroof FA: for OE number: A 205 321 03 04; for OE number: A 205 321 04 04; for OE number: A 205 321 05 04 RA: for OE number: A 205 324 03 04; for OE number: A 205 324 04 04; for OE number: 205 324 04 04; for OE number: 205 324 03 04
B 3	C 200 EQ Boost 04/18 - / 135 kW	37-290078	36-291502 with standard chassis; Fully Automatic FA: for OE number: A 205 321 58 04; for OE number: A 205 321 59 04 RA: for OE number: 205 324 25 04; for OE number: A 205 324 25 04; for OE number: 205 324 24 04; for OE number: A 205 324 24 04
B 3	C 200 EQ Boost 04/18 - / 135 kW	37-289652	36-291465 with sports suspension; with AMG Sports Package; with towbar FA: for OE number: A 205 321 14 04; for OE number: A 205 321 15 04; for OE number: A 205 321 16 04 RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04



MERCEDES-BENZ				
MERCEDES-BENZ C-CLASS (W205)				
B 3	C 200 EQ Boost 4-matic 04/18 – / 135 kW	37-289768	36-291465	with sports suspension; with AMG Sports Package FA: for OE number: A 205 321 37 04; for OE number: A 205 321 38 04; for OE number: A 205 321 39 04 RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04
B 3	C 300 EQ Boost 05/19 – / 190 kW	37-288914	36-291557	with standard chassis FA: for OE number: A 205 321 02 04; for OE number: A 205 321 01 04 RA: for OE number: A 205 324 02 04; for OE number: 205 324 01 04; for OE number: A 205 324 01 04; for OE number: 205 324 02 04
B 3	C 300 EQ Boost 05/19 – / 190 kW	37-289652	36-291465	with sports suspension FA: for OE number: A 205 321 14 04; for OE number: A 205 321 15 04; for OE number: A 205 321 16 04 RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04
B 3	C 300 EQ Boost 4-matic 05/19 – / 190 kW	37-289690	36-291564	For vehicles with comfort suspension FA: for OE number: A 205 321 25 04; for OE number: A 205 321 26 04; for OE number: A 205 321 27 04 RA: for OE number: A 205 324 03 04; for OE number: A 205 324 04 04; for OE number: 205 324 04 04; for OE number: 205 324 03 04
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW	24-251310	24-251327	with standard chassis
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW	24-251341	24-278249	with sports suspension
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW	24-251433	24-251426	Vehicle Type: Avantgarde; with standard chassis
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW	24-251440	24-251419	with off-road suspension
B 4 DMC	C 200 EQ Boost 4-matic, C 300 e 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 235 kW	24-251556 24-251563	24-278232	with standard chassis FA: 24-251563; 24-251556
B 4 DMC	C 200 EQ Boost 4-matic, C 300 e 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 235 kW	24-251631 24-251648	24-251655	with sports suspension FA: 24-251648; 24-251631
B 4 DMC	C 200 EQ Boost 4-matic, C 300 e 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 235 kW		24-251419	with off-road suspension
B 4 DMC	C 200 EQ Boost 4-matic, C 300 e 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 235 kW	24-257237 24-252027	24-251426	Vehicle Type: Avantgarde; with standard chassis FA: 24-252027; 24-257237
B 4 DMC	C 300 BlueTEC Hybrid / h 05/14 – 05/18 150 kW		24-281621	For vehicles with comfort suspension
B 4 DTC	C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 150 – 235 kW	24-277945 24-277952	24-277969 24-277976	with lowered chassis; Rear Wheel Drive FA: 24-277952; 24-277945 RA: 24-277976; 24-277969
B 4 AMC	C 200 EQ Boost, C 300 EQ Boost, C 300 BlueTEC Hybrid / h 05/14 – 05/18 135 – 190 kW	44-278304 44-278311		for pneumatic suspension vehicles; with electronic suspension control FA: 44-278311; for OE number: A 205 320 83 00; 44-278304; for OE number: A 205 320 84 00
B 4 AMC	C 200 EQ Boost, C 300 e 04/18 – / 135 – 235 kW	44-251673 44-251680		for pneumatic suspension vehicles FA: 44-251680; for OE number: A 205 320 47 68; 44-251673; for OE number: A 205 320 48 68
B 4 AMC	C 200 EQ Boost 4-matic 04/18 – / 135 kW	44-281014 44-281007		for pneumatic suspension vehicles; with electronic suspension control; All-wheel Drive FA: 44-281007; for OE number: A 205 320 85 00; 44-281014; for OE number: A 205 320 86 00
B 4 AMC	C 200 EQ Boost 4-matic 04/18 – / 135 kW	44-251598 44-251604		for pneumatic suspension vehicles; with electronic suspension control FA: 44-251604; for OE number: A 205 320 49 68; 44-251598; for OE number: A 205 320 50 68
B 4 AMC	C 300 e, C 350 e, C 300 de 02/15 – 08/18 205 – 235 kW	44-278304 44-278311		for pneumatic suspension vehicles; with electronic suspension control FA: 44-278311; for OE number: A 205 320 83 00; 44-278304; for OE number: A 205 320 84 00
B 4 AMC	C 300 e 4-matic, C 300 EQ Boost 4-matic 05/19 – / 190 – 235 kW	44-281014 44-281007		for pneumatic suspension vehicles; with electronic suspension control; All-wheel Drive FA: 44-281007; for OE number: A 205 320 85 00; 44-281014; for OE number: A 205 320 86 00
B 4 AMC	C 300 e 4-matic, C 300 EQ Boost 4-matic 05/19 – / 190 – 235 kW	44-251598 44-251604	26-251691 26-251707	for pneumatic suspension vehicles; with electronic suspension control; All-wheel Drive FA: 44-251604; for OE number: A 205 320 49 68; 44-251598; for OE number: A 205 320 50 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30

MERCEDES-BENZ				
MERCEDES-BENZ C-CLASS (W205)				
B 4 AMC	C 300 EQ Boost, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 05/18 150 – 225 kW	44-251673 $\frac{1}{\text{h}}$ 44-251680 $\frac{1}{\text{h}}$	 	26-251691 $\frac{1}{\text{h}}$ 26-251707 $\frac{1}{\text{h}}$ for pneumatic suspension vehicles; with electronic suspension control FA: 44-251680; for OE number: A 205 320 47 68; 44-251673; for OE number: A 205 320 48 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 4 AMC	C 350 e 02/15 – 08/18 205 kW	44-251673 $\frac{1}{\text{h}}$ 44-251680 $\frac{1}{\text{h}}$	 	26-281292 $\frac{1}{\text{h}}$ 26-281285 $\frac{1}{\text{h}}$ for pneumatic suspension vehicles; with electronic suspension control FA: 44-251680; for OE number: A 205 320 47 68; 44-251673; for OE number: A 205 320 48 68 RA: 26-281285; for OE number: A 205 320 85 30; 26-281292; for OE number: A 205 320 86 30
B 6	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW	24-241304 $\frac{1}{\text{h}}$		24-241311 $\frac{1}{\text{h}}$ without electronic suspension control
B 6	C 200 EQ Boost 4-matic, C 300 e 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 235 kW	24-252034 $\frac{1}{\text{h}}$ 24-252041 $\frac{1}{\text{h}}$	 	24-241311 $\frac{1}{\text{h}}$ FA: 24-252041; 24-252034
B 8	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW	24-241328 $\frac{1}{\text{h}}$		24-241335 $\frac{1}{\text{h}}$ FA: with sports suspension; for PR number: 486
B 8	C 200 EQ Boost 4-matic, C 300 e 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 235 kW	24-252058 $\frac{1}{\text{h}}$ 24-252065 $\frac{1}{\text{h}}$	 	24-241335 $\frac{1}{\text{h}}$ FA: 24-252065; 24-252058
B12 PK	C 200 EQ Boost 4-matic 04/18 – / 135 kW			46-337160 Conditions see certificates; without electronic suspension control; with General Certification (ABE); Lowering ca. [mm]: 35 mm FA: Axle load [kg] to 1065 kg RA: Axle load [kg] to 1180 kg
B14	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW			47-241343 Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 40-45 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 05/14 – 08/18 135 – 235 kW			48-241373 without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Payload to: 1125 kg RA: Lowering ca. [mm]: 45-50 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost 4-matic, C 300 e 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 235 kW			48-252096 without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 45-50 mm; Axle load [kg] to 1325 kg
MERCEDES-BENZ C-CLASS T-Model (S205)				
B 1	C 200 EQ Boost, C 200 EQ Boost 4-matic, C 300 e, C 300 EQ Boost, C 300 EQ Boost 4-matic, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	12-307197		with standard chassis; without Airmatic DC
B 3	C 200 EQ Boost 04/18 – / 135 kW	37-290078		36-291557 with standard chassis; Manual Transmission; with towbar FA: for OE number: A 205 321 58 04; for OE number: A 205 321 59 04 RA: for OE number: A 205 324 02 04; for OE number: 205 324 01 04; for OE number: A 205 324 01 04; for OE number: 205 324 02 04
B 3	C 200 EQ Boost 04/18 – / 135 kW	37-289645		36-291465 with sports suspension; with AMG Sports Package; Manual Transmission FA: for OE number: A 205 321 13 04; Red RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04
B 3	C 200 EQ Boost 04/18 – / 135 kW	37-290078		36-291557 with standard chassis; Fully Automatic FA: for OE number: A 205 321 58 04; for OE number: A 205 321 59 04 RA: for OE number: A 205 324 02 04; for OE number: 205 324 01 04; for OE number: A 205 324 01 04; for OE number: 205 324 02 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 190 kW	37-289706		For vehicles with comfort suspension FA: for OE number: A 205 321 28 04; Grey; Yellow; Green
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 190 kW	37-289690		For vehicles with comfort suspension; All-wheel Drive FA: for OE number: A 205 321 25 04; for OE number: A 205 321 26 04; for OE number: A 205 321 27 04
B 3	C 300 EQ Boost 05/19 – / 190 kW	37-289591		36-291564 For vehicles with comfort suspension FA: for OE number: A 205 321 03 04; for OE number: A 205 321 04 04; for OE number: A 205 321 05 04 RA: for OE number: A 205 324 03 04; for OE number: A 205 324 04 04; for OE number: 205 324 04 04; for OE number: 205 324 03 04
B 3	C 300 BlueTEC Hybrid / h 10/14 – 05/18 150 kW	37-289607		36-291571 For vehicles with comfort suspension FA: for OE number: A 205 321 06 04; for OE number: A 205 321 07 04 RA: for OE number: A 205 324 05 04; for OE number: A 205 324 06 04; for OE number: A 205 324 07 04; for OE number: 205 324 05 04; for OE number: 205 324 07 04; for OE number: 205 324 06 04
B 3	C 300 BlueTEC Hybrid / h 10/14 – 05/18 150 kW	37-289607		36-291571 For vehicles with comfort suspension; with towbar FA: for OE number: A 205 321 06 04; for OE number: A 205 321 07 04 RA: for OE number: A 205 324 05 04; for OE number: A 205 324 06 04; for OE number: A 205 324 07 04; for OE number: 205 324 05 04; for OE number: 205 324 07 04; for OE number: 205 324 06 04



MERCEDES-BENZ				
MERCEDES-BENZ C-CLASS T-Model (S205)				
B 3	C 300 BlueTEC Hybrid / h 10/14 – 05/18 150 kW	37-289591	36-291564	with standard chassis FA: for OE number: A 205 321 03 04; for OE number: A 205 321 04 04; for OE number: A 205 321 05 04 RA: for OE number: A 205 324 03 04; for OE number: A 205 324 04 04; for OE number: 205 324 04 04; for OE number: 205 324 03 04
B 3	C 300 BlueTEC Hybrid / h 10/14 – 05/18 150 kW	37-289591	36-291571	with standard chassis; with sunroof FA: for OE number: A 205 321 03 04; for OE number: A 205 321 04 04; for OE number: A 205 321 05 04 RA: for OE number: A 205 324 05 04; for OE number: A 205 324 06 04; for OE number: A 205 324 07 04; for OE number: 205 324 05 04; for OE number: 205 324 07 04; for OE number: 205 324 06 04
B 3	C 300 BlueTEC Hybrid / h 10/14 – 05/18 150 kW	37-289669	36-291489	with sports suspension; with AMG Sports Package; with sunroof; with towbar FA: for OE number: A 205 321 17 04; for OE number: A 205 321 18 04; for OE number: A 205 321 19 04 RA: for OE number: 205 324 13 04; for OE number: A 205 324 13 04; for OE number: 205 324 14 04; for OE number: A 205 324 14 04; for OE number: 205 324 15 04; for OE number: A 205 324 15 04
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	24-251310 $\frac{1}{h}$	24-251327 $\frac{1}{o}$	with standard chassis
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	24-251341 $\frac{1}{h}$	24-278249 $\frac{1}{o}$	with sports suspension
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	24-251433 $\frac{1}{h}$	24-251426 $\frac{1}{o}$	Vehicle Type: Avantgarde; with standard chassis
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 de 04/18 – / 135 – 235 kW	24-277945 $\frac{1}{h}$ 24-277952 $\frac{1}{h}$	24-277969 $\frac{1}{o}$ 24-277976 $\frac{1}{o}$	with lowered chassis FA: 24-277952; 24-277945 RA: 24-277976; 24-277969
B 4 DMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	24-251440 $\frac{1}{h}$	24-251419 $\frac{1}{o}$	with off-road suspension
B 4 DMC	C 300 BlueTEC Hybrid / h 10/14 – 05/18 150 kW	24-251310 $\frac{1}{h}$	24-281652 $\frac{1}{o}$	For vehicles with comfort suspension; with leveling control
B 4 DMC	C 300 BlueTEC Hybrid / h 10/14 – 05/18 150 kW	24-277945 $\frac{1}{h}$ 24-277952 $\frac{1}{h}$	24-277969 $\frac{1}{o}$ 24-277976 $\frac{1}{o}$	with lowered chassis FA: 24-277952; 24-277945 RA: 24-277976; 24-277969
B 4 AMC	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	44-278304 $\frac{1}{h}$ 44-278311 $\frac{1}{o}$		for pneumatic suspension vehicles; with electronic suspension control FA: 44-278311; for OE number: A 205 320 83 00; 44-278304; for OE number: A 205 320 84 00
B 4 AMC	C 200 EQ Boost, C 300 EQ Boost, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 225 kW	44-251673 $\frac{1}{h}$ 44-251680 $\frac{1}{h}$	26-251691 $\frac{1}{o}$ 26-251707 $\frac{1}{o}$	for pneumatic suspension vehicles; with electronic suspension control FA: 44-251680; for OE number: A 205 320 47 68; 44-251673; for OE number: A 205 320 48 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 4 AMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 190 kW	44-281014 $\frac{1}{h}$ 44-281007 $\frac{1}{o}$		for pneumatic suspension vehicles; with electronic suspension control FA: 44-281007; for OE number: A 205 320 85 00; 44-281014; for OE number: A 205 320 86 00
B 4 AMC	C 200 EQ Boost 4-matic 04/18 – / 135 kW	44-251598 $\frac{1}{h}$ 44-251604 $\frac{1}{h}$	26-251691 $\frac{1}{o}$ 26-251707 $\frac{1}{o}$	for pneumatic suspension vehicles; with electronic suspension control FA: 44-251604; for OE number: A 205 320 49 68; 44-251598; for OE number: A 205 320 50 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 4 AMC	C 300 e, C 350 e 02/15 – 05/18 205 – 235 kW	44-278304 $\frac{1}{h}$ 44-278311 $\frac{1}{o}$		for pneumatic suspension vehicles; with electronic suspension control FA: 44-278311; for OE number: A 205 320 83 00; 44-278304; for OE number: A 205 320 84 00
B 4 AMC	C 300 EQ Boost 4-matic 05/19 – / 190 kW	44-251598 $\frac{1}{h}$ 44-251604 $\frac{1}{h}$	26-251691 $\frac{1}{o}$ 26-251707 $\frac{1}{o}$	for pneumatic suspension vehicles; with electronic suspension control; All-wheel Drive FA: 44-251604; for OE number: A 205 320 49 68; 44-251598; for OE number: A 205 320 50 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 4 AMC	C 350 e 02/15 – 05/18 205 kW	44-251673 $\frac{1}{h}$ 44-251680 $\frac{1}{h}$	26-281292 $\frac{1}{o}$ 26-281285 $\frac{1}{o}$	for pneumatic suspension vehicles; with electronic suspension control FA: 44-251680; for OE number: A 205 320 47 68; 44-251673; for OE number: A 205 320 48 68 RA: 26-281285; for OE number: A 205 320 85 30; 26-281292; for OE number: A 205 320 86 30
B 6	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	24-241304 $\frac{1}{h}$	24-241311 $\frac{1}{o}$	without electronic suspension control
B 6	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 04/18 – / 135 – 190 kW	24-252034 $\frac{1}{h}$ 24-252041 $\frac{1}{h}$	24-241311 $\frac{1}{o}$	with standard chassis FA: 24-252041; 24-252034
B 8	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 – 05/18 135 – 235 kW	24-241328 $\frac{1}{h}$	24-241335 $\frac{1}{o}$	FA: with sports suspension; for PR number: 486



MERCEDES-BENZ					
MERCEDES-BENZ C-CLASS T-Model (S205)					
B 8	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 04/18 - / 135 - 190 kW	24-252058 $\frac{1}{H}$ 24-252065 $\frac{1}{H}$	 	24-241335 $\frac{1}{O}$	with sports suspension FA: 24-252065; 24-252058
B12 PK	C 200 EQ Boost 4-matic 04/18 - / 135 kW	46-337177			Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1065 kg RA: Lowering ca. [mm]: 20 mm; Axle load [kg] to 1235 kg
B14	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 - 05/18 135 - 235 kW	47-241343			without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 40-45 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost, C 300 e, C 300 EQ Boost, C 350 e, C 300 BlueTEC Hybrid / h, C 300 de 10/14 - 05/18 135 - 235 kW	48-241373			without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 40-45 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 04/18 - / 135 - 190 kW	48-252096			without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 45-50 mm; Axle load [kg] to 1325 kg
MERCEDES-BENZ C-CLASS Coupe (C205)					
B 1	C 300 EQ Boost 05/19 - / 190 kW			11-305934	Rigid Axle; without lowered chassis
B 1	C 200 EQ Boost, C 200 EQ Boost 4-matic, C 300 EQ Boost, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	12-307197			with standard chassis; without Airmatic DC
B 3	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 - 190 kW	37-289652		36-291465	with sports suspension; with AMG Sports Package FA: for OE number: A 205 321 14 04; for OE number: A 205 321 15 04; for OE number: A 205 321 16 04 RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	37-289775			with sports suspension; with electronic suspension control FA: for OE number: A 205 321 40 04; for OE number: A 205 321 41 04; for OE number: A 205 321 42 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	37-289768			with sports suspension; with electronic suspension control FA: for OE number: A 205 321 37 04; for OE number: A 205 321 38 04; for OE number: A 205 321 39 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	37-289706			with standard chassis; Trim Level Avantgarde FA: for OE number: A 205 321 28 04; Grey; Yellow; Green
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	37-289690			with standard chassis; Trim Level Avantgarde FA: for OE number: A 205 321 25 04; for OE number: A 205 321 26 04; for OE number: A 205 321 27 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW			36-291557	Trim Level Avantgarde RA: for OE number: A 205 324 02 04; for OE number: 205 324 01 04; for OE number: A 205 324 01 04; for OE number: 205 324 02 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW			36-291564	Trim Level Avantgarde RA: for OE number: A 205 324 03 04; for OE number: A 205 324 04 04; for OE number: 205 324 04 04; for OE number: 205 324 03 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW			36-291458	with sports suspension; with electronic suspension control; Trim Level Avantgarde RA: for OE number: 205 324 09 04; for OE number: A 205 324 09 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW			36-291465	with sports suspension; with electronic suspension control; Trim Level Avantgarde RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW			36-291472	with sports suspension; with electronic suspension control; Trim Level Avantgarde RA: for OE number: 205 324 12 04; for OE number: A 205 324 12 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW			36-291489	with sports suspension; with electronic suspension control; Trim Level Avantgarde RA: for OE number: 205 324 13 04; for OE number: A 205 324 13 04; for OE number: 205 324 14 04; for OE number: A 205 324 14 04; for OE number: 205 324 15 04; for OE number: A 205 324 15 04
B 3	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW			36-291502	Trim Level Avantgarde RA: for OE number: 205 324 25 04; for OE number: A 205 324 25 04; for OE number: 205 324 24 04; for OE number: A 205 324 24 04
B 4 DMC	C 200 EQ Boost 05/18 - / 135 kW	24-251310 $\frac{1}{H}$		24-251327 $\frac{1}{O}$	with standard chassis
B 4 DMC	C 200 EQ Boost 05/18 - / 135 kW	24-251341 $\frac{1}{H}$		24-278249 $\frac{1}{O}$	with sports suspension
B 4 DMC	C 200 EQ Boost 05/18 - / 135 kW	24-251440 $\frac{1}{H}$		24-251419 $\frac{1}{O}$	with off-road suspension
B 4 DMC	C 200 EQ Boost 05/18 - / 135 kW	24-251341 $\frac{1}{H}$		24-278027 $\frac{1}{O}$	Vehicle Type: Avantgarde; with standard chassis
B 4 DMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	24-278041 $\frac{1}{H}$ 24-278058 $\frac{1}{H}$	 	24-278065 $\frac{1}{O}$	Vehicle Type: Avantgarde FA: 24-278058; 24-278041
B 4 AMC	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 - 190 kW	44-278304 $\frac{1}{O}$ 44-278311 $\frac{1}{O}$	 		for pneumatic suspension vehicles; with electronic suspension control FA: 44-278311; for OE number: A 205 320 83 00; 44-278304; for OE number: A 205 320 84 00



MERCEDES-BENZ				
MERCEDES-BENZ C-CLASS Coupe (C205)				
B 4 AMC	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 – 190 kW	44-251673 $\frac{1}{\text{H}}$ 44-251680 $\frac{1}{\text{H}}$	 	26-251691 $\frac{1}{\text{O}}$ 26-251707 $\frac{1}{\text{O}}$ for pneumatic suspension vehicles; with electronic suspension control FA: 44-251680; for OE number: A 205 320 47 68; 44-251673; for OE number: A 205 320 48 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 4 AMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	44-281014 $\frac{1}{\text{H}}$ 44-281007 $\frac{1}{\text{O}}$	 	for pneumatic suspension vehicles; with electronic suspension control FA: 44-281007; for OE number: A 205 320 85 00; 44-281014; for OE number: A 205 320 86 00
B 4 AMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	44-251598 $\frac{1}{\text{H}}$ 44-251604 $\frac{1}{\text{H}}$	 	26-251691 $\frac{1}{\text{O}}$ 26-251707 $\frac{1}{\text{O}}$ for pneumatic suspension vehicles; with electronic suspension control FA: 44-251604; for OE number: A 205 320 49 68; 44-251598; for OE number: A 205 320 50 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 6	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 – 190 kW	24-241304 $\frac{1}{\text{H}}$	24-241311 $\frac{1}{\text{O}}$	without electronic suspension control
B 8	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 – 190 kW	24-241328 $\frac{1}{\text{H}}$	24-241335 $\frac{1}{\text{O}}$	FA: with sports suspension; for PR number: 486
B12 PK	C 200 EQ Boost 4-matic 05/18 - / 135 kW	46-337160		Conditions see certificates; without electronic suspension control; with General Certification (ABE); Lowering ca. [mm]: 35 mm FA: Axle load [kg] to 1065 kg RA: Axle load [kg] to 1180 kg
B14	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 – 190 kW	47-241343		without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 40-45 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 – 190 kW	48-241373		without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Payload to: 1125 kg RA: Lowering ca. [mm]: 40-45 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	48-252096		without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 45-50 mm; Axle load [kg] to 1325 kg
MERCEDES-BENZ C-CLASS Convertible (A205)				
B 1	C 200 EQ Boost, C 200 EQ Boost 4-matic, C 300 EQ Boost, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	12-307197		with standard chassis; without Airmatic DC
B 3	C 200 EQ Boost 05/18 - / 135 kW	37-289652	36-291557	with standard chassis FA: for OE number: A 205 321 14 04; for OE number: A 205 321 15 04; for OE number: A 205 321 16 04 RA: for OE number: A 205 324 02 04; for OE number: 205 324 01 04; for OE number: A 205 324 01 04; for OE number: 205 324 02 04
B 3	C 200 EQ Boost 05/18 - / 135 kW	37-289652	36-291465	with sports suspension; with AMG Sports Package FA: for OE number: A 205 321 14 04; for OE number: A 205 321 15 04; for OE number: A 205 321 16 04 RA: for OE number: 205 324 10 04; for OE number: A 205 324 10 04; for OE number: 205 324 11 04; for OE number: A 205 324 11 04
B 4 DMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	24-257237 $\frac{1}{\text{H}}$ 24-252027 $\frac{1}{\text{H}}$	 	24-281645 $\frac{1}{\text{O}}$ for coil-spring suspension vehicles; with standard chassis; Vehicle Type: Avantgarde; for left-hand drive vehicles FA: 24-252027; 24-257237
B 4 DMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	24-281638 $\frac{1}{\text{H}}$		for coil-spring suspension vehicles; with standard chassis; Vehicle Type: Avantgarde; for right-hand drive vehicles
B 4 DMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	24-251631 $\frac{1}{\text{H}}$ 24-251648 $\frac{1}{\text{H}}$	 	24-281669 $\frac{1}{\text{O}}$ for coil-spring suspension vehicles; with sports suspension; for left-hand drive vehicles FA: 24-251648; 24-251631
B 4 DMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	24-251631 $\frac{1}{\text{H}}$ 24-251648 $\frac{1}{\text{H}}$	 	24-281676 $\frac{1}{\text{O}}$ for coil-spring suspension vehicles; with sports suspension; for right-hand drive vehicles FA: 24-251648; 24-251631
B 4 DMC	C 300 EQ Boost 05/19 - / 190 kW	24-251310 $\frac{1}{\text{H}}$	24-251327 $\frac{1}{\text{O}}$	with standard chassis
B 4 DMC	C 300 EQ Boost 05/19 - / 190 kW	24-251341 $\frac{1}{\text{H}}$	24-278249 $\frac{1}{\text{O}}$	with sports suspension
B 4 DMC	C 300 EQ Boost 05/19 - / 190 kW	24-281638 $\frac{1}{\text{H}}$		Vehicle Type: Avantgarde; with standard chassis
B 4 AMC	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 – 190 kW	44-278304 $\frac{1}{\text{O}}$ 44-278311 $\frac{1}{\text{O}}$	 	for pneumatic suspension vehicles; with electronic suspension control FA: 44-278311; for OE number: A 205 320 83 00; 44-278304; for OE number: A 205 320 84 00
B 4 AMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 – 190 kW	44-281014 $\frac{1}{\text{H}}$ 44-281007 $\frac{1}{\text{O}}$	 	for pneumatic suspension vehicles; with electronic suspension control FA: 44-281007; for OE number: A 205 320 85 00; 44-281014; for OE number: A 205 320 86 00

MERCEDES-BENZ				
MERCEDES-BENZ C-CLASS Convertible (A205)				
B 4 AMC	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	44-251598 $\frac{1}{H}$ 44-251604 $\frac{1}{H}$	 	26-251691 $\frac{1}{O}$ 26-251707 $\frac{1}{O}$ for pneumatic suspension vehicles; with electronic suspension control FA: 44-251604; for OE number: A 205 320 49 68; 44-251598; for OE number: A 205 320 50 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 6	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 - 190 kW	24-241304 $\frac{1}{H}$		24-241311 $\frac{1}{O}$ without electronic suspension control
B 6	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	24-252034 $\frac{1}{H}$ 24-252041 $\frac{1}{H}$	 	24-241311 $\frac{1}{O}$ with standard chassis FA: 24-252041; 24-252034
B 8	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 - 190 kW	24-241328 $\frac{1}{H}$		24-241335 $\frac{1}{O}$ with sports suspension FA: for PR number: 486
B 8	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	24-252058 $\frac{1}{H}$ 24-252065 $\frac{1}{H}$	 	24-241335 $\frac{1}{O}$ with sports suspension FA: 24-252065; 24-252058
B12 PK	C 200 EQ Boost 05/18 - / 135 kW	46-334770		Conditions see certificates; without leveling control; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1065 kg RA: Axle load [kg] to 1250 kg
B12 PK	C 200 EQ Boost 4-matic 05/18 - / 135 kW	46-337191		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1190 kg RA: Axle load [kg] to 1250 kg
B14	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 - 190 kW	47-241343		Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 15-40 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost, C 300 EQ Boost 05/18 - / 135 - 190 kW	48-241373		without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Payload to: 1125 kg RA: Lowering ca. [mm]: 15-40 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 200 EQ Boost 4-matic, C 300 EQ Boost 4-matic 05/18 - / 135 - 190 kW	48-252096		without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 45-50 mm; Axle load [kg] to 1325 kg
MERCEDES-BENZ C-CLASS (W206)				
B 6	C 180, C 200, C 300, C 300 e, C 200 d, C 220 d, C 300 d 03/21 - / 120 - 230 kW	24-331388 $\frac{1}{H}$		24-331395 $\frac{1}{O}$ FA: with sports suspension; For vehicles with comfort suspension; with standard chassis RA: without leveling control
ES	C 180, C 200, C 300, C 300 e, C 200 d, C 220 d, C 300 d 03/21 - / 120 - 230 kW	47-319332		with standard chassis; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1145 kg RA: Axle load [kg] to 1340 kg
ES	C 200 4-matic, C 300 4-matic, C 300 e 4-matic, C 400 e 4-matic, C 220 d 4-matic, C 300 d 4-matic 03/21 - / 147 - 280 kW	47-331013		Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1145 kg RA: Axle load [kg] to 1340 kg
MERCEDES-BENZ C-CLASS T-MODEL (S206)				
ES	C 180, C 200, C 300, C 200 d, C 220 d, C 300 d 03/21 - / 120 - 195 kW	47-319332		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1145 kg RA: Axle load [kg] to 1340 kg
ES	C 200 4-matic, C 300 4-matic, C 220 d 4-matic 03/21 - / 147 - 190 kW	47-331013		FA: Axle load [kg] to 1145 kg; Lowering ca. [mm]: 30-40 mm RA: Axle load [kg] to 1340 kg; Lowering ca. [mm]: 30-50 mm
ES	C 300 e 12/21 - / 230 kW	47-319332		without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 30-50 mm
MERCEDES-BENZ CLA (C118)				
B 4	CLA 250 e 06/20 - / 160 kW	22-328007 22-328014	 	19-306346 $\frac{1}{O}$ For vehicles with comfort suspension FA: 22-328014; 22-328007 RA: Rigid Axle
B 6	CLA 250 e 06/20 - / 160 kW	22-327970 22-327987	 	24-327992 $\frac{1}{O}$ RA: Rigid Axle
ES	CLA 250 e 06/20 - / 160 kW	47-327108		Rigid Axle; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1145 kg RA: Axle load [kg] to 1195 kg
MERCEDES-BENZ CLA Shooting Brake (X118)				
B 4	CLA 250 e 06/20 - / 160 kW	22-328007 22-328014	 	19-306346 $\frac{1}{O}$ For vehicles with comfort suspension FA: 22-328014; 22-328007 RA: Rigid Axle





MERCEDES-BENZ

MERCEDES-BENZ CLS (C257)

B 1	CLS 260 EQ Boost, CLS 350 EQ Boost, CLS 350 EQ Boost 4-matic, CLS 450 EQ Boost, CLS 450 EQ Boost 4-matic, AMG CLS 53 EQ Boost 4-matic+, CLS 300 d 4-matic 12/17 - / 135 - 320 kW	12-307197		with standard chassis
B 4	CLS 260 EQ Boost, CLS 350 EQ Boost, CLS 450 EQ Boost 08/18 - / 135 - 270 kW	24-295390 $\frac{1}{H}$	24-265775 $\frac{1}{O}$	with standard chassis; Rear Wheel Drive
B 4 DMC	CLS 350 EQ Boost 4-matic, CLS 450 EQ Boost 4-matic, AMG CLS 53 EQ Boost 4-matic+ 12/17 - / 220 - 320 kW	24-265768 $\frac{1}{H}$ 24-294676 $\frac{1}{H}$	24-265775 $\frac{1}{O}$	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension; All-wheel Drive FA: 24-294676; 24-265768
B 4 AMC	CLS 260 EQ Boost, CLS 350 EQ Boost, CLS 450 EQ Boost 08/18 - / 135 - 270 kW	44-286651 $\frac{1}{H}$ 44-286668 $\frac{1}{H}$		with standard chassis FA: 44-286668; 44-286651
B 4 AMC	CLS 350 EQ Boost 4-matic, CLS 450 EQ Boost 4-matic 12/17 - / 220 - 270 kW	44-286675 $\frac{1}{H}$ 44-286682 $\frac{1}{H}$		for pneumatic suspension vehicles FA: 44-286682; 44-286675
B 6	CLS 260 EQ Boost, CLS 350 EQ Boost, CLS 450 EQ Boost 08/18 - / 135 - 270 kW	24-257978 $\frac{1}{H}$	24-257985 $\frac{1}{O}$	for vehicles without pneumatic suspension; without electronic suspension control; without off-road suspension; with standard chassis
B 6	CLS 350 EQ Boost 4-matic, CLS 450 EQ Boost 4-matic 12/17 - / 220 - 270 kW	24-265614 $\frac{1}{H}$ 24-265621 $\frac{1}{H}$	24-257985 $\frac{1}{O}$	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-265621; 24-265614
B 8	CLS 260 EQ Boost, CLS 350 EQ Boost, CLS 450 EQ Boost 08/18 - / 135 - 270 kW	24-257992 $\frac{1}{H}$	24-258005 $\frac{1}{O}$	with sports suspension; for vehicles without pneumatic suspension; without electronic suspension control
B 8	CLS 350 EQ Boost 4-matic, CLS 450 EQ Boost 4-matic 12/17 - / 220 - 270 kW	24-265713 $\frac{1}{H}$ 24-265720 $\frac{1}{H}$	24-258005 $\frac{1}{O}$	with sports suspension; for left-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-265713
B 8	CLS 350 EQ Boost 4-matic 08/18 - / 220 kW	24-273633 $\frac{1}{H}$ 24-265713 $\frac{1}{H}$ 24-273640 $\frac{1}{H}$ 24-265720 $\frac{1}{H}$	24-273039 $\frac{1}{O}$	with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-273633; 24-265713
B 8	CLS 450 EQ Boost 4-matic 12/17 - / 270 kW	24-265713 $\frac{1}{H}$ 24-273633 $\frac{1}{H}$ 24-273640 $\frac{1}{H}$ 24-265720 $\frac{1}{H}$	24-273039 $\frac{1}{O}$	with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-273633; 24-265713
B14	CLS 260 EQ Boost, CLS 350 EQ Boost, CLS 450 EQ Boost 08/18 - / 135 - 270 kW	47-258037		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1325 kg
B16 PSS10	CLS 260 EQ Boost, CLS 350 EQ Boost, CLS 450 EQ Boost 08/18 - / 135 - 270 kW	48-258067		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1325 kg
B16 PSS10	CLS 350 EQ Boost 4-matic, CLS 450 EQ Boost 4-matic 12/17 - / 220 - 270 kW	48-265737		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1280 kg; Lowering ca. [mm]: 20-45 mm RA: Axle load [kg] to 1340 kg; Lowering ca. [mm]: 30-45 mm

MERCEDES-BENZ E-CLASS (W212)

B 1	E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 kW	12-305612	12-224623	FA: for vehicles without pneumatic suspension RA: without ball bearing
B 3	E 400 Hybrid, E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 - 225 kW		36-277193	RA: for OE number: A 212 324 13 04
B 3	E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 kW	37-279998		For vehicles with comfort suspension; Fully Automatic
B 3	E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 kW		36-277179	For vehicles with comfort suspension; Fully Automatic
B 3	E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 kW		36-277162	with sports suspension; Fully Automatic
B 3	E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 kW	37-280017		with sports suspension; Fully Automatic
B 4 DMC	E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 kW	22-194091 $\frac{1}{H}$	24-194112 $\frac{1}{O}$	with standard chassis; without Airmatic DC
B 4 DMC	E 300 Hybrid / BlueTEC Hybrid 12/11 - 12/16 150 kW	22-194107 $\frac{1}{H}$	24-194129 $\frac{1}{O}$	with off-road suspension; without Airmatic DC

MERCEDES-BENZ				
MERCEDES-BENZ E-CLASS (W212)				
B 4 AMC	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW		40-303468 40-303451	 with Airmatic DC; with electronic suspension control; for pneumatic suspension vehicles RA: for OE number: 212 320 37 25; for OE number: A 212 320 37 25; for OE number: 212 320 03 25; for OE number: A 212 320 03 25; 40-303451; for OE number: A 212 320 38 25; for OE number: 212 320 38 25; 40-303468
B 6	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	22-302380	24-166874	with standard chassis; without Airmatic DC
B 8	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	22-302397	24-166898	without Airmatic DC; with AMG Sports Package; Vehicle Type: Avantgarde; with sports suspension
B16 PSS10	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	48-166560		with standard chassis; without Airmatic DC; Conditions see certificates FA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1220 kg RA: Lowering ca. [mm]: 30-55 mm; Axle load [kg] to 1260 kg
MERCEDES-BENZ E-CLASS T-Model (S212)				
B 1	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	12-305612	12-224623	FA: for vehicles without pneumatic suspension RA: without ball bearing
B 3	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	37-280000		For vehicles with comfort suspension; Fully Automatic
B 3	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	37-280024		with sports suspension; Fully Automatic
B 3 AMC	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW		40-303444 40-303437	 with standard chassis RA: for OE number: 212 320 21 25; for OE number: 212 320 39 25; for OE number: A 212 320 39 25; for OE number: A 212 320 21 25; 40-303437; for OE number: 212 320 40 25; for OE number: A 212 320 40 25; for OE number: A 212 320 20 25; for OE number: 212 320 20 25; 40-303444
B 4 DMC	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	22-194091	24-194136	with standard chassis; without Airmatic DC; with off-road suspension
B 4 AMC	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW		40-303444 40-303437	 with Airmatic DC; with electronic suspension control; for pneumatic suspension vehicles RA: for OE number: 212 320 21 25; for OE number: 212 320 39 25; for OE number: A 212 320 39 25; for OE number: A 212 320 21 25; 40-303437; for OE number: 212 320 40 25; for OE number: A 212 320 40 25; for OE number: A 212 320 20 25; for OE number: 212 320 20 25; 40-303444
B 6	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	22-302380	24-171014	without Airmatic DC; with standard chassis
B 8	E 300 Hybrid / BlueTEC Hybrid 12/11 – 12/16 150 kW	22-302397	24-171014	without Airmatic DC; Vehicle Type: Avantgarde; with sports suspension
MERCEDES-BENZ E-CLASS (W213)				
B 1	E 200 EQ Boost, E 200 EQ Boost 4-matic, E 260 EQ Boost, E 260 EQ Boost 4-matic, E 300 e, E 300 e 4-matic, E 300 EQ Boost, E 350 e, E 350 EQ Boost, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+, 2.0 E 220 d, 2.0 E 220 d 4-matic, E 300 de, E 300 de 4-matic, E 300 d 4-matic 07/16 – / 135 – 320 kW	12-307197		with standard chassis
B 4 DMC	E 200 EQ Boost, E 260 EQ Boost, E 300 EQ Boost, E 350 e, E 350 EQ Boost, 2.0 E 220 d 07/16 – / 135 – 235 kW	24-295390	24-265775	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension
B 4 DMC	E 200 EQ Boost, E 260 EQ Boost 04/19 – / 135 – 145 kW	24-295390 24-265157	24-294720	For vehicles with comfort suspension; without electronic suspension control; for vehicles without pneumatic suspension FA: for OE number: A 213 320 35 30
B 4 DMC	E 200 EQ Boost, E 260 EQ Boost, E 300 EQ Boost, E 350 e, E 350 EQ Boost, 2.0 E 220 d 07/16 – / 135 – 235 kW	24-295406	24-296267	for vehicles with increased ground clearance; without electronic suspension control; for vehicles without pneumatic suspension
B 4 DMC	E 200 EQ Boost 4-matic, E 260 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+, 2.0 E 220 d 4-matic 04/18 – / 135 – 320 kW	24-265768 24-294676	24-265775	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-294676; 24-265768
B 4 DMC	E 200 EQ Boost 4-matic, E 260 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+, 2.0 E 220 d 4-matic 04/18 – / 135 – 320 kW	24-265768 24-294676	24-294720	For vehicles with comfort suspension; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-294676; 24-265768
B 4 DMC	E 300 EQ Boost, 2.0 E 220 d 06/19 – / 147 – 190 kW	24-265157 24-295390	24-294720	For vehicles with comfort suspension; without electronic suspension control; for vehicles without pneumatic suspension FA: for OE number: A 213 320 35 30
B 4 DMC	E 350 e, E 350 EQ Boost 07/16 – / 210 – 235 kW	24-265157 24-295390	24-296267	without electronic suspension control; for vehicles without pneumatic suspension FA: for OE number: A 213 320 35 30
B 4 DTC	2.0 E 220 d 4-matic 02/22 – / 147 kW	26-265841 26-265858		with electronic suspension control FA: 26-265858; 26-265841
B 4 AMC	E 350 e, E 350 EQ Boost, 2.0 E 220 d 07/16 – / 147 – 235 kW	44-286637 44-286644	26-269993	for pneumatic suspension vehicles; with electronic suspension control FA: 44-286644; 44-286637



MERCEDES-BENZ				
MERCEDES-BENZ E-CLASS (W213)				
B 4 AMC	2.0 E 220 d 4-matic 02/22 - / 147 kW	44-288853 44-288860		26-280875 1/1
				for pneumatic suspension vehicles FA: 44-288860; 44-288853
B 6	E 200 EQ Boost, E 260 EQ Boost, E 300 e, E 300 EQ Boost, E 350 e, 2.0 E 220 d, E 300 de 07/16 - / 135 - 235 kW	24-257978 1/1		24-257985 1/1
				for vehicles without pneumatic suspension; without electronic suspension control; without off-road suspension; with standard chassis
B 6	E 200 EQ Boost, E 260 EQ Boost, E 300 e, E 300 EQ Boost, E 350 e, E 350 EQ Boost, 2.0 E 220 d, E 300 de 07/16 - / 135 - 235 kW	24-257978 1/1		24-273046 1/1
				for vehicles without pneumatic suspension; without electronic suspension control; with off-road suspension; with standard chassis
B 6	E 200 EQ Boost 4-matic, E 260 EQ Boost 4-matic, E 300 e 4-matic, E 350 EQ Boost, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+, 2.0 E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic 04/18 - / 135 - 320 kW	24-265614 24-265621		24-257985 1/1
				with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-265621; 24-265614
B 6	E 200 EQ Boost 4-matic, E 260 EQ Boost 4-matic, E 300 e 4-matic, E 350 EQ Boost, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+, 2.0 E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic 04/18 - / 135 - 320 kW	24-265614 24-265621		
				for vehicles with increased ground clearance; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-265621; 24-265614
B 8	E 200 EQ Boost, E 260 EQ Boost, E 300 e, E 300 EQ Boost, E 350 e, E 350 EQ Boost, 2.0 E 220 d, E 300 de 07/16 - / 135 - 235 kW	24-257992 1/1		24-258005 1/1
				with sports suspension; for vehicles without pneumatic suspension; without electronic suspension control
B 8	E 200 EQ Boost 4-matic, E 260 EQ Boost 4-matic, E 300 e 4-matic, E 350 EQ Boost, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+, 2.0 E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic 04/18 - / 135 - 320 kW	24-265713 24-265720		24-258005 1/1
				with sports suspension; for left-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-265713
B 8	E 200 EQ Boost 4-matic, E 260 EQ Boost 4-matic, E 300 e 4-matic 04/19 - / 135 - 235 kW	24-273633 24-265713 24-265720 24-273640		24-273039 1/1
				with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-265713; 24-273633
B 8	E 350 EQ Boost, AMG E 53 EQ Boost 4-matic+ 04/18 - / 220 - 320 kW	24-265713 24-273633 24-273640 24-265720		24-273039 1/1
				with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-273633; 24-265713
B 8	E 450 EQ Boost 4-matic, E 300 de 4-matic, E 300 d 4-matic 06/20 - / 195 - 270 kW	24-273633 24-265713 24-273640 24-265720		24-273039 1/1
				with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-273633; 24-265713
B 8	2.0 E 220 d 4-matic 02/22 - / 147 kW	24-265713 24-273633 24-265720 24-273640		24-273039 1/1
				with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-265713; 24-273633
B12 PK	E 200 EQ Boost, 2.0 E 220 d 06/19 - / 145 - 147 kW	46-335586		Conditions see certificates; without electronic suspension control; for vehicles without pneumatic suspension; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1110 kg RA: Axle load [kg] to 1265 kg
B14	E 200 EQ Boost, E 260 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, 2.0 E 220 d 08/18 - / 135 - 220 kW	47-258037		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1340 kg
B14	E 300 e, E 350 e, E 300 de 07/16 - / 210 - 235 kW	47-258037		for vehicles without pneumatic suspension; without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1340 kg
B16 PSS10	E 200 EQ Boost, E 260 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, 2.0 E 220 d 08/18 - / 135 - 220 kW	48-258067		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1340 kg
B16 PSS10	E 200 EQ Boost 4-matic, E 260 EQ Boost 4-matic, E 300 e 4-matic, E 350 EQ Boost, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+, 2.0 E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic 04/18 - / 135 - 320 kW	48-265737		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1280 kg; Lowering ca. [mm]: 20-45 mm RA: Axle load [kg] to 1340 kg; Lowering ca. [mm]: 30-45 mm
B16 PSS10	E 300 e, E 350 e, E 300 de 07/16 - / 210 - 235 kW	48-258067		for vehicles without pneumatic suspension; without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1340 kg

MERCEDES-BENZ				
MERCEDES-BENZ E-CLASS T-Model (S213)				
B 1	E 200 EQ Boost, E 200 EQ Boost 4-matic, E 300 e, E 300 EQ Boost, E 450 EQ Boost, AMG E 53 EQ Boost 4-matic+, E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic, E 300 de 04/18 - / 145 - 320 kW	12-307197		with standard chassis
B 4 DMC	E 200 EQ Boost, E 300 e, E 300 EQ Boost, E 220 d, E 300 de 10/18 - / 145 - 235 kW	24-295390 $\frac{1}{H}$	19-273075 $\frac{1}{O}$	without electronic suspension control; with standard chassis
B 4 DMC	E 200 EQ Boost, E 300 e, E 300 EQ Boost, E 220 d, E 300 de 10/18 - / 145 - 235 kW	24-265157 $\frac{1}{H}$	19-273082 $\frac{1}{O}$	without electronic suspension control; with sports suspension; For vehicles with comfort suspension FA: for OE number: A 213 320 35 30
B 4 DTC	E 200 EQ Boost, E 300 e, E 300 EQ Boost, E 220 d, E 300 de 10/18 - / 145 - 235 kW		26-280875 $\frac{1}{H}$	with electronic suspension control
B 4 AMC	E 200 EQ Boost 4-matic, E 450 EQ Boost, AMG E 53 EQ Boost 4-matic+, E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic 04/18 - / 145 - 320 kW	44-288853 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 44-288860 $\frac{1}{H}$	26-280875 $\frac{1}{H}$	for pneumatic suspension vehicles FA: 44-288860; 44-288853
B 6	E 200 EQ Boost, E 300 e, E 300 EQ Boost, E 220 d, E 300 de 10/18 - / 145 - 235 kW	24-257978 $\frac{1}{H}$	24-266222 $\frac{1}{O}$	without electronic suspension control; with standard chassis
B 6	E 200 EQ Boost 4-matic, E 450 EQ Boost, AMG E 53 EQ Boost 4-matic+, E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic 04/18 - / 145 - 320 kW	24-265614 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-265621 $\frac{1}{H}$	24-266222 $\frac{1}{O}$	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-265621; 24-265614
B 8	E 200 EQ Boost, E 300 e, E 300 EQ Boost, E 220 d, E 300 de 10/18 - / 145 - 235 kW	24-257992 $\frac{1}{H}$	24-266239 $\frac{1}{O}$	without electronic suspension control; with sports suspension
B 8	E 200 EQ Boost 4-matic, E 450 EQ Boost, AMG E 53 EQ Boost 4-matic+, E 220 d 4-matic, E 300 de 4-matic, E 300 d 4-matic 04/18 - / 145 - 320 kW	24-265713 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-265720 $\frac{1}{H}$	24-266239 $\frac{1}{O}$	with sports suspension; for left-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-265713
B 8	E 200 EQ Boost 4-matic, E 450 EQ Boost 06/19 - / 145 - 270 kW	24-273633 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-265713 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-273640 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-265720 $\frac{1}{H}$	24-266239 $\frac{1}{O}$	with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-273633; 24-265713
B 8	AMG E 53 EQ Boost 4-matic+, E 220 d 4-matic 04/18 - / 147 - 320 kW	24-265713 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-273633 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-273640 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-265720 $\frac{1}{H}$	24-266239 $\frac{1}{O}$	with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-273633; 24-265713
B 8	E 300 de 4-matic, E 300 d 4-matic 08/20 - / 195 - 225 kW	24-273633 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-265713 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-265720 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-273640 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$	24-266239 $\frac{1}{O}$	with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-265713; 24-273633
B12 PK	E 220 d 02/22 - / 147 kW	46-348012		Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1110 kg; Lowering ca. [mm]: 15-20 mm RA: Axle load [kg] to 1530 kg; Lowering ca. [mm]: 25 mm

MERCEDES-BENZ E-CLASS All-Terrain (S213)				
B 1	E 200 EQ Boost, E 450 EQ Boost 08/20 - / 145 - 270 kW	12-307197		with standard chassis
B 4 AMC	E 200 EQ Boost, E 450 EQ Boost 08/20 - / 145 - 270 kW	44-286736 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 44-286743 $\frac{1}{H}$		with standard chassis; for pneumatic suspension vehicles FA: 44-286743; 44-286736

MERCEDES-BENZ E-CLASS Coupe (C238)				
B 1	E 260 EQ Boost, E 260 EQ Boost 4-matic, E 200 EQ Boost, E 200 EQ Boost 4-matic, E 300 EQ Boost, E 300 d 4-matic, E 350 EQ Boost 4-matic, E 350 EQ Boost, E 450 EQ Boost, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+ 10/17 - / 135 - 320 kW	12-307197		with standard chassis
B 4 DMC	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, E 450 EQ Boost 10/17 - / 135 - 270 kW	24-295390 $\frac{1}{H}$		
B 4 DMC	E 260 EQ Boost 4-matic, E 200 EQ Boost 4-matic, E 350 EQ Boost 4-matic 09/18 - / 135 - 220 kW	24-265768 $\frac{1}{H}$ $\frac{1}{X}$ $\frac{1}{K}$ $\frac{1}{L}$ $\frac{1}{M}$ $\frac{1}{N}$ $\frac{1}{O}$ $\frac{1}{P}$ $\frac{1}{Q}$ $\frac{1}{R}$ $\frac{1}{S}$ $\frac{1}{T}$ $\frac{1}{U}$ $\frac{1}{V}$ $\frac{1}{W}$ $\frac{1}{X}$ $\frac{1}{Y}$ $\frac{1}{Z}$ 24-294676 $\frac{1}{H}$		without electronic suspension control; for left-hand drive vehicles FA: 24-294676; 24-265768



MERCEDES-BENZ			
MERCEDES-BENZ E-CLASS Coupe (C238)			
B 4 AMC	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, E 450 EQ Boost 10/17 - / 135 - 270 kW	44-286637 44-286644	
			with standard chassis; for pneumatic suspension vehicles FA: 44-286644; 44-286637
B 6	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, E 450 EQ Boost 10/17 - / 135 - 270 kW	24-257978	
			for vehicles without pneumatic suspension; without electronic suspension control; without off-road suspension
B 6	E 260 EQ Boost 4-matic, E 200 EQ Boost 4-matic, E 300 d 4-matic, E 350 EQ Boost 4-matic, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+ 05/18 - / 135 - 320 kW	24-265713 24-265720	
			with standard chassis; for left-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-265713
B 6	E 260 EQ Boost 4-matic, E 300 d 4-matic, E 450 EQ Boost 4-matic 12/19 - / 135 - 270 kW	24-273633 24-265713 24-273640 24-265720	
			with standard chassis; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-273633; 24-265713
B 6	E 200 EQ Boost 4-matic, E 350 EQ Boost 4-matic 09/18 - / 145 - 220 kW	24-265713 24-273633 24-273640 24-265720	
			with standard chassis; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-273633; 24-265713
B 6	AMG E 53 EQ Boost 4-matic+ 05/18 - / 320 kW	24-265713 24-273633 24-265720 24-273640	
			with standard chassis; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-265713; 24-273633
B 8	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, E 450 EQ Boost 10/17 - / 135 - 270 kW	24-257992	
			with sports suspension; for vehicles without pneumatic suspension; without electronic suspension control
B14	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, E 450 EQ Boost 10/17 - / 135 - 270 kW	47-258037	
			for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1255 kg
B16 PSS10	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost, E 450 EQ Boost 10/17 - / 135 - 270 kW	48-258067	
			for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1255 kg
B16 PSS10	E 260 EQ Boost 4-matic, E 200 EQ Boost 4-matic, E 300 d 4-matic, E 350 EQ Boost 4-matic, E 450 EQ Boost 4-matic, AMG E 53 EQ Boost 4-matic+ 05/18 - / 135 - 320 kW	48-265737	
			for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1280 kg; Lowering ca. [mm]: 20-45 mm RA: Axle load [kg] to 1300 kg; Lowering ca. [mm]: 30-45 mm
MERCEDES-BENZ E-CLASS Convertible (A238)			
B 4 DMC	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost 10/17 - / 135 - 220 kW	24-295390	
			Trim Level Avantgarde
B 4 DMC	E 260 EQ Boost 4-matic, E 200 EQ Boost 4-matic, E 300 d 4-matic, E 450 EQ Boost 4-matic 06/19 - / 135 - 270 kW	24-265768 24-294676	
			without electronic suspension control; for left-hand drive vehicles FA: 24-294676; 24-265768
B 6	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost 10/17 - / 135 - 220 kW	24-257978	
			for vehicles without pneumatic suspension; without electronic suspension control; without off-road suspension
B 6	E 260 EQ Boost 4-matic, E 200 EQ Boost 4-matic, E 300 d 4-matic, E 450 EQ Boost 4-matic 06/19 - / 135 - 270 kW	24-265713 24-265720	
			with sports suspension; for left-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-265713
B 6	E 260 EQ Boost 4-matic, E 200 EQ Boost 4-matic 06/19 - / 135 - 145 kW	24-265713 24-273633 24-265720 24-273640	
			with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-265713; 24-273633
B 6	E 300 d 4-matic 04/21 - / 195 kW	24-265713 24-273633 24-273640 24-265720	
			with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-273640; 24-273633; 24-265713
B 6	E 450 EQ Boost 4-matic 07/20 - / 270 kW	24-273633 24-265713 24-265720 24-273640	
			with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-265713; 24-273633
B 8	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost 10/17 - / 135 - 220 kW	24-257992	
			with sports suspension; for vehicles without pneumatic suspension; without electronic suspension control



MERCEDES-BENZ

MERCEDES-BENZ E-CLASS Convertible (A238)

B14	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost 10/17 - / 135 - 220 kW	47-258037		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1255 kg
B16 PSS10	E 260 EQ Boost, E 200 EQ Boost, E 300 EQ Boost, E 350 EQ Boost 10/17 - / 135 - 220 kW	48-258067		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1255 kg
B16 PSS10	E 260 EQ Boost 4-matic, E 200 EQ Boost 4-matic, E 300 d 4-matic, E 450 EQ Boost 4-matic 06/19 - / 135 - 270 kW	48-265737		for vehicles without pneumatic suspension; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1280 kg; Lowering ca. [mm]: 20-45 mm RA: Axle load [kg] to 1300 kg; Lowering ca. [mm]: 30-45 mm

MERCEDES-BENZ S-CLASS (W221)

B 1 AMC	S 400 Hybrid 01/09 - 12/13 205 - 220 kW	10-255605		for pneumatic suspension vehicles
B 4 AMC	S 400 Hybrid 01/09 - 12/13 205 - 220 kW	44-109462	44-109479 44-109486	for pneumatic suspension vehicles; with standard chassis RA: 44-109486; 44-109479

MERCEDES-BENZ S-CLASS (W222, V222, X222)

B 1 AMC	S 320 EQ Boost, S 400 Hybrid / h, S 450 EQ Boost, S 450 EQ Boost 4-matic, S 450 Maybach EQ Boost 4-matic, S 500 EQ Boost, S 500 EQ Boost 4-matic, S 500 Hybrid / e, S 560 e, S 300 BlueTEC Hybrid / h 05/13 - 05/17 170 - 350 kW	10-309414		
B 4 AMC	S 400 Hybrid / h, S 450 EQ Boost, S 500 EQ Boost, S 500 Hybrid / e, S 320 EQ Boost 05/13 - 05/17 220 - 320 kW	44-239961 44-239978	44-239985 44-239992	for pneumatic suspension vehicles; with electronic suspension control FA: 44-239978; for OE number: A 222 320 01 13; for OE number: A 222 320 47 13; 44-239961; for OE number: A 222 320 02 13; for OE number: A 222 320 48 13 RA: 44-239992; for OE number: A 222 320 53 13; for OE number: A 222 320 73 13; 44-239985; for OE number: A 222 320 52 13; for OE number: A 222 320 74 13
B 4 AMC	S 400 Hybrid / h, S 450 EQ Boost, S 450 EQ Boost 4-matic, S 500 EQ Boost, S 500 Hybrid / e, S 300 BlueTEC Hybrid / h, S 320 EQ Boost 05/13 - 05/17 170 - 320 kW	44-275389 44-275396	44-275426 44-275433	for pneumatic suspension vehicles; with electronic suspension control FA: 44-275396; for OE number: A 222 320 01 00; for OE number: A 222 320 19 00; 44-275389; for OE number: A 222 320 02 00; for OE number: A 222 320 20 00 RA: 44-275433; for OE number: A 222 320 29 00; for OE number: A 222 320 59 01; 44-275426; for OE number: A 222 320 30 00; for OE number: A 222 320 60 01
B 4 AMC	S 450 EQ Boost 4-matic 07/17 - / 270 kW	44-240004 44-240011	44-239985 44-239992	for pneumatic suspension vehicles FA: 44-240011; for OE number: A 222 320 49 13; for OE number: A 222 320 63 13; for OE number: A 222 320 81 13; 44-240004; for OE number: A 222 320 50 13; for OE number: A 222 320 64 13; for OE number: A 222 320 82 13 RA: 44-239992; for OE number: A 222 320 53 13; for OE number: A 222 320 73 13; 44-239985; for OE number: A 222 320 52 13; for OE number: A 222 320 74 13
B 4 AMC	S 450 EQ Boost 4-matic 07/17 - / 270 kW	44-275501 44-275518	44-275426 44-275433	for pneumatic suspension vehicles FA: 44-275518; for OE number: A 222 320 21 00; for OE number: A 222 320 05 00; 44-275501; for OE number: A 222 320 22 00 RA: 44-275433; for OE number: A 222 320 29 00; for OE number: A 222 320 59 01; 44-275426; for OE number: A 222 320 30 00; for OE number: A 222 320 60 01
B 4 AMC	S 300 BlueTEC Hybrid / h 02/14 - 05/17 170 kW	44-239961 44-239978	44-239985 44-239992	for pneumatic suspension vehicles FA: 44-239978; for OE number: A 222 320 01 13; for OE number: A 222 320 47 13; 44-239961; for OE number: A 222 320 02 13; for OE number: A 222 320 48 13 RA: 44-239992; for OE number: A 222 320 53 13; for OE number: A 222 320 73 13; 44-239985; for OE number: A 222 320 52 13; for OE number: A 222 320 74 13

MERCEDES-BENZ AMG GT (X290)

ER	43 EQ Boost, 43 EQ Boost 4-matic+, 53 EQ Boost 4-matic+ 09/18 - / 270 - 320 kW	89-310458		without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; not permitted on public roads; Lowering ca. [mm]: 0-20 mm
----	---	-----------	--	---

MERCEDES-BENZ M-CLASS (W164)

B 1 AMC	ML 450 Hybrid 4-matic 09/09 - 12/11 208 kW	10-255612		for pneumatic suspension vehicles
B 3	ML 450 Hybrid 4-matic 09/09 - 12/11 208 kW	36-166640	36-165599	with standard chassis; for coil-spring suspension vehicles
B 3	ML 450 Hybrid 4-matic 09/09 - 12/11 208 kW	36-200818	36-201853	with standard chassis; Reinforced Version ; for coil-spring suspension vehicles



MERCEDES-BENZ

MERCEDES-BENZ M-CLASS (W164)

B 4	ML 450 Hybrid 4-matic 09/09 – 12/11	208 kW	24-166652 $\frac{1}{H}$ 12-167616	$\frac{1}{H}$ PK	24-144834 $\frac{1}{H}$	with standard chassis; for coil-spring suspension vehicles
B 4 AMC	ML 450 Hybrid 4-matic 09/09 – 12/11	208 kW	44-165062 $\frac{X}{H}$	$\frac{X}{H}$	24-158657 $\frac{X}{H}$ 40-247687	without ADS; for pneumatic suspension vehicles; with electronic suspension control
B 4 AMC	ML 450 Hybrid 4-matic 09/09 – 12/11	208 kW	44-156251 $\frac{X}{H}$	$\frac{X}{H}$	24-166980 $\frac{X}{H}$ 40-247687	with ADS; for pneumatic suspension vehicles RA: with electronic suspension control
B 6	ML 450 Hybrid 4-matic 09/09 – 12/11	208 kW	12-167616 24-124362 $\frac{1}{H}$	$\frac{1}{H}$ PK	24-293006 $\frac{1}{H}$	with standard chassis; for coil-spring suspension vehicles

MERCEDES-BENZ GLE (W166)

B 1 AMC	500 e 4-matic 04/15 – 10/18	325 kW	10-255650			
B 3	500 e 4-matic 04/15 – 10/18	325 kW			36-165599	with standard chassis
B 3 AMC	500 e 4-matic 04/15 – 10/18	325 kW			40-247687	with ADS; for pneumatic suspension vehicles; with electronic suspension control
B 4	500 e 4-matic 04/15 – 10/18	325 kW	24-293792 $\frac{1}{H}$		24-293013 $\frac{1}{H}$	with standard chassis
B 4 AMC	500 e 4-matic 04/15 – 10/18	325 kW	44-283155 $\frac{X}{H}$ 44-283162 $\frac{X}{H}$	$\frac{1}{H}$ $\frac{1}{H}$	27-271001 $\frac{1}{H}$ 40-247687	with ADS; for pneumatic suspension vehicles; with electronic suspension control FA: 44-283162; 44-283155
B 4 AMC	500 e 4-matic 04/15 – 10/18	325 kW	44-273439 $\frac{X}{H}$ 44-273446 $\frac{X}{H}$	$\frac{1}{H}$ $\frac{1}{H}$	40-247687	with ADS; for pneumatic suspension vehicles; with electronic suspension control FA: 44-273446; 44-273439
B 6	500 e 4-matic 04/15 – 10/18	325 kW	24-293808 $\frac{1}{H}$		24-293020 $\frac{1}{H}$	for coil-spring suspension vehicles; with standard chassis
B 8	500 e 4-matic 04/15 – 10/18	325 kW	24-293839 $\frac{1}{H}$		24-293044 $\frac{1}{H}$	with lowered chassis; with sports suspension
B12 PK	500 e 4-matic 04/15 – 10/18	325 kW	46-262431			Conditions see certificates; without leveling control; without electronic suspension control; for coil-spring suspension vehicles; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1500 kg RA: Axle load [kg] to 1650 kg

MERCEDES-BENZ EQA (H243)

B 4	EQA 250, EQA 250+ 02/21 – /	140 kW	22-330017 22-330024	$\frac{1}{H}$ $\frac{1}{H}$	19-329888 $\frac{1}{O}$	For vehicles with comfort suspension FA: 22-330024; 22-330017
B 4	EQA 250, EQA 250+ 02/21 – /	140 kW	22-330031 22-330048	$\frac{1}{H}$ $\frac{1}{H}$	19-329888 $\frac{1}{O}$	with standard chassis; Vehicle Type: Avantgarde FA: 22-330048; 22-330031
B 4	EQA 300 4-matic, EQA 350 4-matic 05/21 – /	168 – 215 kW	22-330017 22-330024	$\frac{1}{H}$ $\frac{1}{H}$	19-329888 $\frac{1}{O}$	For vehicles with comfort suspension FA: 22-330024; 22-330017
B 4	EQA 300 4-matic, EQA 350 4-matic 05/21 – /	168 – 215 kW	22-330031 22-330048	$\frac{1}{H}$ $\frac{1}{H}$	19-329888 $\frac{1}{O}$	with standard chassis; Vehicle Type: Avantgarde FA: 22-330048; 22-330031
B 6	EQA 250, EQA 250+, EQA 300 4-matic, EQA 350 4-matic 02/21 – /	140 – 215 kW	22-338334 22-338341	$\frac{1}{H}$ $\frac{1}{H}$	24-338356 $\frac{1}{O}$	with standard chassis FA: 22-338341; 22-338334

MERCEDES-BENZ EQB (X243)

B 4	EQB 250, EQB 300 4-matic, EQB 350 4-matic 12/21 – /	140 – 215 kW	22-330017 22-330024	$\frac{1}{H}$ $\frac{1}{H}$	19-329888 $\frac{1}{O}$	For vehicles with comfort suspension FA: 22-330024; 22-330017
B 4	EQB 250, EQB 300 4-matic, EQB 350 4-matic 12/21 – /	140 – 215 kW	22-330031 22-330048	$\frac{1}{H}$ $\frac{1}{H}$	19-329888 $\frac{1}{O}$	with standard chassis; Vehicle Type: Avantgarde FA: 22-330048; 22-330031
B 6	EQB 250, EQB 300 4-matic, EQB 350 4-matic 12/21 – /	140 – 215 kW	22-338334 22-338341	$\frac{1}{H}$ $\frac{1}{H}$	24-338356 $\frac{1}{O}$	with standard chassis FA: 22-338341; 22-338334

MERCEDES-BENZ GLA (H247)

B 6	GLA 250 e 06/20 – /	160 kW	22-324498 22-324504	$\frac{1}{H}$ $\frac{1}{H}$	24-324519 $\frac{1}{O}$	with standard chassis; For vehicles with comfort suspension FA: 22-324504; without electronic suspension control; 22-324498 RA: Rigid Axle
-----	------------------------	--------	------------------------	-----------------------------	-------------------------	--

MERCEDES-BENZ GLC (X253)

B 1	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost, 300 EQ Boost 4-matic, 300 e 4-matic, 350 e 4-matic, 300 de 4-matic 01/16 – 04/19	145 – 235 kW	12-307197			with standard chassis
-----	---	--------------	-----------	--	--	-----------------------


MERCEDES-BENZ
MERCEDES-BENZ GLC (X253)

B 4 DMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	24-262934 1/2 24-262965 1/2	19-263007 1/2	with standard chassis; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 485 FA: 24-262965; 24-262934 RA: for PR number: 482
B 4 DMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	24-262989 1/2 24-262996 1/2	19-263038 1/2	with sports suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 486 FA: 24-262996; 24-262989
B 4 DMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	24-263016 1/2 24-263023 1/2	19-263007 1/2	with off-road suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 482 FA: 24-263023; 24-263016 RA: for PR number: 485
B 4 DMC	350 e 4-matic 01/16 - 04/19 235 kW	24-262989 1/2 24-262996 1/2	19-263038 1/2	with sports suspension; for PR number: 486 FA: 24-262996; 24-262989
B 4 DMC	350 e 4-matic 01/16 - 04/19 235 kW	24-263016 1/2 24-263023 1/2	19-288901 1/2	for vehicles with increased ground clearance; for PR number: 482 FA: 24-263023; 24-263016
B 4 DTC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	26-270005 1/2 26-270012 1/2	26-270029 1/2	for coil-spring suspension vehicles; with electronic suspension control; for PR number: 459 FA: 26-270012; 26-270005
B 4 DTC	350 e 4-matic 01/16 - 04/19 235 kW	26-270005 1/2 26-270012 1/2	26-270029 1/2	for coil-spring suspension vehicles; with electronic suspension control; for PR number: 459 FA: 26-270012; 26-270005
B 4 AMC	F-CELL, 200 EQ Boost, 200 EQ Boost 4-matic, 300 4-matic, 300 EQ Boost, 300 EQ Boost 4-matic, 300 e 4-matic, 300 de 4-matic 10/18 - 04/20 80 - 235 kW	44-262884 1/2 44-262891 1/2	26-262901 1/2	for pneumatic suspension vehicles; with electronic suspension control; for PR number: 489; for PR number: 806; for PR number: 807 FA: 44-262891; 44-262884
B 4 AMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	44-281052 1/2 44-281045 1/2	26-288932 1/2	for pneumatic suspension vehicles; with electronic suspension control FA: 44-281045; 44-281052 RA: for PR number: 489; for PR number: 808; for OE number: A 253 320 45 00
B 4 AMC	350 e 4-matic 01/16 - 04/19 235 kW	44-281052 1/2 44-281045 1/2		for pneumatic suspension vehicles; with electronic suspension control FA: 44-281045; 44-281052
B 4 AMC	350 e 4-matic 01/16 - 04/19 235 kW	44-262884 1/2 44-262891 1/2	26-262901 1/2	for pneumatic suspension vehicles; with electronic suspension control; for PR number: 489; for PR number: 806; for PR number: 807 FA: 44-262891; 44-262884
B 6	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	24-263047 1/2 24-263092 1/2	24-263061 1/2	with standard chassis; with sports suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 485; for PR number: 486 FA: 24-263092; 24-263047 RA: for PR number: 482
B 6	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	24-263054 1/2 24-263078 1/2	24-263061 1/2	with off-road suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 482 FA: 24-263078; 24-263054 RA: for PR number: 485; for PR number: 486
B12 PK	200 4-matic, 300 4-matic 05/22 - / 145 - 190 kW	46-338969		without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 25 mm RA: Axle load [kg] to 1340 kg; Lowering ca. [mm]: 20 mm

MERCEDES-BENZ GLC Coupe (C253)

B 1	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic, 300 e 4-matic, 350 e 4-matic, 300 de 4-matic 10/16 - 04/19 145 - 235 kW	12-307197		with standard chassis
B 4 DMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	24-262989 1/2 24-262996 1/2	19-263038 1/2	with sports suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 486 FA: 24-262996; 24-262989
B 4 DMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	24-263016 1/2 24-263023 1/2	19-263007 1/2	with off-road suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 482 FA: 24-263023; 24-263016 RA: for PR number: 485
B 4 DMC	350 e 4-matic 10/16 - 04/19 235 kW	24-262989 1/2 24-262996 1/2	19-263038 1/2	with sports suspension; for PR number: 486 FA: 24-262996; 24-262989
B 4 DMC	350 e 4-matic 10/16 - 04/19 235 kW	24-263016 1/2 24-263023 1/2	19-288901 1/2	for vehicles with increased ground clearance; for PR number: 482 FA: 24-263023; 24-263016
B 4 DTC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	26-270005 1/2 26-270012 1/2	26-270029 1/2	for coil-spring suspension vehicles; with electronic suspension control; for PR number: 459 FA: 26-270012; 26-270005
B 4 DTC	350 e 4-matic 10/16 - 04/19 235 kW	26-270005 1/2 26-270012 1/2	26-270029 1/2	for coil-spring suspension vehicles; with electronic suspension control; for PR number: 459 FA: 26-270012; 26-270005
B 4 AMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	44-281052 1/2 44-281045 1/2	26-288932 1/2	for pneumatic suspension vehicles; with electronic suspension control FA: 44-281045; 44-281052 RA: for PR number: 489; for PR number: 808; for OE number: A 253 320 45 00



MERCEDES-BENZ					
MERCEDES-BENZ GLC Coupe (C253)					
B 4 AMC	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic 04/19 - / 145 - 190 kW	44-262884 44-262891	 	26-262901	for pneumatic suspension vehicles; with electronic suspension control; for PR number: 489; for PR number: 806; for PR number: 807 FA: 44-262891; 44-262884
B 4 AMC	300 e 4-matic, 350 e 4-matic, 300 de 4-matic 10/16 - 04/19 225 - 235 kW	44-262884 44-262891	 	26-262901	for pneumatic suspension vehicles; with electronic suspension control; for PR number: 489; for PR number: 806; for PR number: 807 FA: 44-262891; 44-262884
B 4 AMC	350 e 4-matic 10/16 - 04/19 235 kW	44-281052 44-281045	 		for pneumatic suspension vehicles; with electronic suspension control FA: 44-281045; 44-281052
B 4 AMC	350 e 4-matic 10/16 - 04/19 235 kW	44-262884 44-262891	 	26-262901	for pneumatic suspension vehicles; with electronic suspension control; for PR number: 489; for PR number: 806; for PR number: 807 FA: 44-262891; 44-262884
B 6	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic, 350 e 4-matic 10/16 - 04/19 145 - 235 kW	24-263047 24-263092	 	24-263061	with standard chassis; with sports suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 485; for PR number: 486 FA: 24-263092; 24-263047 RA: for PR number: 482
B 6	200 EQ Boost, 200 EQ Boost 4-matic, 300 EQ Boost 4-matic, 350 e 4-matic 10/16 - 04/19 145 - 235 kW	24-263054 24-263078	 	24-263061	with off-road suspension; without electronic suspension control; for coil-spring suspension vehicles; for PR number: 482 FA: 24-263078; 24-263054 RA: for PR number: 485; for PR number: 486
B12 PK	200 EQ Boost 4-matic 04/19 - / 145 kW	46-338969			without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1250 kg; Lowering ca. [mm]: 25 mm RA: Axle load [kg] to 1340 kg; Lowering ca. [mm]: 20 mm
MERCEDES-BENZ VITO Bus (W639)					
B 3 AMC	E-CELL 03/12 - / 60 kW			40-275635	with leveling control; for pneumatic suspension vehicles
MERCEDES-BENZ VITO / MIXTO Van (W639)					
B 3 AMC	E-CELL 03/12 - / 60 kW			40-275635	with leveling control; for pneumatic suspension vehicles
MERCEDES-BENZ eVITO Van (W447)					
B 1	Electric 03/19 - / 85 kW	12-296156			with standard chassis
B 4	Electric 03/19 - / 85 kW	22-276131		24-276108	with standard chassis FA: serie production spring seat must be used
B 6	Electric 03/19 - / 85 kW	22-282828		24-276870	FA: serie production spring seat must be used
MERCEDES-BENZ eVITO Tourer (W447)					
B 1	Electric 04/19 - / 85 - 150 kW	12-296156			with standard chassis
B 4	Electric 04/19 - / 85 - 150 kW	22-276131		24-276108	with standard chassis FA: serie production spring seat must be used
B 6	Electric 04/19 - / 85 - 150 kW	22-282828		24-262187	with standard chassis FA: serie production spring seat must be used
B 6	Electric 04/19 - / 85 - 150 kW	22-282828		24-276870	FA: serie production spring seat must be used
MERCEDES-BENZ SPRINTER 3-t Bus (B903)					
B 4	308 E 01/96 - 05/06 40 kW	22-214751 11-270430		19-064529	with standard chassis RA: Length 1 [mm]: 323 mm; Length 2 [mm]: 510 mm; Length [mm]: 547 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 4	308 E 01/96 - 05/06 40 kW	22-214751 11-270430		19-100180	with off-road suspension RA: Length 1 [mm]: 322 mm; Length 2 [mm]: 506 mm; Length [mm]: 543 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
B 6	308 E 01/96 - 05/06 40 kW	11-270430 22-226631		24-223911	RA: Length [mm]: 541 mm; Length 1 [mm]: 323 mm; Length 2 [mm]: 506 mm; Mounting points diameter [mm] 14 mm; Mounting points diameter [mm] 12 mm
MERCEDES-BENZ EQV (W447)					
B 4	EQV 300, EQV 250 06/20 - / 150 kW	22-276131		24-276108	with standard chassis FA: serie production spring seat must be used
B 6	EQV 300, EQV 250 06/20 - / 150 kW	22-282828		24-276870	FA: serie production spring seat must be used

MERCEDES-BENZ (BBDC)					
MERCEDES-BENZ (BBDC) C-CLASS (W205)					
B 4 DMC	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW	24-251556 $\frac{1}{H}$ 24-251563 $\frac{1}{H}$	 	24-251327 $\frac{1}{O}$	with standard chassis FA: 24-251563; 24-251556
B 4 DMC	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW	24-251631 $\frac{1}{H}$ 24-251648 $\frac{1}{H}$	 	24-251655 $\frac{1}{O}$	with sports suspension FA: 24-251648; 24-251631
B 4 DMC	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW			24-251419 $\frac{1}{O}$	with off-road suspension
B 4 DMC	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW			24-251419 $\frac{1}{O}$	with off-road suspension
B 4 DMC	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW	24-257237 $\frac{1}{H}$ 24-252027 $\frac{1}{H}$	 	24-251426 $\frac{1}{O}$	Vehicle Type: Avantgarde FA: 24-252027; 24-257237
B 4 AMC	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW	44-251598 $\frac{1}{H}$ 44-251604 $\frac{1}{H}$	 	26-251691 $\frac{1}{O}$ 26-251707 $\frac{1}{O}$	 for pneumatic suspension vehicles; with electronic suspension control FA: 44-251604; for OE number: A 205 320 49 68; 44-251598; for OE number: A 205 320 50 68 RA: 26-251707; for OE number: A 205 320 79 30; for OE number: A 205 320 43 30; 26-251691; for OE number: A 205 320 80 30; for OE number: A 205 320 44 30
B 6	C 260 EQ Boost, C 260 L EQ Boost, C 350 eL 01/15 - / 135 - 205 kW	24-241304 $\frac{1}{H}$		24-241311 $\frac{1}{O}$	FA: with standard chassis
B 6	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW	24-252034 $\frac{1}{H}$ 24-252041 $\frac{1}{H}$	 	24-241311 $\frac{1}{O}$	FA: 24-252041; 24-252034
B 8	C 260 EQ Boost, C 260 L EQ Boost, C 350 eL 01/15 - / 135 - 205 kW	24-241328 $\frac{1}{H}$		24-241335 $\frac{1}{O}$	FA: with sports suspension; for PR number: 486
B 8	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW	24-252058 $\frac{1}{H}$ 24-252065 $\frac{1}{H}$	 	24-241335 $\frac{1}{O}$	FA: 24-252065; 24-252058
B14	C 260 EQ Boost, C 260 L EQ Boost, C 350 eL 01/15 - / 135 - 205 kW			47-241343	without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Lowering ca. [mm]: 20-45 mm; Axle load [kg] to 1125 kg RA: Lowering ca. [mm]: 15-40 mm; Axle load [kg] to 1270 kg
B16 PSS10	C 260 EQ Boost, C 260 L EQ Boost, C 350 eL 01/15 - / 135 - 205 kW			48-241373	without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1125 kg RA: Axle load [kg] to 1270 kg
B16 PSS10	C 260 EQ Boost 4-matic, C 260 L EQ Boost 4-matic 10/18 - / 135 kW			48-252096	without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1125 kg RA: Axle load [kg] to 1325 kg
B16 PSS10	C 260 L EQ Boost 4-matic 10/18 - / 135 kW			48-252096	without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1125 kg RA: Axle load [kg] to 1325 kg
MERCEDES-BENZ (BBDC) E-CLASS (W212)					
B 1	E 400 L HYBRID 06/14 - / 225 kW	12-305612			for vehicles without pneumatic suspension
B 4 DMC	E 400 L HYBRID 06/14 - / 225 kW	22-197665 $\frac{1}{S}$		24-194112 $\frac{1}{O}$	without Airmatic DC; with standard chassis; with electronic suspension control
B 6	E 400 L HYBRID 06/14 - / 225 kW	22-309822 $\frac{1}{S}$		24-166874 $\frac{1}{O}$	without Airmatic DC; with standard chassis
MERCEDES-BENZ (BBDC) E-CLASS (W213)					
B 4 DMC	E 260 L EQ Boost, E 300 e L 03/19 - / 135 - 155 kW	24-295390 $\frac{1}{H}$		24-265775 $\frac{1}{O}$	without electronic suspension control; for vehicles without pneumatic suspension
B 4 DMC	E 260 L EQ Boost, E 300 e L 03/19 - / 135 - 155 kW	24-295390 $\frac{1}{H}$ 24-265157 $\frac{1}{H}$		24-291804 $\frac{1}{O}$	without electronic suspension control; for vehicles without pneumatic suspension FA: for OE number: A 213 320 35 30
B 4 DMC	E 260 L EQ Boost 4-matic, E 350 L EQ Boost 4-matic 03/19 - / 135 - 220 kW	24-265768 $\frac{1}{H}$ 24-294676 $\frac{1}{H}$	 	24-265775 $\frac{1}{O}$	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-294676; 24-265768
B 4 DMC	E 260 L EQ Boost 4-matic, E 350 L EQ Boost 4-matic 03/19 - / 135 - 220 kW	24-265768 $\frac{1}{H}$ 24-294676 $\frac{1}{H}$	 	24-294720 $\frac{1}{O}$	For vehicles with comfort suspension; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-294676; 24-265768
B 6	E 260 L EQ Boost, E 300 e L 03/19 - / 135 - 155 kW	24-257978 $\frac{1}{H}$		24-257985 $\frac{1}{O}$	for vehicles without pneumatic suspension; without electronic suspension control; without off-road suspension; with standard chassis
B 6	E 260 L EQ Boost, E 300 e L 03/19 - / 135 - 155 kW	24-257978 $\frac{1}{H}$		24-273046 $\frac{1}{O}$	for vehicles without pneumatic suspension; without electronic suspension control; with off-road suspension; with standard chassis
B 6	E 260 L EQ Boost 4-matic 03/19 - / 135 kW	24-265614 $\frac{1}{H}$ 24-265621 $\frac{1}{H}$	 	24-273046 $\frac{1}{O}$ 24-257985 $\frac{1}{O}$	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-265621; 24-265614





MERCEDES-BENZ (BBDC)

MERCEDES-BENZ (BBDC) E-CLASS (W213)

B 6	E 260 L EQ Boost 4-matic, E 350 L EQ Boost 4-matic 03/19 - / 135 - 220 kW	24-265614 $\frac{1}{H}$ 24-265621 $\frac{1}{H}$	 		for vehicles with increased ground clearance; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-265621; 24-265614
B 6	E 350 L EQ Boost 4-matic 03/19 - / 220 kW	24-265614 $\frac{1}{H}$ 24-265621 $\frac{1}{H}$	 	24-257985 $\frac{1}{O}$ 24-273046 $\frac{1}{O}$	with standard chassis; without electronic suspension control; for vehicles without pneumatic suspension FA: 24-265621; 24-265614
B 8	E 260 L EQ Boost, E 300 e L 03/19 - / 135 - 155 kW	24-257992 $\frac{1}{H}$		24-258005 $\frac{1}{O}$	with sports suspension; for vehicles without pneumatic suspension; without electronic suspension control
B 8	E 260 L EQ Boost 4-matic, E 350 L EQ Boost 4-matic 03/19 - / 135 - 220 kW	24-265713 $\frac{1}{H}$ 24-265720 $\frac{1}{H}$	 	24-258005 $\frac{1}{O}$	with sports suspension; for left-hand drive vehicles; without electronic suspension control FA: 24-265720; 24-265713
B 8	E 260 L EQ Boost 4-matic, E 350 L EQ Boost 4-matic 03/19 - / 135 - 220 kW	24-273633 $\frac{1}{H}$ 24-265713 $\frac{1}{H}$ 24-273640 $\frac{1}{H}$ 24-265720 $\frac{1}{H}$	 	24-273039 $\frac{1}{O}$	with sports suspension; for right-hand drive vehicles; without electronic suspension control FA: 24-273640; 24-265720; 24-273633; 24-265713
B14	E 260 L EQ Boost, E 300 e L 03/19 - / 135 - 155 kW			47-258037	for vehicles without pneumatic suspension; without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1340 kg
B16 PSS10	E 260 L EQ Boost, E 300 e L 03/19 - / 135 - 155 kW			48-258067	for vehicles without pneumatic suspension; without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 1275 kg RA: Axle load [kg] to 1340 kg
B16 PSS10	E 260 L EQ Boost 4-matic, E 350 L EQ Boost 4-matic 03/19 - / 135 - 220 kW			48-265737	for vehicles without pneumatic suspension; without roadworthy certificate; Threaded Suspension (height adjustable); without electronic suspension control FA: Axle load [kg] to 1280 kg; Lowering ca. [mm]: 20-45 mm RA: Axle load [kg] to 1340 kg; Lowering ca. [mm]: 30-45 mm

MERCEDES-BENZ (BBDC) EQA (H243)

B 4	EQA 260, EQA 300 4-matic 11/21 - / 140 - 168 kW	22-330017 22-330024	 	19-329888 $\frac{1}{O}$	For vehicles with comfort suspension FA: 22-330024; 22-330017
B 4	EQA 260, EQA 300 4-matic 11/21 - / 140 - 168 kW	22-330031 22-330048	 	19-329888 $\frac{1}{O}$	with standard chassis; Vehicle Type: Avantgarde FA: 22-330048; 22-330031
B 6	EQA 260, EQA 300 4-matic 11/21 - / 140 - 168 kW	22-338334 22-338341	 	24-338356 $\frac{1}{O}$	with standard chassis FA: 22-338341; 22-338334

MERCEDES-BENZ (BBDC) EQB (X243)

B 4	EQB 260, EQB 350 4-matic 11/21 - / 140 - 215 kW	22-330017 22-330024	 	19-329888 $\frac{1}{O}$	For vehicles with comfort suspension FA: 22-330024; 22-330017
B 4	EQB 260, EQB 350 4-matic 11/21 - / 140 - 215 kW	22-330031 22-330048	 	19-329888 $\frac{1}{O}$	with standard chassis; Vehicle Type: Avantgarde FA: 22-330048; 22-330031
B 6	EQB 260, EQB 350 4-matic 11/21 - / 140 - 215 kW	22-338334 22-338341	 	24-338356 $\frac{1}{O}$	with standard chassis FA: 22-338341; 22-338334

MERCURY

MERCURY MARINER

B 4	2.3 Hybrid, 2.3 Hybrid 4WD 09/05 - 12/07 116 kW			19-165998 $\frac{1}{O}$	with standard chassis
B 4	2.3 Hybrid, 2.3 Hybrid AWD, 2.5 Hybrid, 2.5 Hybrid AWD 09/07 - 12/11 114 - 116 kW			19-165998 $\frac{1}{O}$	with standard chassis

MINI

MINI MINI (F56)

B 4	Cooper SE / Electric 11/19 - / 75 - 135 kW	22-317520 22-317537	 	19-317540 $\frac{1}{O}$	FA: 22-317537; 22-317520
-----	---	------------------------	------	-------------------------	--------------------------

MINI MINI COUNTRYMAN (F60)

B 4	Cooper SE ALL4 01/17 - / 162 - 165 kW	22-289278 $\frac{1}{X}$ 22-289285 $\frac{1}{X}$	 	19-291260 $\frac{1}{O}$	with standard chassis; without electronic suspension control FA: 22-289285; 22-289278
B 6	Cooper SE ALL4 01/17 - / 162 - 165 kW	22-286437 $\frac{1}{X}$ 22-286444 $\frac{1}{X}$	 	24-286459 $\frac{1}{O}$	without electronic suspension control; with standard chassis FA: 22-286444; 22-286437
B 6	Cooper SE ALL4 01/17 - / 162 - 165 kW	22-286468 $\frac{1}{X}$ 22-286475 $\frac{1}{X}$	 	24-286480 $\frac{1}{O}$	without electronic suspension control; with sports suspension FA: 22-286475; 22-286468


MITSUBISHI
MITSUBISHI OUTLANDER III (GG_W, GF_W, ZJ, ZL, ZK)

B 1	2.4 Hybrid 4WD 09/18 - /	99 kW		12-288823	with standard chassis
B 4	2.0 Hybrid 4WD 01/14 - /	87 kW		19-281605	with standard chassis; →05/15
B 4	2.0 Hybrid 4WD 01/14 - /	87 kW		19-281612	with standard chassis; 06/15→

MITSUBISHI OUTLANDER III Van (GF_W, GG_W)

B 1	Hybrid 4WD 09/18 - /	99 kW		12-288823	with standard chassis
-----	-------------------------	-------	--	-----------	-----------------------

MITSUBISHI OUTLANDER IV (DG, GM_W)

B 4	2.4 Hybrid All-wheel Drive 05/22 - /	98 kW		19-336640	RA: Multilink Axle
B 4	2.4 Hybrid All-wheel Drive 05/22 - /	98 kW	22-336859 22-336866		FA: 22-336866; 22-336859

NISSAN
NISSAN ARIYA (FE0)

B 4	EV, EV e-4ORCE 07/20 - /	160 - 290 kW	22-342638 22-342645		FA: 22-342645; 22-342638
-----	-----------------------------	--------------	------------------------	--	--------------------------

NISSAN LEAF (ZE0)

B 1	Electric 11/10 - /	80 kW	12-307159 12-315659		with standard chassis FA: 12-315659; 12-307159
B 4	Electric 11/10 - /	80 kW	22-324221 22-328632	19-324234	with standard chassis FA: 22-328632; 22-324221

NISSAN LEAF (ZE1)

B 1	Electric 08/17 - /	110 - 160 kW	12-307159 12-315659		with standard chassis FA: 12-315659; 12-307159
B 4	Electric 08/17 - /	110 - 160 kW	22-324245 22-328243	19-324258	with standard chassis FA: 22-328243; 22-324245

NISSAN QASHQAI III (J12)

B 4	1.3 DIG-T All-wheel Drive 04/21 - /	116 kW		19-336640	Multilink Axle; with standard chassis
-----	--	--------	--	-----------	---------------------------------------

NISSAN X-TRAIL III (T32_, T32R, T32RR)

B 4	2.0 Hybrid 10/16 - /	104 - 138 kW	22-251503 22-251510	19-246390	with standard chassis FA: 22-251510; 22-251503
B 4	2.0 Hybrid ALL MODE 4x4-i 11/16 - /	138 kW	22-260543 22-260550	19-246390	FA: 22-260550; 22-260543
B 6	2.0 Hybrid, 2.0 Hybrid ALL MODE 4x4-i 10/16 - /	104 - 138 kW	22-251534 22-251541	24-246385	with standard chassis FA: 22-251541; 22-251534 RA: Multilink Axle

OPEL
OPEL VIVARO C Van (K0)

B 1	VIVARO-E 09/20 - /	100 kW		12-307210	with standard chassis
-----	-----------------------	--------	--	-----------	-----------------------

OPEL CORSA F

B 6	CORSA-e 07/19 - /	100 kW	22-314062 22-325716	24-345347	with standard chassis FA: 22-325716; with sports suspension; 22-314062
-----	----------------------	--------	------------------------	-----------	---

OPEL MOKKA

B 4	MOKKA-e 06/20 - /	100 kW	22-328298 22-328304	19-343488	FA: 22-328304; 22-328298
-----	----------------------	--------	------------------------	-----------	--------------------------

**M
O**



PEUGEOT				
PEUGEOT 208 II (UB_, UP_, UW_, UJ_)				
B 6	e-208 06/19 - /	100 kW	22-314062 22-325716	24-345347 with standard chassis FA: 22-325716; with sports suspension; 22-314062
B12 PK	e-208 06/19 - /	100 kW	46-346391	Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 990 kg RA: Axle load [kg] to 1000 kg
PEUGEOT 508 II (FB_, FH_, F3_)				
B 4	Hybrid 225 08/19 - /	165 kW	22-295477	19-295480 with standard chassis FA: for OE number: 98 280 640 80; for OE number: 98 290 933 80
B 4	Hybrid 225 08/19 - /	165 kW	22-311986	19-295480 with standard chassis FA: for OE number: 98 280 994 80; for OE number: 98 303 909 80
PEUGEOT 508 SW II (FC_, FJ_, F4_)				
B 4	Hybrid 224, PSE Hybrid4 360 08/19 - /	165 - 265 kW	22-311986	19-295480 with standard chassis FA: for OE number: 98 280 994 80; for OE number: 98 303 909 80
PEUGEOT 2008 II (UD_, US_, UY_, UK_)				
B 4	e-2008 09/19 - /	100 kW	22-328298 22-328304	19-330297 FA: 22-328304; 22-328298
PEUGEOT 3008 SUV (MC_, MR_, MJ_, M4_)				
B 4	Hybrid, Hybrid4 10/19 - /	165 - 220 kW	22-275981	19-275970
PEUGEOT PARTNER Box Body/MPV				
B 1	Électrique 06/13 - /	49 kW	12-117932	
B 4	Électrique 06/13 - /	49 kW	22-226716 22-226723 11-270676	19-226750 with standard chassis; 06/08→ FA: 22-226723; 22-226716 RA: Payload to: 600 kg
B 4	Électrique 06/13 - /	49 kW	22-226716 22-226723 11-270676	19-226736 with standard chassis; 06/08→ FA: 22-226723; 22-226716 RA: Payload to: 800 kg; Payload to: 1000 kg
POLESTAR				
POLESTAR POLESTAR 2 (P)				
B 4	EV 04/21 - /	165 - 170 kW	22-335722 22-335739	19-347820 with standard chassis FA: for variant code CK23; 22-335739; 22-335722
B 4	EV 04/21 - /	165 - 170 kW	22-335821 22-335838	19-347820 FA: for variant code CK07; 22-335838; 22-335821
PORSCHE				
PORSCHE CAYENNE (92A)				
B 4	3.0 S E-Hybrid 06/10 - /	245 kW	19-194875 19-194899	19-194882 with standard chassis; for vehicles without pneumatic suspension; without PASM FA: 19-194899; 19-194875
B 4 AMC	3.0 S E-Hybrid 06/10 - /	245 kW	45-240256 45-240263	45-240270 45-240287 for pneumatic suspension vehicles; with electronic suspension control FA: 45-240263; 45-240256 RA: 45-240287; 45-240270
B 6	3.0 S E-Hybrid 06/10 - /	245 kW	24-239943 24-239950	24-197083 for vehicles without pneumatic suspension; without PASM; with standard chassis FA: 24-239950; 24-239943
PORSCHE CAYENNE (9YA)				
B 4	2.0 E-Hybrid AWD, 3.0 E-Hybrid AWD, 4.0 Turbo S E-Hybrid AWD 11/18 - /	284 - 500 kW	22-322036	19-322049 with standard chassis; for coil-spring suspension vehicles; without electronic suspension control
B 6	2.0 E-Hybrid AWD, 3.0 E-Hybrid AWD, 4.0 Turbo S E-Hybrid AWD 11/18 - /	284 - 500 kW	24-323055	24-323048 without electronic suspension control; for coil-spring suspension vehicles; with standard chassis
B 6 DTC	2.0 E-Hybrid AWD, 3.0 E-Hybrid AWD, 4.0 Turbo S E-Hybrid AWD 11/18 - /	284 - 500 kW	26-324753	20-324698 with electronic suspension control; for coil-spring suspension vehicles

PORSCHE					
PORSCHE CAYENNE Coupe (9YB)					
B 4	2.0 E-Hybrid AWD, 3.0 E-Hybrid AWD 01/19 - / 284 - 339 kW	22-322036	19-322049		with standard chassis; for coil-spring suspension vehicles; without electronic suspension control
B 6	2.0 E-Hybrid AWD, 3.0 E-Hybrid AWD 01/19 - / 284 - 339 kW	24-323055	24-323048		without electronic suspension control; for coil-spring suspension vehicles; with standard chassis
B 6 DTC	2.0 E-Hybrid AWD, 3.0 E-Hybrid AWD 01/19 - / 284 - 339 kW	26-324753	20-324698		with electronic suspension control FA: for coil-spring suspension vehicles
B 6 DTC	4.0 Turbo S E-Hybrid AWD 10/19 - / 500 kW		20-324698		RA: with electronic suspension control

PORSCHE PANAMERA (970)					
B 4	3.0 S E-Hybrid 03/11 - 10/16 279 - 306 kW	24-217941	24-217958		with standard chassis; for vehicles without pneumatic suspension; without electronic suspension control; without PASM
B 4 DTC	3.0 S E-Hybrid 03/11 - 10/16 279 - 306 kW	26-217963	26-256436		with standard chassis; for vehicles without pneumatic suspension; with electronic suspension control; with PASM
B 6	3.0 S E-Hybrid 03/11 - 10/16 279 - 306 kW	24-265393	24-265584		with standard chassis; for vehicles without pneumatic suspension; without electronic suspension control; without PASM
B 6 DTC	3.0 S E-Hybrid 03/11 - 10/16 279 - 306 kW	26-265599	26-265605		with standard chassis; for vehicles without pneumatic suspension; with electronic suspension control; with PASM

RENAULT					
RENAULT CAPTUR II (HF_)					
B 4	TCe 160, TCe 140 01/20 - / 103 - 116 kW	22-325914	19-327310		with standard chassis

RENAULT CLIO I (B/C57_, 5/357_)					
B 1	Electric 05/96 - 02/98 21 kW	11-283409			with standard chassis

RENAULT FLUENCE (L3_)					
B 1	Z.E. 02/12 - / 70 kW	12-234196			with standard chassis

RENAULT KANGOO Express (FW0/1_)					
B 1	Z.E. 10/11 - / 44 kW	12-244904			
B 3	Z.E. 10/11 - / 44 kW	37-314903			with standard chassis
B 3	Z.E. 10/11 - / 44 kW	37-314903			with standard chassis
B 3	Z.E. 10/11 - / 44 kW	37-314910			with standard chassis; Trim Level Rapid Maxi; Trim Level 2 Sitzplätze
B 3	Z.E. 10/11 - / 44 kW	37-314927			with standard chassis; Trim Level Rapid Maxi; Trim Level 5 Sitzplätze
B 3	Z.E. 10/11 - / 44 kW	37-314927			with standard chassis; Trim Level Doppelkabine

RENAULT SCÉNIC IV (J9_)					
B 4	1.5 dCi 110 Hybrid Assist 04/17 - / 81 kW	22-277275	19-277288		with standard chassis; Manual Transmission
B 4	1.5 dCi 110 Hybrid Assist 04/17 - / 81 kW	22-283054	19-277288		with standard chassis; Fully Automatic
B 6	1.5 dCi 110 Hybrid Assist 04/17 - / 81 kW	22-277268	24-266369		with standard chassis

RENAULT GRAND SCÉNIC IV (R9_)					
B 4	1.5 dCi 110 Hybrid Assist 04/17 - / 81 kW	22-277275	19-287737		with standard chassis
B 6	1.5 dCi 110 Hybrid Assist 04/17 - / 81 kW	22-277268	24-266369		with standard chassis

RENAULT TWINGO III (BCM_, BCA_)					
B 6	Z.E. 05/20 - / 60 kW	22-248268	24-264426		with standard chassis



RENAULT				
RENAULT TWINGO III (BCM_, BCA_)				
B14	Z.E: 05/20 - /	60 kW	47-248281	with standard chassis; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 750 kg RA: Lowering ca. [mm]: 50 mm; Axle load [kg] to 870 kg
RENAULT ZOE (BFM_)				
B 1	ZOE R75, ZOE 06/12 - /	57 - 100 kW	12-245000	
B 4	ZOE R75, ZOE 06/12 - /	57 - 100 kW	22-324184	19-324197
B 4	ZOE R75, ZOE 06/12 - /	57 - 100 kW	22-326683	
RENAULT ZOE Hatchback Van (BFM_)				
B 4	Electric 04/19 - /	65 - 100 kW	22-324184	19-324197
B 4	Electric 04/19 - /	65 - 100 kW	22-326683	
RENAULT ARKANA I (LCM_, LDN_)				
B 4	1.3 TCe 140, 1.3 TCe 160, 1.6 E-TECH 145 09/20 - /	103 - 116 kW	22-327291 22-327307	19-325835 19-345314

SEAT				
SEAT LEON (KL1)				
B 1	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 11/19 - /	81 - 150 kW	14-292330	with electronic suspension control
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 11/19 - /	81 - 150 kW		19-334042
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 11/19 - /	81 - 150 kW		19-230542
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 11/19 - /	81 - 150 kW	22-230522	not for model X-Perience FA: Strut outside diameter [mm] 50mm; Length 2 [mm]: 548 mm; for PR number: G11; for PR number: G01; for PR number: G07; for PR number: G16; for PR number: G21; for PR number: G24
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 11/19 - /	81 - 150 kW	22-273994	not for model X-Perience FA: Strut outside diameter [mm] 55mm
B 6	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 11/19 - /	81 - 150 kW	35-229872	24-267137
ES	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 11/19 - /	81 - 150 kW	47-327030	with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg
SEAT LEON Sportstourer (KL8)				
B 1	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 03/20 - /	81 - 150 kW	14-292330	with electronic suspension control
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 03/20 - /	81 - 150 kW		19-334042
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 03/20 - /	81 - 150 kW	22-230522	without electronic suspension control; with standard chassis; with sports suspension; with off-road suspension; not for model X-Perience FA: Strut outside diameter [mm] 50mm; Length 2 [mm]: 548 mm; for PR number: G11; for PR number: G01; for PR number: G07; for PR number: G16; for PR number: G21; for PR number: G24
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 03/20 - /	81 - 150 kW		19-230542
B 4	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 03/20 - /	81 - 150 kW	22-273994	with standard chassis; with sports suspension; with off-road suspension; without electronic suspension control; not for model X-Perience FA: Strut outside diameter [mm] 55mm
B 6	1.0 TSI Mild Hybrid, 1.4 TSI e-Hybrid, 1.5 eTSI 03/20 - /	81 - 150 kW	35-229872	24-267137
B12 PK	1.4 TSI e-Hybrid 05/20 - /	150 kW	46-340832	Conditions see certificates; without electronic suspension control; Strut outside diameter [mm] 55mm; Multilink Axle FA: Axle load [kg] to 1095 kg; Lowering ca. [mm]: 35 mm RA: Axle load [kg] to 1055 kg; Lowering ca. [mm]: 30 mm



SEAT

SEAT Mii (KF1, KE1)

B 3	electric 01/20 - /	61 kW	37-312664		with standard chassis
-----	-----------------------	-------	-----------	--	-----------------------

SEAT TARRACO (KN2)

B 1	1.4 e-HYBRID 02/21 - /	180 kW	14-292330		with electronic suspension control
-----	---------------------------	--------	-----------	--	------------------------------------

SKODA

SKODA E-CITIGO (NE1)

B 3	e iv 09/19 - 09/21	61 kW	37-312664		with standard chassis
-----	-----------------------	-------	-----------	--	-----------------------

SKODA ENYAQ iV SUV (5AZ)

B 4	50, 60, 80 10/20 - /	109 - 150 kW	22-338563 $\frac{1}{\times}$	\uparrow 19-324586 $\frac{1}{\circ}$	without electronic suspension control; with standard chassis; Rear Wheel Drive
-----	-------------------------	--------------	------------------------------	--	--

B 4	80X 4x4 10/21 - /	195 kW	22-338587 $\frac{1}{\times}$	\uparrow 19-324586 $\frac{1}{\circ}$	without electronic suspension control; with standard chassis
-----	----------------------	--------	------------------------------	--	--

ES	50, 60, 80 10/20 - /	109 - 150 kW	47-330108		Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Axle load [kg] to 1210 kg; Lowering ca. [mm]: 25-45 mm RA: Axle load [kg] to 1560 kg; Lowering ca. [mm]: 20-40 mm
----	-------------------------	--------------	-----------	--	---

ES	80X 4x4 10/21 - /	195 kW	47-327085		for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates
----	----------------------	--------	-----------	--	--

SKODA ENYAQ iV Coupe (5AC)

B 4	60, 80 07/21 - /	132 - 150 kW	22-338563 $\frac{1}{\times}$	\uparrow 19-324586 $\frac{1}{\circ}$	Rear Wheel Drive
-----	---------------------	--------------	------------------------------	--	------------------

B 4	80X 4x4, RS 07/21 - /	195 - 220 kW	22-338587 $\frac{1}{\times}$	\uparrow 19-324586 $\frac{1}{\circ}$	All-wheel Drive
-----	--------------------------	--------------	------------------------------	--	-----------------

ES	60, 80 07/21 - /	132 - 150 kW	47-330108		Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Axle load [kg] to 1210 kg; Lowering ca. [mm]: 25-45 mm RA: Axle load [kg] to 1560 kg; Lowering ca. [mm]: 20-40 mm
----	---------------------	--------------	-----------	--	---

ES	80X 4x4, RS 07/21 - /	195 - 220 kW	47-327085		Conditions see certificates; for PR number: 1X1; Threaded Suspension (height adjustable)
----	--------------------------	--------------	-----------	--	--

SKODA OCTAVIA IV (NX3, NN3)

B 1	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	14-292330		with electronic suspension control
-----	--	-------------	-----------	--	------------------------------------

B 4	1.0 TSI e-TEC, 1.4 TSI iv, 1.5 TSI e-TEC 06/20 - /	81 - 150 kW	22-344434	\uparrow 19-342023 $\frac{1}{\circ}$	with standard chassis RA: Rigid Axle
-----	---	-------------	-----------	--	---

B 4	1.0 TSI e-TEC, 1.4 TSI iv, 1.5 TSI e-TEC 06/20 - /	81 - 150 kW	22-344434	\uparrow 19-342047 $\frac{1}{\circ}$	with standard chassis RA: Multilink Axle
-----	---	-------------	-----------	--	---

B 4	1.0 TSI e-TEC, 1.4 TSI iv, 1.5 TSI e-TEC 06/20 - /	81 - 150 kW	22-344434	\uparrow 19-342030 $\frac{1}{\circ}$	with sports suspension RA: Multilink Axle; for PR number: 1JE
-----	---	-------------	-----------	--	--

B 6	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	35-229872 $\frac{1}{\times}$	\uparrow 24-267137 $\frac{1}{\circ}$	FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
-----	--	-------------	------------------------------	--	---

ES	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	47-327030		with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg
----	--	-------------	-----------	--	---

SKODA OCTAVIA IV Combi (NX5)

B 4	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	22-344434	\uparrow 19-342023 $\frac{1}{\circ}$	with standard chassis RA: Rigid Axle
-----	--	-------------	-----------	--	---

B 4	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	22-344434	\uparrow 19-342047 $\frac{1}{\circ}$	with standard chassis RA: Multilink Axle
-----	--	-------------	-----------	--	---

B 4	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	22-344434	\uparrow 19-342030 $\frac{1}{\circ}$	with sports suspension RA: Multilink Axle; for PR number: 1JE
-----	--	-------------	-----------	--	--

B 6	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	35-229872 $\frac{1}{\times}$	\uparrow 24-267137 $\frac{1}{\circ}$	FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
-----	--	-------------	------------------------------	--	---

ES	1.0 TSI e-TEC, 1.4 TSI iv, 1.4 TSI RS iv, 1.5 TSI e-TEC 06/20 - /	81 - 180 kW	47-327030		with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg
----	--	-------------	-----------	--	---



SKODA				
SKODA SUPERB III (3V3)				
B12 PK	1.4 TSI IV 08/19 - /	160 kW	46-331052	Conditions see certificates; with General Certification (ABE); without electronic suspension control FA: Lowering ca. [mm]: 30-35 mm; Axle load [kg] to 1075 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1250 kg; without leveling control
ES	1.4 TSI IV 08/19 - /	160 kW	47-327030	with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg
SKODA SUPERB III Estate (3V5)				
ES	1.4 TSI IV 08/19 - /	160 kW	47-327030	with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg

SMART					
SMART FORTWO Coupe (451)					
B 1	electric drive, electric drive Brabus 11/09 - 12/12	20 - 60 kW	12-251391	FA: without ball bearing	
B 4	electric drive, electric drive Brabus 11/09 - 12/12	20 - 60 kW	22-145697	24-126793 $\frac{1}{\circ}$	with standard chassis FA: serie production spring seat must be used
SMART FORTWO Cabrio (451)					
B 1	electric drive, Electric, electric drive Brabus 11/09 - 12/12	20 - 60 kW	12-251391	FA: without ball bearing	
B 4	electric drive, Electric, electric drive Brabus 11/09 - 12/12	20 - 60 kW	22-145697	24-126793 $\frac{1}{\circ}$	with standard chassis FA: serie production spring seat must be used

SMART FORTWO Coupe (453)					
B 1	electric drive / EQ, electric drive 11/16 - /	41 - 60 kW	12-303885	with standard chassis	
B 4	electric drive / EQ, electric drive 11/16 - /	41 - 60 kW	22-248244 $\frac{1}{\downarrow}$	19-248257 $\frac{1}{\circ}$	with standard chassis
B 6	electric drive / EQ, electric drive 11/16 - /	41 - 60 kW	22-248268 $\frac{1}{\downarrow}$	24-264426 $\frac{1}{\circ}$	with standard chassis
B14	electric drive / EQ, electric drive 11/16 - /	41 - 60 kW	47-248281	with standard chassis; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 750 kg RA: Lowering ca. [mm]: 20-50 mm; Axle load [kg] to 870 kg	

SMART FORFOUR Hatchback (453)					
B 1	electric drive / EQ, electric drive 05/17 - /	41 - 60 kW	12-303885	with standard chassis	
B 4	electric drive / EQ, electric drive 05/17 - /	41 - 60 kW	22-248244 $\frac{1}{\downarrow}$	19-248257 $\frac{1}{\circ}$	with standard chassis
B 6	electric drive / EQ, electric drive 05/17 - /	41 - 60 kW	22-248268 $\frac{1}{\downarrow}$	24-264426 $\frac{1}{\circ}$	with standard chassis
B14	electric drive / EQ, electric drive 05/17 - /	41 - 60 kW	47-248281	with standard chassis; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 750 kg RA: Lowering ca. [mm]: 50 mm; Axle load [kg] to 870 kg	

SMART FORTWO Convertible (453)					
B 1	electric drive / EQ, electric drive 11/16 - /	41 - 60 kW	12-303885	with standard chassis	
B 4	electric drive / EQ, electric drive 11/16 - /	41 - 60 kW	22-248244 $\frac{1}{\downarrow}$	19-248257 $\frac{1}{\circ}$	with standard chassis
B 6	electric drive / EQ, electric drive 11/16 - /	41 - 60 kW	22-248268 $\frac{1}{\downarrow}$	24-264426 $\frac{1}{\circ}$	with standard chassis

STREETSCOOTER				
STREETSCOOTER WORK Van				
B 4	Elektro 01/15 - /	30 kW		19-232560 $\frac{1}{\circ}$



SUBARU

SUBARU XV (_GP_)

B 4	2.0 Hybrid AWD 01/14 - /	110 - 120 kW	22-278340 22-278357		19-278360	with standard chassis FA: 22-278357; 22-278340
B 6	2.0 Hybrid AWD 01/14 - /	110 - 120 kW	22-278371 22-278388		24-278393	with standard chassis FA: 22-278388; 22-278371

SUBARU XV (GT)

B 4	2.0 i e-BOXER AWD 10/19 - /	107 - 110 kW	22-283597 22-283603		19-283616	with standard chassis FA: 22-283603; 22-283597
B 6	2.0 i e-BOXER AWD 10/19 - /	107 - 110 kW	22-283627 22-283634			with standard chassis FA: 22-283634; 22-283627

SUZUKI

SUZUKI IGNIS III (MF)

B 4	1.2 Hybrid, 1.2 Hybrid AllGrip 10/16 - /	61 - 66 kW	22-315571 22-315588		19-315591	with standard chassis FA: 22-315588; 22-315571 RA: 02/16 →
-----	---	------------	------------------------	--	-----------	--

SUZUKI SX4 S-CROSS (JY)

B 4	1.4 Hybrid, 1.4 Hybrid AllGrip 08/19 - /	95 kW	22-282354 22-282361		19-282084	with standard chassis FA: 22-282361; 22-282354
B 6	1.4 Hybrid, 1.4 Hybrid AllGrip 08/19 - /	95 kW	22-282378 22-282385		24-282390	with standard chassis FA: 22-282385; 22-282378

SUZUKI SWIFT V (AZ)

B 4	1.0 SHVS, 1.2 SHVS, 1.4 Sport SHVS, 1.2 Hybrid 01/17 - /	61 - 95 kW	22-277770 22-318978		19-277783	with standard chassis FA: 22-318978; 22-277770
B 6	1.0 SHVS, 1.2 SHVS, 1.4 Sport SHVS, 1.2 Hybrid 01/17 - /	61 - 95 kW	22-277794 22-319142		24-277808	with standard chassis FA: 22-319142; 22-277794

TESLA

TESLA MODEL 3 (5YJ3)

B 4	EV 01/17 - /	175 - 239 kW	22-326607 22-342669		19-326610	without electronic suspension control
B 4	EV AWD, EV Performance AWD, EV Performance AWD, EV 06/18 - /	258 - 377 kW	22-326621 22-342676		19-326610	FA: 22-342676; 22-326621
B 6	EV 01/17 - /	175 - 239 kW	22-622662 22-342683		24-626231	without electronic suspension control FA: 22-342683; 22-622662
B 6	EV AWD, EV Performance AWD, EV Performance AWD, EV 06/18 - /	258 - 377 kW	22-326591 22-342690		24-626231	
ES	EV 01/17 - /	175 - 239 kW			47-318885	FA: Lowering ca. [mm]: 5-45 mm RA: Lowering ca. [mm]: 20-50 mm
ES	EV AWD, EV Performance AWD, EV Performance AWD, EV 06/18 - /	258 - 377 kW			47-326637	without electronic suspension control; Threaded Suspension (height adjustable) FA: Lowering ca. [mm]: 15-40 mm RA: Lowering ca. [mm]: 0-35 mm

TESLA MODEL Y (5YJY)

B 6	EV, EV All-wheel Drive, EV Performance All-wheel Drive, EV Performance All-wheel Drive 03/19 - /	192 - 393 kW	22-326591 22-342690		24-626231	
B 6	EV 03/19 - /	192 - 255 kW	22-622662 22-342683		24-626231	FA: 22-342683; 22-622662
ES	EV All-wheel Drive 03/19 - /	258 kW			47-348615	FA: Lowering ca. [mm]: 15-40 mm RA: Lowering ca. [mm]: 0-35 mm

TOYOTA

TOYOTA AURIS (_E18_)

B 4	1.8 Hybrid 10/12 - 12/18	73 kW	22-168337 22-168344		19-268422	with standard chassis FA: 22-168344; 22-168337
-----	-----------------------------	-------	------------------------	--	-----------	---



TOYOTA				
TOYOTA AURIS Estate (_E18_)				
B 4	1.8 Hybrid 07/13 – 12/18	73 kW	22-168337 22-168344	19-268422 with standard chassis FA: 22-168344; 22-168337
TOYOTA C-HR (_X1_)				
B 4	1.8 Hybrid, 2.0 Hybrid 10/16 – /	90 – 112 kW	22-315601 22-315618	19-315621 with standard chassis FA: 22-315618; 22-315601
TOYOTA C-HR VAN (_X1_)				
B 4	1.8 Hybrid 10/16 – /	72 kW	22-315601 22-315618	19-315621 with standard chassis FA: 22-315618; 22-315601
TOYOTA HIGHLANDER / KLUGER (_U4_)				
B 4	3.5 Hybrid AWD 08/10 – 08/14	209 kW	22-282668 22-282675	22-282705 22-282712 with standard chassis FA: 22-282675; 22-282668 RA: 22-282712; 22-282705
B 6	3.5 Hybrid AWD 08/10 – 08/14	209 kW	22-282729 22-282736	22-282767 22-282774 with standard chassis FA: 22-282736; 22-282729 RA: 22-282774; 22-282767
TOYOTA HIGHLANDER / KLUGER (_U5_)				
B 4	3.5 Hybrid AWD 12/13 – /	209 – 228 kW	22-282835 22-282842	19-282862 with standard chassis FA: 22-282842; 22-282835
TOYOTA PRIUS Saloon (_W1_)				
B 4	1.5 Hybrid 09/00 – 12/03	85 kW	22-196873 22-196880	with standard chassis FA: 22-196880; 22-196873
TOYOTA PRIUS Liftback (_W2_)				
B 1	1.5 Hybrid 09/03 – 12/09	57 – 107 kW		12-248971
B 4	1.5 Hybrid 09/03 – 12/09	57 – 107 kW	22-196651 22-196668	19-196671 with standard chassis FA: 22-196668; 22-196651
TOYOTA PRIUS (_W3_)				
B 4	1.8 Plug-in Hybrid, 1.8 Hybrid 06/08 – /	73 – 132 kW		19-229614 with standard chassis
TOYOTA RAV 4 I (_A1_)				
B 6 4600	Electric EV 06/95 – 12/03	45 – 50 kW	34-030615	24-021203 with standard chassis; Vehicle Type: Electric; 01/98→ FA: for bolted struts only
TOYOTA RAV 4 IV (_A4_)				
B 4	2.5 Hybrid, 2.5 Hybrid 4WD 11/15 – 11/18	145 kW	22-282910 22-282927	19-282930 FA: 22-282927; 22-282910
B 6	2.5 Hybrid, 2.5 Hybrid 4WD 11/15 – 11/18	145 kW	22-282941 22-282958	24-282963 with standard chassis FA: 22-282958; 22-282941
TOYOTA YARIS (_P13_)				
B 1	1.5 Hybrid 03/12 – /	55 kW		12-273218
B 4	1.5 Hybrid 03/12 – /	54 – 55 kW	22-230676 22-230683	19-158150 with off-road suspension; with standard chassis FA: 22-230683; 22-230676
B14	1.5 Hybrid 03/12 – /	54 – 55 kW		47-237834 Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 895 kg RA: Axle load [kg] to 825 kg
TOYOTA YARIS Hatchback Van (_P13_)				
B 4	1.5 Hybrid 04/15 – /	55 kW	22-230676 22-230683	19-158150 with off-road suspension; with standard chassis FA: 22-230683; 22-230676
B14	1.5 Hybrid 04/15 – /	55 kW		47-237834 Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 20-40 mm FA: Axle load [kg] to 895 kg RA: Axle load [kg] to 825 kg


TOYOTA
TOYOTA YARIS (P21, PA1, PH1)

B 4	1.5 HEV, 1.5 Hybrid 02/20 - /	67 - 85 kW	22-329592 22-329608		19-329581	with standard chassis FA: 22-329608; 22-329592
-----	----------------------------------	------------	------------------------	--	-----------	---

VAUXHALL
VAUXHALL CORSA Mk V (F)

B 6	CORSA-e 07/19 - /	100 kW	22-314062 22-325716		24-345347	with standard chassis FA: 22-325716; with sports suspension; 22-314062
-----	----------------------	--------	------------------------	--	-----------	---

B12 PK	CORSA-e 07/19 - /	100 kW	46-346391		Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 990 kg RA: Axle load [kg] to 1000 kg
-----------	----------------------	--------	-----------	--	---

VOLVO
VOLVO C40

B 4	Recharge, Recharge AWD 10/21 - /	170 - 300 kW	22-335722 22-335739		19-347257	FA: for variant code CK23; 22-335739; 22-335722
-----	-------------------------------------	--------------	------------------------	--	-----------	---

VOLVO S90 II (234)

B 4	T8 Hybrid AWD, T8 Hybrid Polestar AWD, T8 Plug-in Hybrid Polestar AWD, T8 Plug-in Hybrid AWD, B4 Mild-Hybrid, B5 Mild-Hybrid, B6 Mild-Hybrid AWD, B5 Mild Hybrid AWD 10/17 - /	145 - 335 kW	24-279123		24-279130	Monotube; without electronic suspension control FA: for OE number: 314 789 71; for OE number: 314 769 71; for OE number: 316 582 52; for OE number: 316 582 53 RA: for OE number: 31476973; for OE number: 31658009; for OE number: 31658010
-----	--	--------------	-----------	--	-----------	--

B 4	T8 Hybrid AWD, T8 Hybrid Polestar AWD, T8 Plug-in Hybrid Polestar AWD, T8 Plug-in Hybrid AWD, B4 Mild-Hybrid, B5 Mild-Hybrid, B6 Mild-Hybrid AWD, B5 Mild Hybrid AWD 10/17 - /	145 - 335 kW	19-279145		19-279152	Twin-Tube; with standard chassis FA: for OE number: 31658242; for OE number: 31658243; for OE number: 31658003; for OE number: 31658002 RA: for OE number: 31476856; for OE number: 31476860; for OE number: 31476861; for OE number: 31476862; for OE number: 31476865
-----	--	--------------	-----------	--	-----------	--

B 6	T8 Hybrid AWD, T8 Hybrid Polestar AWD, T8 Plug-in Hybrid Polestar AWD, T8 Plug-in Hybrid AWD, B4 Mild-Hybrid, B5 Mild-Hybrid, B6 Mild-Hybrid AWD, B5 Mild Hybrid AWD 10/17 - /	145 - 335 kW	24-274852		24-274845	without electronic suspension control
-----	--	--------------	-----------	--	-----------	---------------------------------------

B12 PK	T8 Hybrid AWD, T8 Hybrid Polestar AWD, T8 Plug-in Hybrid Polestar AWD, T8 Plug-in Hybrid AWD 10/17 - /	223 - 335 kW	46-331977		Conditions see certificates FA: Axle load [kg] to 1300 kg; Lowering ca. [mm]: 25 mm RA: Axle load [kg] to 1380 kg; Lowering ca. [mm]: 20 mm
-----------	--	--------------	-----------	--	---

VOLVO V60 I (155)

B 1	D6 Hybrid AWD 06/12 - 12/15	158 kW	12-231614			
-----	--------------------------------	--------	-----------	--	--	--

VOLVO V90 II Estate (235)

B 4	B4 Mild-Hybrid, B5 Mild-Hybrid, B6 Mild-Hybrid AWD, T6 Plug-in-Hybrid AWD, T8 Hybrid AWD, T8 Plug-in Hybrid Polestar AWD, T8 Plug-in-Hybrid AWD, T8 Plug-in Hybrid AWD, B4 Mild-Hybrid AWD, B5 Mild Hybrid AWD 03/16 - 12/18	145 - 335 kW	24-279123		24-279130	Monotube; not for model Cross Country; without electronic suspension control FA: for OE number: 314 789 71; for OE number: 314 769 71; for OE number: 316 582 52; for OE number: 316 582 53 RA: for OE number: 31476973; for OE number: 31658009; for OE number: 31658010
-----	---	--------------	-----------	--	-----------	---

B 6	B4 Mild-Hybrid, B5 Mild-Hybrid, B6 Mild-Hybrid AWD, T6 Plug-in-Hybrid AWD, T8 Hybrid AWD, T8 Plug-in Hybrid Polestar AWD, T8 Plug-in-Hybrid AWD, T8 Plug-in Hybrid AWD, B4 Mild-Hybrid AWD, B5 Mild Hybrid AWD 03/16 - 12/18	145 - 335 kW	24-274852		24-274845	not for model Cross Country; without electronic suspension control
-----	---	--------------	-----------	--	-----------	--

VOLVO V90 II Cross Country (236)

B 4	B5 Mild-Hybrid AWD 03/20 - /	184 kW	24-279123		24-279130	Monotube; not for model Cross Country; without electronic suspension control FA: for OE number: 314 789 71; for OE number: 314 769 71; for OE number: 316 582 52; for OE number: 316 582 53 RA: for OE number: 31476973; for OE number: 31658009; for OE number: 31658010
-----	---------------------------------	--------	-----------	--	-----------	---

B 6	B5 Mild-Hybrid AWD 03/20 - /	184 kW	24-274852		24-274845	not for model Cross Country; without electronic suspension control
-----	---------------------------------	--------	-----------	--	-----------	--

VOLVO XC40 (536)

B 4	Recharge AWD, Recharge 11/20 - /	160 - 300 kW	22-335722 22-335739		19-347257	FA: for variant code CK23; 22-335739; 22-335722
-----	-------------------------------------	--------------	------------------------	--	-----------	---





VOLVO

VOLVO XC60 II (246)

B 4	T8 Hybrid AWD, T8 Hybrid Polestar AWD 03/17 - / 223 - 246 kW	19-282329 $\frac{1}{\times}$		with standard chassis
B 4	T8 Hybrid AWD, T8 Hybrid Polestar AWD 03/17 - / 223 - 246 kW	19-298412 $\frac{1}{\times}$		with standard chassis FA: for OE number: 31658004
B 4	T8 Hybrid AWD, T8 Hybrid Polestar AWD 03/17 - / 223 - 246 kW		19-287461 $\frac{1}{\circ}$	with standard chassis
B 4	T8 Hybrid AWD, T8 Hybrid Polestar AWD 03/17 - / 223 - 246 kW		19-298771 $\frac{1}{\circ}$	with standard chassis
B 4	T8 Hybrid AWD, T8 Hybrid Polestar AWD 03/17 - / 223 - 246 kW		19-298788 $\frac{1}{\circ}$	with standard chassis
B 6	T8 Hybrid AWD, T8 Hybrid Polestar AWD 03/17 - / 223 - 246 kW	19-313115 $\frac{1}{\times}$	24-287487 $\frac{1}{\circ}$	with standard chassis

VOLVO XC90 II (256)

B 4	T8 Hybrid AWD, T8 Twin Engine AWD, B5 Mild-Hybrid AWD 06/15 - 12/18 173 - 298 kW	24-258852 $\frac{1}{\times}$	24-258869 $\frac{1}{\circ}$	with standard chassis; without electronic suspension control; Vehicle Type: C102; Monotube FA: for coil-spring suspension vehicles
B 6	T8 Hybrid AWD, T8 Twin Engine AWD, B5 Mild-Hybrid AWD 06/15 - 12/18 173 - 298 kW	24-254496 $\frac{1}{\times}$	24-254489 $\frac{1}{\circ}$	for coil-spring suspension vehicles; without electronic suspension control

VW

VW ARTEON (3H7, 3H8)

B 1	1.4 eHybrid 11/20 - / 115 kW		12-281459	with electronic suspension control
B 1	1.4 eHybrid 11/20 - / 115 kW		14-292330	with electronic suspension control

VW ARTEON SHOOTING BRAKE (3H9)

B 1	1.4 eHybrid 11/20 - / 115 kW		14-292330	with electronic suspension control
B 4	1.4 eHybrid 11/20 - / 115 kW	22-296245 $\frac{1}{\uparrow}$		with standard chassis

VW CADDY IV MPV (SAB, SAJ)

B 4	ABT e-Caddy 04/20 - / 83 kW		19-313658 $\frac{1}{\circ}$	Wheelbase [mm]: 3002 mm RA: without Xenon light
-----	--------------------------------	--	-----------------------------	--

VW GOLF III (1H1)

B 1	Citystromer 11/94 - 08/97 20 kW	12-244669	12-117239	→to CH-No.: 1H-SW062538; for vehicles with "Basisachse" only RA: without ball bearing
B 4	Citystromer 11/94 - 08/97 20 kW	11-101291 $\frac{1}{\text{PK}}$	11-101352 $\frac{1}{\text{PK}}$	with off-road suspension
B 6	Citystromer 11/94 - 08/97 20 kW	35-043959 $\frac{1}{\uparrow}$ 11-101291 $\frac{1}{\text{PK}}$	11-101352 $\frac{1}{\text{PK}}$ 24-015240 $\frac{1}{\circ}$	with standard chassis FA: Monotube
B 6	Citystromer 11/94 - 08/97 20 kW	35-043959 $\frac{1}{\uparrow}$	11-101352 $\frac{1}{\text{PK}}$ 24-015240 $\frac{1}{\circ}$	without electronic suspension control; with standard chassis FA: Monotube
B 6	Citystromer 11/94 - 08/97 20 kW	35-043959 $\frac{1}{\uparrow}$ 11-101291 $\frac{1}{\text{PK}}$	11-101352 $\frac{1}{\text{PK}}$ 24-015240 $\frac{1}{\circ}$	without electronic suspension control; with standard chassis FA: Twin-Tube
B 6	Citystromer 11/94 - 08/97 20 kW	35-043959 $\frac{1}{\uparrow}$	11-101352 $\frac{1}{\text{PK}}$ 24-006569 $\frac{1}{\circ}$	without electronic suspension control; with standard chassis RA: Length 2 [mm]: 608 mm; Length 1 [mm]: 415 mm
B 8	Citystromer 11/94 - 08/97 20 kW	11-101291 $\frac{1}{\text{PK}}$ 35-043966 $\frac{1}{\uparrow}$	11-101352 $\frac{1}{\text{PK}}$ 24-015295 $\frac{1}{\circ}$	with sports suspension; for vehicles with "Basisachse" only FA: Monotube
B 8	Citystromer 11/94 - 08/97 20 kW	35-043928 $\frac{1}{\uparrow}$ 11-101291 $\frac{1}{\text{PK}}$	24-015295 $\frac{1}{\circ}$ 11-101352 $\frac{1}{\text{PK}}$	with sports suspension; for vehicles with "Plusachse" only FA: Monotube
B14	Citystromer 11/94 - 08/97 20 kW		47-124844	Spacers required for several wheel/tyre combinations; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 990 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 890 kg
B16 PSS9	Citystromer 11/94 - 08/97 20 kW		48-080569	Spacers required for several wheel/tyre combinations; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Lowering ca. [mm]: 30-50 mm; Axle load [kg] to 980 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 840 kg



VW					
VW GOLF VI (5K1)					
B 1	Blue E-Motion 12/10 – 11/13 65 kW	11-270287		with standard chassis; without electronic suspension control	
B 1	Blue E-Motion 12/10 – 11/13 65 kW	14-292330		with electronic suspension control	
VW GOLF VII (5G1, BQ1, BE1, BE2)					
B 1	e-Golf 03/14 – 02/17 85 – 100 kW	14-292330		with electronic suspension control	
B 4	e-Golf 03/14 – 02/17 85 – 100 kW	22-230522		19-275277	without electronic suspension control; with standard chassis; with sports suspension FA: Strut outside diameter [mm] 50mm; Length 2 [mm]: 548 mm; for PR number: G11; for PR number: G01; for PR number: G07; for PR number: G16; for PR number: G21; for PR number: G24 RA: Multilink Axle
B 6	e-Golf, 1.4 GTE Hybrid 03/14 – 02/17 85 – 110 kW	35-229872		24-267137	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
B12 PK	1.4 GTE Hybrid 05/14 – / 110 kW	46-340122		Strut outside diameter [mm] 55mm; Multilink Axle	
ES	e-Golf, 1.4 GTE Hybrid 03/14 – 02/17 85 – 110 kW	47-327030		with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1090 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 980 kg	
VW GOLF VIII (CD1)					
B 1	1.0 eTSI, 1.4 TSI eHybrid, 1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 81 – 180 kW	14-292330		with electronic suspension control	
B 4	1.0 eTSI, 1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 81 – 180 kW	22-297716		without electronic suspension control; with standard chassis; with sports suspension; with off-road suspension FA: Strut outside diameter [mm] 55mm	
B 4	1.0 eTSI, 1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 81 – 180 kW	22-230522		without electronic suspension control; with standard chassis; with sports suspension; with off-road suspension FA: Strut outside diameter [mm] 50mm; Length 2 [mm]: 548 mm; for PR number: G11; for PR number: G01; for PR number: G07; for PR number: G16; for PR number: G21; for PR number: G24	
B 4	1.0 eTSI 06/20 – / 81 kW			19-328645	with standard chassis; Rigid Axle
B 4	1.0 eTSI 06/20 – / 81 kW			19-230542	with sports suspension RA: Rigid Axle; for PR number: 1JA; for PR number: 1JC; for PR number: 0K0; Piston conrod diameter [mm] 11mm
B 4	1.0 eTSI 06/20 – / 81 kW			19-232157	for vehicles with increased ground clearance RA: Rigid Axle
B 4	1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 110 – 180 kW			19-252391	with standard chassis; Multilink Axle
B 4	1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 110 – 180 kW			19-230559	Multilink Axle; with sports suspension RA: without leveling control; Length 1 [mm]: 399 mm; Length 2 [mm]: 625 mm
B 4	1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 110 – 180 kW			19-276977	with standard chassis; with sports suspension; for PR number: 0K4; Multilink Axle RA: without leveling control
B 4	1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 110 – 180 kW			19-297699	Multilink Axle; for vehicles with increased ground clearance
B 6	1.0 eTSI, 1.4 TSI eHybrid, 1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 81 – 180 kW	35-229872		24-267137	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
B12 PK	1.5 eTSI 12/19 – / 110 kW	46-341037		Conditions see certificates; without electronic suspension control; Multilink Axle; Strut outside diameter [mm] 55mm; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1095 kg RA: Axle load [kg] to 1025 kg	
ES	1.0 eTSI, 1.4 TSI eHybrid, 1.4 GTE Plug-in Hybrid, 1.5 eTSI 12/19 – / 81 – 180 kW	47-327030		with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1090 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 980 kg	
ER	1.0 eTSI 06/20 – / 81 kW	89-313022		with standard chassis; with sports suspension; without roadworthy certificate; Multilink Axle; Strut outside diameter [mm] 55mm; not permitted on public roads; with suspension strut support bearing; Lowering ca. [mm]: 30-70 mm	
VW GOLF VIII Variant (CG5)					
B 4	1.0 eTSI, 1.5 eTSI 09/20 – / 81 – 110 kW	22-297716		without electronic suspension control; with standard chassis; with sports suspension; with off-road suspension FA: Strut outside diameter [mm] 55mm	



VW					
VW GOLF VIII Variant (CG5)					
B 4	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 110 kW	22-230522	↑	without electronic suspension control; with standard chassis; with sports suspension; with off-road suspension FA: Strut outside diameter [mm] 50mm; Length 2 [mm]: 548 mm; for PR number: G11; for PR number: G01; for PR number: G07; for PR number: G16; for PR number: G21; for PR number: G24	
B 4	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 96 kW		19-328645 ⚙️	with standard chassis; Rigid Axle	
B 4	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 96 kW		19-230542 ⚙️	with sports suspension RA: Rigid Axle; for PR number: 1JA; for PR number: 1JC; for PR number: 0K0; Piston conrod diameter [mm] 11mm	
B 4	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 96 kW		19-232157 ⚙️	for vehicles with increased ground clearance RA: Rigid Axle	
B 4	1.5 eTSI 12/20 - / 110 kW		19-252391 ⚙️	with standard chassis; Multilink Axle	
B 4	1.5 eTSI 12/20 - / 110 kW		19-230559 ⚙️	Multilink Axle; with sports suspension RA: without leveling control; Length 1 [mm]: 399 mm; Length 2 [mm]: 625 mm	
B 4	1.5 eTSI 12/20 - / 110 kW		19-297699 ⚙️	Multilink Axle; for vehicles with increased ground clearance	
B 4	1.5 eTSI 12/20 - / 110 kW		19-276977 ⚙️	with standard chassis; with sports suspension; for PR number: 0K4; Multilink Axle RA: without leveling control	
B 6	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 110 kW	35-229872 ⚙️	↑	24-267137 ⚙️	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: Multilink Axle
B12 PK	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 110 kW	46-332448		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 990 kg RA: Axle load [kg] to 1030 kg	
B12 PK	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 110 kW	46-332455		Conditions see certificates; without electronic suspension control; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 990 kg RA: Axle load [kg] to 1030 kg	
B12 PK	1.5 eTSI 12/20 - / 96 - 110 kW	46-332462		Conditions see certificates; without electronic suspension control; disconnect DCC; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1090 kg RA: Axle load [kg] to 1030 kg	
B12 PK	1.5 eTSI 12/20 - / 96 - 110 kW	46-332479		Conditions see certificates; without electronic suspension control; disconnect DCC; Lowering ca. [mm]: 30 mm FA: Axle load [kg] to 1090 kg RA: Axle load [kg] to 1030 kg	
ES	1.0 eTSI, 1.5 eTSI 09/20 - / 81 - 110 kW	47-327030		with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1090 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 980 kg	
VW ID.3 (E11)					
B 4	Pure, Pro, 1st, Pro S 11/19 - / 93 - 150 kW	22-323521 ⚙️	↑	19-323510 ⚙️	without electronic suspension control
B 6	Pure, Pro, 1st, Pro S 11/19 - / 93 - 150 kW	22-323606 ⚙️	↑	24-323604 ⚙️	without electronic suspension control; with sports suspension
ES	Pure, Pro, 1st, Pro S 11/19 - / 93 - 150 kW	47-324466		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates	
VW ID.4 (E21)					
B 4	Pure, Pure Performance, Pro, Performance 05/20 - / 109 - 150 kW	22-327123 ⚙️	↑	19-324586 ⚙️	without electronic suspension control FA: for PR number: 1X2
B 4	PRO, GTX 05/21 - / 195 - 220 kW	22-330079 ⚙️	↑	19-324586 ⚙️	without electronic suspension control FA: for PR number: 1X1
B 6	Pure, Pure Performance, Pro, Performance 05/20 - / 109 - 150 kW	22-330055 ⚙️	↑	24-324595 ⚙️	without electronic suspension control; with sports suspension
B 6	PRO, GTX 05/21 - / 195 - 220 kW	22-327130 ⚙️	↑	24-324595 ⚙️	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	PRO, GTX 05/21 - / 195 - 220 kW	47-327085		for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates	
VW ID.5 (E39)					
B 4	Pro, Pro Performance 07/21 - / 128 - 150 kW	22-327123 ⚙️	↑	19-324586 ⚙️	without electronic suspension control FA: for PR number: 1X2
B 4	GTX 08/21 - / 220 kW	22-330079 ⚙️	↑	19-324586 ⚙️	without electronic suspension control FA: for PR number: 1X1



VW						
VW ID.5 (E39)						
B 6	Pro, Pro Performance 07/21 - /	128 – 150 kW	22-330055		24-324595	without electronic suspension control; with sports suspension
B 6	GTX 08/21 - /	220 kW	22-327130		24-324595	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	Pro, Pro Performance 07/21 - /	128 – 150 kW	47-330108			Conditions see certificates; Threaded Suspension (height adjustable); without electronic suspension control FA: Axle load [kg] to 1210 kg; Lowering ca. [mm]: 25-45 mm RA: Axle load [kg] to 1560 kg; Lowering ca. [mm]: 20-40 mm
ES	GTX 08/21 - /	220 kW	47-327085			for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates
VW ID. Buzz Bus						
B 4	Electric 05/22 - /	150 kW	22-344540			without electronic suspension control; Rear Wheel Drive FA: for PR number: 1X2
B 6	Electric 05/22 - /	150 kW	22-340634		24-340663	without electronic suspension control
B12 PK	Electric 05/22 - /	150 kW	46-349651			Wheelbase [mm]: 2989 mm; Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1475 kg; Lowering ca. [mm]: 25 mm RA: Axle load [kg] to 20 kg; Lowering ca. [mm]: 20 mm
VW ID. Buzz Van						
B 6	Electric 05/22 - /	150 kW	22-340634		24-340663	without electronic suspension control
B12 PK	Electric 05/22 - /	150 kW	46-349651			Wheelbase [mm]: 2989 mm; Conditions see certificates; without electronic suspension control FA: Axle load [kg] to 1475 kg; Lowering ca. [mm]: 25 mm RA: Axle load [kg] to 20 kg; Lowering ca. [mm]: 20 mm
VW JETTA IV (162, 163, AV3, AV2)						
B 1	1.4 TSI Hybrid 04/11 - /	110 kW	11-270287			with standard chassis; with sports suspension
B 1	1.4 TSI Hybrid 04/11 - /	110 kW			11-115755	with standard chassis; with sports suspension; for PR number: 1JA; for PR number: 1JD; for PR number: 1JF; for PR number: UB2
B 1	1.4 TSI Hybrid 04/11 - /	110 kW	12-244942		12-224081	FA: for OE number: 1K0 412 331 B RA: without ball bearing
B 4	1.4 TSI Hybrid 04/11 - /	110 kW	22-131607		19-127439	with standard chassis; without electronic suspension control FA: for PR number: G46; for PR number: G57; for PR number: G10; Strut outside diameter [mm] 50mm RA: without leveling control
B 4	1.4 TSI Hybrid 04/11 - /	110 kW	22-131614		19-127439	with standard chassis; without electronic suspension control FA: for PR number: G47; for PR number: G57; Strut outside diameter [mm] 55mm; Parameter: 146/64 RA: without leveling control
B 4	1.4 TSI Hybrid 04/11 - /	110 kW	22-139184		19-127439	with sports suspension; without electronic suspension control FA: for PR number: G10; for PR number: G46; for PR number: G57; Strut outside diameter [mm] 50mm RA: without leveling control
B 4	1.4 TSI Hybrid 04/11 - /	110 kW	22-139191		19-127439	with sports suspension; without electronic suspension control FA: for PR number: G47; for PR number: G57; Strut outside diameter [mm] 55mm RA: without leveling control
B 6	1.4 TSI Hybrid 04/11 - /	110 kW	35-250845		24-172936	without electronic suspension control FA: for PR number: G10; for PR number: G46; for PR number: G57; Strut outside diameter [mm] 50mm RA: without leveling control; Length [mm]: 631,5 mm; Length 2 [mm]: 583,5 mm; Length 1 [mm]: 371 mm
B 6	1.4 TSI Hybrid 04/11 - /	110 kW	35-108177		24-172936	without electronic suspension control FA: for PR number: G47; for PR number: G57; Strut outside diameter [mm] 55mm RA: without leveling control; Length [mm]: 631,5 mm; Length 2 [mm]: 583,5 mm; Length 1 [mm]: 371 mm
B 8	1.4 TSI Hybrid 04/11 - /	110 kW	35-250869		24-178006	without electronic suspension control FA: for PR number: G46; for PR number: G57; for PR number: G10; Strut outside diameter [mm] 50mm RA: without leveling control
B 8	1.4 TSI Hybrid 04/11 - /	110 kW	35-108191		24-178006	without electronic suspension control FA: for PR number: G47; for PR number: G57; Strut outside diameter [mm] 55mm RA: without leveling control
B12 PK	1.4 TSI Hybrid 04/11 - /	110 kW	46-259370			Conditions see certificates; without electronic suspension control; disconnect DCC; Strut outside diameter [mm] 50mm; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 990 kg; for PR number: G46; for PR number: G57; for PR number: G10 RA: Axle load [kg] to 1080 kg



VW

VW JETTA IV (162, 163, AV3, AV2)

B12 PK	1.4 TSI Hybrid 04/11 - /	110 kW	46-259400	Conditions see certificates; without electronic suspension control; disconnect DCC; Strut outside diameter [mm] 55mm; Lowering ca. [mm]: 25 mm FA: Axle load [kg] to 990 kg; for PR number: G46; for PR number: G57; for PR number: G10 RA: Axle load [kg] to 1080 kg
B14	1.4 TSI Hybrid 04/11 - /	110 kW	47-127708	disconnect DCC; Strut outside diameter [mm] 55mm; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Multilink Axle; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1210 kg; for PR number: G47; for PR number: G57 RA: Axle load [kg] to 1100 kg
B16 PSS10	1.4 TSI Hybrid 04/11 - /	110 kW	48-135238	disconnect DCC; Threaded Suspension (height adjustable); Strut outside diameter [mm] 50mm; without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1210 kg; for PR number: G46; for PR number: G57; for PR number: G10 RA: Axle load [kg] to 1100 kg
B16 PSS10	1.4 TSI Hybrid 04/11 - /	110 kW	48-135245	disconnect DCC; Strut outside diameter [mm] 55mm; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1210 kg; for PR number: G07; for PR number: G08; for PR number: G47; for PR number: G57 RA: Axle load [kg] to 1100 kg

VW PASSAT B8 (3G2, CB2)

B 1	1.4 GTE Hybrid 06/15 - 11/18	115 kW	12-243945	FA: without ball bearing	
B 1	1.4 GTE Hybrid 06/15 - 11/18	115 kW	12-281459	with electronic suspension control	
B 1	1.4 GTE Hybrid 06/15 - 11/18	115 kW	14-292330	with electronic suspension control	
B 3	1.4 GTE Hybrid 06/15 - 11/18	115 kW	37-309213	36-301942	with standard chassis
B 4	1.4 GTE Hybrid 06/15 - 11/18	115 kW	22-230539	19-253428	with off-road suspension FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 6	1.4 GTE Hybrid 06/15 - 11/18	115 kW	35-229919	24-267137	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32 RA: Multilink Axle
ES	1.4 GTE Hybrid 06/15 - 11/18	115 kW	47-327030	with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg	

VW PASSAT B8 Variant (3G5, CB5)

B 1	1.4 GTE Hybrid 06/15 - /	115 kW		12-281459	without electronic suspension control
B 1	1.4 GTE Hybrid 06/15 - /	115 kW		14-292330	with electronic suspension control
B 3	1.4 GTE Hybrid 06/15 - /	115 kW	37-309213	36-301942	with standard chassis
B 4	1.4 GTE Hybrid 06/15 - /	115 kW	22-230539	19-253428	with off-road suspension FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 4 DTC	1.4 GTE Hybrid 06/15 - /	115 kW	23-238978	20-267520	with electronic suspension control FA: Strut outside diameter [mm] 55mm; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Multilink Axle
B 6	1.4 GTE Hybrid 06/15 - /	115 kW	35-229919	24-229890	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32 RA: for PR number: 0N4; Multilink Axle; without leveling control
B 6 DTC	1.4 GTE Hybrid 06/15 - /	115 kW	23-254343	20-267537	with electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Multilink Axle



VW			
VW PASSAT B8 Variant (3G5, CB5)			
B12 PK	1.4 GTE Hybrid 06/15 - / 115 kW	46-280749	Conditions see certificates; with General Certification (ABE); without electronic suspension control FA: Lowering ca. [mm]: 30-35 mm; Axle load [kg] to 1200 kg RA: Lowering ca. [mm]: 30 mm; Axle load [kg] to 1250 kg; without leveling control
ES	1.4 GTE Hybrid 06/15 - / 115 kW	47-327030	with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1140 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 1230 kg
VW TIGUAN (AD1, AX1)			
B 1	1.4 eHybrid 11/20 - / 110 kW	12-273096 12-243945	FA: without ball bearing
B 1	1.4 eHybrid 11/20 - / 110 kW		12-281459 with electronic suspension control
B 1	1.4 eHybrid 11/20 - / 110 kW	12-273096 12-243945	FA: without ball bearing
B 1	1.4 eHybrid 11/20 - / 110 kW	14-292330	with electronic suspension control
B16 DTC	1.4 eHybrid 11/20 - / 110 kW	49-255874	Strut outside diameter [mm] 55mm; Multilink Axle; Threaded Suspension (height adjustable); with electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: for PR number: G02; for PR number: G04; Axle load [kg] to 1120 kg RA: Axle load [kg] to 1230 kg
VW TOUAREG (7P5, 7P6)			
B 4	3.0 V6 TSI Hybrid 04/10 - 03/18 245 kW	19-189666 $\frac{1}{H}$ 19-189673 $\frac{1}{H}$	19-189680 $\frac{1}{O}$ with standard chassis; for vehicles without pneumatic suspension; without electronic suspension control FA: 19-189673; 19-189666
B 4	3.0 V6 TSI Hybrid 04/10 - 03/18 245 kW	19-189697 $\frac{1}{H}$ 19-189703 $\frac{1}{H}$	19-189710 $\frac{1}{O}$ with sports suspension; with off-road suspension; for vehicles without pneumatic suspension; without electronic suspension control FA: 19-189703; 19-189697
B 4 AMC	3.0 V6 TSI Hybrid 04/10 - 03/18 245 kW	45-240256 $\frac{1}{H}$ 45-240263 $\frac{1}{H}$	45-240270 $\frac{1}{O}$ 45-240287 $\frac{1}{O}$ for pneumatic suspension vehicles; with electronic suspension control FA: 45-240263; 45-240256 RA: 45-240287; 45-240270
B 6	3.0 V6 TSI Hybrid 04/10 - 03/18 245 kW	24-239943 $\frac{1}{H}$ 24-239950 $\frac{1}{H}$	24-197083 $\frac{1}{O}$ for vehicles without pneumatic suspension; without electronic suspension control FA: 24-239950; 24-239943
VW TOUAREG (CR7)			
B 4	3.0 R 4motion, 3.0 eHybrid 4motion, eHybrid 4motion 09/20 - / 250 - 270 kW	19-321387 $\frac{1}{X}$	19-322346 $\frac{1}{O}$ with standard chassis; for coil-spring suspension vehicles; without electronic suspension control
B 6	3.0 R 4motion, 3.0 eHybrid 4motion, eHybrid 4motion 09/20 - / 250 - 270 kW	24-323055 $\frac{1}{X}$	24-327756 $\frac{1}{O}$ without electronic suspension control; for coil-spring suspension vehicles
VW UP! (121, 122, BL1, BL2, BL3, 123)			
B 1	e-Up 07/13 - / 60 - 61 kW	12-244911	→06/16
B 3	e-Up 07/13 - / 60 - 61 kW	37-312664	36-301744 with standard chassis
VW LOAD UP (121, 122, BL1, BL2)			
B 1	e-Load Up 12/14 - / 60 kW	12-244911	→07/16
VW TRANSPORTER VI / CARAVELLE VI Bus (SGB, SGJ, SHB, SHJ)			
B 6	ABT e-Caravelle 01/20 - / 83 kW	22-318268 $\frac{1}{X}$	24-263894 $\frac{1}{O}$ FA: with standard chassis; with off-road suspension; 10/19→; Vehicle Type: T6.1
B 6	ABT e-Caravelle 01/20 - / 83 kW	22-318275 $\frac{1}{J}$	24-263894 $\frac{1}{O}$ FA: 10/19→; Vehicle Type: T6.1 RA: without electronic suspension control
VW TRANSPORTER VI Van (SGA, SGH, SHA, SHH)			
B 6	ABT e-Transporter 01/20 - / 83 kW	22-319944 $\frac{1}{X}$	24-263894 $\frac{1}{O}$ FA: with sports suspension; 10/19→; Vehicle Type: T6.1
VW MULTIVAN T7 (STM, STN)			
B 4	1.4 e-Hybrid 08/21 - / 160 kW	22-329554 $\frac{1}{J}$	24-336178 $\frac{1}{O}$
B 6	1.4 e-Hybrid 08/21 - / 160 kW	22-329530 $\frac{1}{J}$	24-328500 $\frac{1}{O}$



VW				
VW MULTIVAN T7 (STM, STN)				
ES	1.4 e-Hybrid 08/21 - /	160 kW	47-319318	Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates FA: Axle load [kg] to 1520 kg; Lowering ca. [mm]: 30-50 mm RA: Axle load [kg] to 1475 kg; Lowering ca. [mm]: 30-55 mm

VW (FAW)
VW (FAW) BORA (C52)

B 1	EV 10/19 - /	100 kW	12-243945		FA: without ball bearing	
B 4	EV 10/19 - /	100 kW	22-230522	↑	19-230542 ⚬	without electronic suspension control; with standard chassis; with sports suspension FA: Strut outside diameter [mm] 50mm; Length 2 [mm]: 548 mm RA: for PR number: 0N1; Rigid Axle; Piston conrod diameter [mm] 11mm
B 6	EV 10/19 - /	100 kW	35-229865 ⚬	↑	24-229883 ⚬	without electronic suspension control FA: Strut outside diameter [mm] 50mm; Length 2 [mm]: 548 mm RA: for PR number: 0N1; Rigid Axle
B 8	EV 10/19 - /	100 kW	35-229902 ⚬	↑	24-229920 ⚬	without electronic suspension control FA: Strut outside diameter [mm] 50mm; for PR number: G01; for PR number: G07; for PR number: G16; for PR number: G21; for PR number: G24 RA: for PR number: 0N1; Rigid Axle

VW (FAW) ID.4 CROZZ (E61)

B 4	EV 01/21 - /	125 - 150 kW	22-327123 ⚬	↑	19-324586 ⚬	without electronic suspension control FA: for PR number: 1X2
B 4	EV All-wheel Drive 01/21 - /	230 kW	22-330079 ⚬	↑	19-324586 ⚬	without electronic suspension control FA: for PR number: 1X1
B 6	EV All-wheel Drive 01/21 - /	230 kW	22-327130 ⚬	↑	24-324595 ⚬	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	EV All-wheel Drive 01/21 - /	230 kW	47-327085			for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates

VW (FAW) ID.6 CROZZ (E71)

B 4	EV 07/21 - /	132 - 150 kW	22-327123 ⚬	↑	19-324586 ⚬	without electronic suspension control FA: for PR number: 1X2
B 4	EV 07/21 - /	230 kW	22-330079 ⚬	↑	19-324586 ⚬	without electronic suspension control FA: for PR number: 1X1
B 6	EV 07/21 - /	230 kW	22-327130 ⚬	↑	24-324595 ⚬	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	EV 07/21 - /	230 kW	47-327085			for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates

VW (FAW) MAGOTAN (B8L, OB2, OB3)

B 1	GTE Hybrid 12/19 - /	155 kW	12-243945			FA: without ball bearing
B 4	GTE Hybrid 12/19 - /	155 kW	22-230539	↑	19-253428 ⚬	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 4	GTE Hybrid 12/19 - /	155 kW	22-230539	↑	19-262727 ⚬	with sports suspension FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control
B 4	GTE Hybrid 12/19 - /	155 kW	22-253415	↑	19-253428 ⚬	with off-road suspension FA: Strut outside diameter [mm] 55mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 4 DTC	GTE Hybrid 12/19 - /	155 kW	23-238978 ⚬	↑	20-267520 ⚬	with electronic suspension control FA: Strut outside diameter [mm] 55mm; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Multilink Axle
B 6	GTE Hybrid 12/19 - /	155 kW	35-229872 ⚬	↑	24-229890 ⚬	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: for PR number: 0N4; Multilink Axle; without leveling control

VW (FAW)					
VW (FAW) MAGOTAN (B8L, OB2, OB3)					
B 6 DTC	GTE Hybrid 12/19 - /	155 kW	23-254343	20-267537	with electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Multilink Axle
B 8	GTE Hybrid 12/19 - /	155 kW	35-229919	24-229937	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32 RA: for PR number: ON4; Multilink Axle; without leveling control
B14	GTE Hybrid 12/19 - /	155 kW	47-251588		Strut outside diameter [mm] 55mm; Threaded Suspension (height adjustable); Multilink Axle; without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1220 kg
B16 PSS10	GTE Hybrid 12/19 - /	155 kW	48-251570 48-609073		Strut outside diameter [mm] 55mm; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Multilink Axle; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1160 kg RA: Axle load [kg] to 1220 kg
B16 DTC	GTE Hybrid 12/19 - /	155 kW	49-255874		Strut outside diameter [mm] 55mm; Multilink Axle; Threaded Suspension (height adjustable); with electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: for PR number: G02; for PR number: G04 RA: for PR number: ON4

VW (SVW)					
VW (SVW) ID.3 (E91)					
B 4	EV 10/21 - /	125 kW	22-323521	19-323510	without electronic suspension control
B 6	EV 10/21 - /	125 kW	22-323606	24-323604	without electronic suspension control; with sports suspension
ES	EV 10/21 - /	125 kW	47-324466		Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates

VW (SVW) ID.4 X (E41)					
B 4	EV 01/21 - /	125 - 150 kW	22-327123	19-324586	without electronic suspension control FA: for PR number: 1X2
B 4	EV All-wheel Drive 01/21 - /	230 kW	22-330079	19-324586	without electronic suspension control FA: for PR number: 1X1
B 6	EV All-wheel Drive 01/21 - /	230 kW	22-327130	24-324595	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	EV All-wheel Drive 01/21 - /	230 kW	47-327085		for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates

VW (SVW) ID.6 X (E51)					
B 4	EV 06/21 - /	132 - 150 kW	22-327123	19-324586	without electronic suspension control FA: for PR number: 1X2
B 4	EV All-wheel Drive 06/21 - /	230 kW	22-330079	19-324586	without electronic suspension control FA: for PR number: 1X1
B 6	EV All-wheel Drive 06/21 - /	230 kW	22-327130	24-324595	without electronic suspension control; with sports suspension FA: Mounting points diameter [mm] 58 mm; for PR number: 1X1
ES	EV All-wheel Drive 06/21 - /	230 kW	47-327085		for PR number: 1X1; Threaded Suspension (height adjustable); Conditions see certificates




VW (SVW) LAVIDA (OC1, OE1)					
B 1	EV 08/19 - /	100 kW	12-243945		FA: without ball bearing
B 3	EV 08/19 - /	100 kW	37-293130	36-301935	with standard chassis
B 4	EV 08/19 - /	100 kW	22-230539	19-253428	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 4	EV 08/19 - /	100 kW	22-230539	19-262727	with sports suspension FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control



VW (SVW)					
VW (SVW) LAVIDA (OC1, OE1)					
B 4	EV 08/19 - / 100 kW	22-253415	↑	19-253428 ♂	with off-road suspension FA: Strut outside diameter [mm] 55mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 4 DTC	EV 08/19 - / 100 kW	23-238978 ♂	↑	20-267520 ♂	with electronic suspension control FA: Strut outside diameter [mm] 55mm; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Multilink Axle
B 6	EV 08/19 - / 100 kW	35-229872 ♂	↑	24-229890 ♂	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: for PR number: ON4; Multilink Axle; without leveling control
B 8	EV 08/19 - / 100 kW	35-229919 ♂	↑	24-229937 ♂	without electronic suspension control; with sports suspension FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32 RA: for PR number: ON4; Multilink Axle; without leveling control
B12 PK	EV 08/19 - / 100 kW	46-280725		Conditions see certificates; without electronic suspension control FA: Lowering ca. [mm]: 30-35 mm; Axle load [kg] to 1200 kg RA: Lowering ca. [mm]: 25 mm; Axle load [kg] to 1250 kg; without leveling control	
B14	EV 08/19 - / 100 kW	47-251588		Strut outside diameter [mm] 55mm; Threaded Suspension (height adjustable); Multilink Axle; without electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1200 kg RA: Axle load [kg] to 1253 kg	
B16 PSS10	EV 08/19 - / 100 kW	48-251570 48-609073		Strut outside diameter [mm] 55mm; Threaded Suspension (height adjustable); without electronic suspension control; Conditions see certificates; Multilink Axle; Lowering ca. [mm]: 30-50 mm FA: Axle load [kg] to 1200 kg RA: Axle load [kg] to 1253 kg	
B16 DTC	EV 08/19 - / 100 kW	49-255874		Strut outside diameter [mm] 55mm; Multilink Axle; Threaded Suspension (height adjustable); with electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: for PR number: G02; for PR number: G04 RA: for PR number: ON4	

VW (SVW) PASSAT B8 (C42, C43)

B 1	430 PHEV 10/18 - / 155 kW	12-243945			FA: without ball bearing
B 1	430 PHEV 10/18 - / 155 kW			12-281459	
B 3	430 PHEV 10/18 - / 155 kW	37-293130		36-301935	with standard chassis
B 4	430 PHEV 10/18 - / 155 kW	22-230539	↑	19-253428 ♂	with standard chassis FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 4	430 PHEV 10/18 - / 155 kW	22-230539	↑	19-262727 ♂	with sports suspension FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: without leveling control
B 4	430 PHEV 10/18 - / 155 kW	22-253415	↑	19-253428 ♂	with off-road suspension FA: Strut outside diameter [mm] 55mm RA: without leveling control; Multilink Axle; Length 1 [mm]: 395 mm; Length 2 [mm]: 634 mm
B 4 DTC	430 PHEV 10/18 - / 155 kW	23-238978 ♂	↑	20-267520 ♂	with electronic suspension control FA: Strut outside diameter [mm] 55mm; Length 2 [mm]: 550 mm; Length 1 [mm]: 372 mm RA: Multilink Axle
B 6	430 PHEV 10/18 - / 155 kW	35-229872 ♂	↑	24-229890 ♂	without electronic suspension control FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32; Length 2 [mm]: 548 mm RA: for PR number: ON4; Multilink Axle; without leveling control
B 6 DTC	430 PHEV 10/18 - / 155 kW	23-254343 ♂	↑	20-267537 ♂	with electronic suspension control FA: Strut outside diameter [mm] 55mm RA: Multilink Axle
B 8	430 PHEV 10/18 - / 155 kW	35-229919 ♂	↑	24-229937 ♂	without electronic suspension control; with sports suspension FA: Strut outside diameter [mm] 55mm; for PR number: G02; for PR number: G06; for PR number: G25; for PR number: G28; for PR number: G29; for PR number: G32 RA: for PR number: ON4; Multilink Axle; without leveling control

			
VW (SVW)			
VW (SVW) PASSAT B8 (C42, C43)			
B16 DTC	430 PHEV 10/18 - / 155 kW	49-255874	Strut outside diameter [mm] 55mm; Multilink Axle; Threaded Suspension (height adjustable); with electronic suspension control; Conditions see certificates; Lowering ca. [mm]: 30-50 mm FA: for PR number: G02; for PR number: G04 RA: for PR number: 0N4
ES	430 PHEV 10/18 - / 155 kW	47-327030	with standard chassis; Multilink Axle; Strut outside diameter [mm] 55mm FA: Lowering ca. [mm]: 20-35 mm; Axle load [kg] to 1090 kg RA: Lowering ca. [mm]: 10-30 mm; Axle load [kg] to 980 kg



Hinweise und Erklärungen.

In allen Zweifelsfällen wenden Sie sich bitte vor dem Umbau an Ihren örtlichen BILSTEIN-Vertriebspartner oder unsere Verkaufsberatung.

BILSTEIN-Stoßdämpfer dürfen immer nur paarweise ausgetauscht werden. Für den Umbau sind Fachwissen und Spezialwerkzeuge erforderlich.

Überlassen Sie die Umrüstung Ihres Fahrzeugs auf BILSTEIN also unbedingt einer Fachwerkstatt. Sie benötigen eine radfreie Hebebühne. Steht Ihnen diese nicht zur Verfügung, ist das Fahrzeug beim Aufbocken unbedingt gegen Verrutschen zu sichern. Auf gar keinen Fall dürfen Arbeiten unter dem Auto durchgeführt werden, wenn es nicht ausreichend gesichert ist. Es drohen sonst schwerste Kopfverletzungen und Quetschungen.

Eine Verwendung darf nur für die in der BILSTEIN-Typenliste ausgewiesene Anwendung erfolgen, da sonst die Funktion des BILSTEIN-Gasdruck-Stoßdämpfers nicht mehr gewährleistet ist. Gleiches gilt für den Fall, dass Stoßdämpfer in einen Schraubstock oder vergleichbare Klemmvorrichtungen eingespannt wurden.

Der BILSTEIN-Gasdruck-Stoßdämpfer darf auf keinen Fall verändert werden, da sonst alle Garantieansprüche und gegebenenfalls auch die Betriebserlaubnis erlöschen. In einem BILSTEIN-Gasdruck-Stoßdämpfer ist die Ölfüllung durch Gas vorgespannt.

Das verbotswidrige Öffnen oder Erhitzen des Stoßdämpfers kann schwerste Verletzungen an den Händen und im Gesicht verursachen. Zum Lösen und Anziehen der Muttern darf kein Schlagschraubendreher verwendet werden; das Befestigungsgewinde wird sonst zerstört. Selbstsichernde Muttern dürfen nur einmal verwendet werden! Fahrwerksfedern sind vorgespannt!

Für den Aus- und Einbau muss ein geeignetes Federspanngerät verwendet werden. Die obere Befestigung darf erst dann gelöst werden, wenn die Feder so weit vorgespannt ist, dass sie von Hand verdreht werden kann. Ein Missachten dieser Anweisung kann Verletzungen im Kopf- und Oberkörperbereich nach sich ziehen.

Alle Befestigungen an Achsbeinen müssen angezogen werden, bevor das Fahrzeug wieder auf den Boden herabgelassen wird. Achten Sie dabei auf eine korrekte Befestigung der Gummipuffer sowie des Schutzrohres.

Alle Original-Anbauteile dürfen nur wiederverwendet werden, wenn sie noch neuwertig sind; ansonsten sind sie durch Neuteile zu ersetzen. Entfernen Sie auf keinen Fall den leichten Ölfilm auf der Dichtung sowie der Kolbenstange. Nach dem Umbau sind Spur, Sturz und ggf. Bremskraftregelung (lastabhängig) und ABS-Sensoren gemäß Werksangaben zu kontrollieren bzw. einzustellen. Die Scheinwerfereinstellung ist ebenfalls zu prüfen und ggf. einzustellen.

Bei der Entsorgung von Altteilen sind die in der Typenliste angeführten Vorschriften zu beachten. Bei Fragen hilft Ihnen unsere Verkaufsberatung oder (nur für Deutschland) die Firma PARTSLIFE GmbH gerne weiter.

PARTSLIFE GmbH
Martin-Behaim-Straße 2, D-63263 Neu-Isenburg
Telefon + 49 (0) 61 02/8 12 92-0, Telefax: -29
info@partslife.de
www.partslife.de

Allgemeine Hinweise BILSTEIN B12 – B16

Für Fahrwerke sind die Hinweise im Gutachten und in der Einbauanleitung unbedingt vor dem Einbau zu beachten. Bei Fahrwerken mit Teilegutachten muss der ordnungsgemäße Einbau der Teile durch einen Sachverständigen (TÜV, DEKRA, KFZ-Sachverständigen) bestätigt werden. Das angegebene Tieferlegungsmaß ist abhängig von der Motorisierung und Ausstattung des Fahrzeuges und kann nicht garantiert werden. Die angegebenen Tieferlegungsdaten resultieren aus dem Teilegutachten. Bei Gewindefahrwerken ist die tiefste zulässige Federtellerposition zur Abnahme nach § 19 StVZO einzustellen. Federtellerpositionen außerhalb des zulässigen Verstellbereiches müssen nach § 21 StVZO vom TÜV neu abgenommen werden. Anhand des Gutachtens ist zu prüfen, ob und ggf. für welche Rad-/Reifenkombinationen Distanzscheiben erforderlich sind.

Spezialwerkzeuge

Spezialwerkzeuge sind nicht im Lieferumfang enthalten!

30er Patronenschlüssel
Bestellnr.: 14-244131

36er Patronenschlüssel
Bestellnr.: 14-244148

Profi-Hakenschlüssel DIN 1810 A 68-75
Bestellnr.: Z4-EWK-9923-HO

Profi-Hakenschlüssel DIN 1810 A 80-90
Bestellnr.: Z4-EWK-9924-HO

Reklamationserfassung

Das Dokument zur Erfassung der Reklamation finden Sie zum Download auf unserer Internetseite www.bilstein.de

Bestellhinweise

Es gelten unsere Liefer- und Zahlungsbedingungen. Alle Angaben unter Vorbehalt, Änderungen sind nicht anzeigepflichtig. Vervielfältigung – auch auszugsweise – ist ohne Zustimmung unzulässig.

Altteile-Entsorgung der BILSTEIN-Gasdruck-Stoßdämpfer

BILSTEIN-Einrohr- und Zweirohr-Gasdruck-Stoßdämpfer dürfen nicht einfach weggeworfen werden. Entsprechend den Unfallverhütungs- und Umweltschutzbestimmungen ist es erforderlich, die Dämpfer drucklos zu machen und den Ölinhalt des Dämpfers sowie die Stoßdämpferteile zu entsorgen (Explosionsgefahr besteht bei Erhitzung über 200 °C). Bei dem nachstehend beschriebenen Entsorgungsablauf ist eine Schutzbrille nach DIN 58211, Teil 2, wie beim Schleifen, zu tragen.

Die Entsorgung geschieht wie folgt:

Abb. 1-3: BILSTEIN-Einrohr-Gasdruck-Stoßdämpfer, Kolbenstangendurchmesser 8 bis 14 mm (Anbauteile, Schutzrohr oder Faltenbalg entfernen) werden auf einer geeigneten Unterlage, z. B. in einem Prisma fixiert und nach der Zeichnung 1 an den drei zu bohrenden Positionen angekört. Zuerst muss der Dämpfer in der Nähe des Dämpferbodens (c) mit einem ca. 5-mm-Bohrer angebohrt werden, damit das Stickstoffgas (bis 25 bar Druck) entweichen kann. Danach sind im angegebenen Abstand (d) zwei Löcher zu bohren, um den Ölfluss zu ermöglichen. In gleicher Weise ist bei BILSTEIN-Einrohr-Federbeinen nach Zeichnung 2 vorzugehen. Als erstes das Außenrohr entfernen. Hier Rohr über der Befestigung (a) (Halterung, Achsschenkel, Schelle) absägen, nicht die Kolbenstange. Sägegrat an den getrennten Teilen entfernen. Rohr über das Chromrohr abziehen. Ebenso ist bei BILSTEIN-Patroneneinsätzen nach Zeichnung 3 vorzugehen. Als erstes das Außenrohr entfernen. Bei (b) das Rohr fassen, umdrehen (Stift nach unten) und kräftig auf eine harte Unterlage stoßen, bis sich das Rohr aus dem Presssitz im Rohrboden löst. Rohr über das Chromrohr abziehen. Die Angaben in den Zeichnungen sind genau zu befolgen.




Abb. 1




Abb. 2




Abb. 3




Abb. 4

Abb. 4: BILSTEIN-Zweirohr-Gasdruck-Stoßdämpfer, Kolbenstangendurchmesser 20 bis 24 mm (Anbauteile, Schutzrohr oder Faltenbalg entfernen) werden auf einer geeigneten Unterlage, z. B. in einem Prisma fixiert und nach der Zeichnung 4 an den zwei zu bohrenden Positionen angekört. Zuerst muss der Dämpfer in der Nähe der Kolbenstangendichtung mit einem 5-mm-Bohrer angebohrt werden, damit das Stickstoffgas entweichen kann (e), weiter bis 15 mm tief bohren (e). Das zweite Loch in angegebener Position bohren (f), (80 mm vom Rohrboden, bei ausgezogener Kolbenstange) 15 mm tief, um den Ölfluss zu ermöglichen. Durch mehrmaliges Bewegen der Kolbenstange wird das Öl aus dem Dämpferrohr gepumpt und in einem dafür zugelassenen Behälter aufgefangen. Das PCB- und PCT-freie Stoßdämpferöl ist nach dem Kreislaufwirtschafts-/Abfallgesetz vom 6.10.1994 zu entsorgen (wie Motoröl). Die drucklos gemachten und vom Stoßdämpferöl befreiten, aber noch mit Öl- und Fettresten behafteten Stoßdämpfer, Federbeine, Patroneneinsätze und deren Einzelteile müssen ebenfalls nach dem Kreislaufwirtschafts-/Abfallgesetz entsorgt werden. Diese Angaben wurden nach bestem Wissen gemacht, unter Berücksichtigung der gültigen Vorschriften. Für jeden Einzelfall können wir keine Gewähr übernehmen. Im Zweifelsfall wenden Sie sich bitte an die Verkaufsberatung der Firma ThyssenKrupp Bilstein GmbH oder an die

PARTSLIFE GmbH

Martin-Behaim-Straße 2, D-63263 Neu-Isenburg

Telefon + 49 (0) 61 02/8 12 92-0, Telefax: -29

info@partslife.de

www.partslife.de